### SAFETY DATA SHEET



Conforms to Regulation (EC) No. 1907/2006 (REACH)

## **RUBIA TIR 9900 FE 5W-30**

**SDS no.** 39334

:

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : RUBIA TIR 9900 FE 5W-30

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Motor oil

1.3 Details of the supplier of the safety data sheet

TOTAL LUBRIFIANTS
562 Avenue du Parc de L'ile
92029 Nanterre Cedex FRANCE
Tél: +33 (0)1 41 35 40 00

Fax: +33 (0)1 41 35 84 71 rm.msds-lubs@total.com

TOTAL UK LIMITED

183 Eversholt St, Kings Cross

London, NW1 1BU UNITED KINGDOM Tel: +44 (0)20 7339 8000 Fax: +44 (0)20 7339 8033 rm.gb-msds@total.co.uk

**Contact** 

H.S.E

1.4 Emergency telephone number

National advisory body/Poison Centre

**Telephone number**: National Poisons Information Service (NPIS): 111

**Supplier** 

**Telephone number**: Emergency telephone: +44 1235 239670

#### SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

**Product definition**: Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Ingredients of unknown

toxicity

: 6.8 percent of the mixture consists of component(s) of unknown acute dermal

toxicity

5.8 percent of the mixture consists of component(s) of unknown acute inhalation

toxicity

Date of revision: Version: 1 United Kingdom (UK) ENGLISH 1/20



SDS no.

39334

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Signal word : No signal word.

**Hazard statements** : No known significant effects or critical hazards.

: Not applicable.

**Precautionary statements** 

Prevention: Not applicable.Response: Not applicable.Storage: Not applicable.Disposal: Not applicable.

Supplemental label

elements

: Contains C14-16-18 Alkyl phenol. May produce an allergic reaction. Safety data

sheet available on request.

Annex XVII - Restrictions on the manufacture,

placing on the market and use of certain dangerous substances, mixtures and

articles

#### 2.3 Other hazards

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification

: Prolonged or repeated contact may dry skin and cause irritation.

### **SECTION 3: Composition/information on ingredients**

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Туре
Distillates (petroleum), hydrotreated heavy paraffinic	REACH #: 01-2119484627-25 EC: 265-157-1 CAS: 64742-54-7	≥50 - ≤75	Asp. Tox. 1, H304	[1]
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil- based	REACH #: 01-2119474878-16 EC: 276-737-9 CAS: 72623-86-0	≤5	Asp. Tox. 1, H304	[1]
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl- 4-hydroxyphenyl)propionate	REACH #: 01-0000015551-76 EC: 406-040-9 CAS: 125643-61-0 Index: 607-530-00-7	≤5	Aquatic Chronic 4, H413	[1]
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil- based	REACH #: 01-2119474889-13 EC: 276-738-4 CAS: 72623-87-1	≤5	Asp. Tox. 1, H304	[1]
bis(nonylphenyl)amine	REACH #: 01-2119488911-28 EC: 253-249-4 CAS: 36878-20-3	≤3	Aquatic Chronic 4, H413	[1]
Distillates (petroleum), solvent- dewaxed heavy paraffinic	REACH #: 01-2119471299-27 EC: 265-169-7	≤3	Asp. Tox. 1, H304	[1]

Date of revision: Version: 1 United Kingdom (UK) ENGLISH 2/20 3/4/2021



SDS no.	39334
•	

Distillates (petroleum), solvent- dewaxed light paraffinic	CAS: 64742-65-0 REACH #: 01-2119480132-48 EC: 265-159-2 CAS: 64742-56-9	≤3	Asp. Tox. 1, H304	[1]
Paraffin oils (petroleum), catalytic dewaxed heavy	REACH #: 01-2119487080-42 EC: 265-174-4 CAS: 64742-70-7	≤3	Asp. Tox. 1, H304	[1]
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)	EC: 298-577-9 CAS: 93819-94-4	<2.5	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 2, H411	[1]
C14-16-18 Alkyl phenol	REACH #: 01-2119498288-19 EC: 931-468-2	≤0.3	Skin Sens. 1B, H317 STOT RE 2, H373	[1]
			See Section 16 for the full text of the H statements declared above.	

**Additional information** 

: Mineral oil of petroleum origin Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### <u>Type</u>

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern
- [6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

**Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Get medical attention if symptoms occur. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be

kept under medical surveillance for 48 hours.

**Skin contact**: Wash skin thoroughly with soap and water or use recognised skin cleanser.

Remove contaminated clothing and shoes. Get medical attention if symptoms occur.

Ingestion : Wash out mouth with water. Remove victim to fresh air and keep at rest in a

position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms

occur.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

Date of revision: Version: 1 United Kingdom (UK) ENGLISH 3/20



**SDS no.** 39334

#### 4.2 Most important symptoms and effects, both acute and delayed

#### Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : No specific data.

**Skin contact**: Adverse symptoms may include the following:

irritation dryness cracking

**Ingestion**: No specific data.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments**: No specific treatment.

### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing

media

: Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

Unsuitable extinguishing

media

: Do not use water jet.

#### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

: In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous combustion

products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides sulfur oxides phosphorus oxides metal oxide/oxides

#### 5.3 Advice for firefighters

Special protective actions

for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without

suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.

Date of revision: Version: 1 United Kingdom (UK) ENGLISH 4/20



SDS no.

39334

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### 6.3 Methods and material for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

6.4 Reference to other

: See Section 1 for emergency contact information.

sections

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

**Protective measures** 

: Put on appropriate personal protective equipment (see Section 8).

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

#### 7.3 Specific end use(s)

Recommendations : Not available. Industrial sector specific

: Not available.

solutions

Date of revision : Version: 1 United Kingdom (UK) **ENGLISH** 5/20



SDS no.

39334

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

#### Occupational exposure limits

No exposure limit value known.

Reportable hazardous constituent(s) contained in UVCB- and/or multi-constituent substance(s) complying with the classification criteria and/or with an exposure limit (OEL)

No exposure limit value known.

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**Advisory OEL** 

: Mineral oil mist: USA: OSHA (PEL) TWA 5 mg/m3, NIOSH (REL) TWA 5 mg/m3, STEL 10 mg/m3, ACGIH (TLV) TWA 5 mg/m3 (highly refined)

#### **DNELs/DMELs**

Product/substance	Type	Exposure	Value	Population	Effects
Distillates (petroleum), hydrotreated heavy paraffinic	DNEL	Long term Inhalation	5.58 mg/m³	Workers	Local
	DNEL	Long term Inhalation	1.19 mg/m³	General population	Local
	DNEL	Long term Oral	740 µg/kg	General population	Systemic
	DNEL	Long term Dermal	970 µg/kg	Workers	Systemic
	DNEL	Long term Inhalation	2.73 mg/m <sup>3</sup>	Workers	Systemic
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	DNEL	Long term Inhalation	5.4 mg/m <sup>3</sup>	Workers	Local
•	DNEL	Long term Inhalation	1.2 mg/m³	General population	Local
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl- 4-hydroxyphenyl)propionate	DNEL	Long term Oral	0.16 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.22 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	0.33 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0.74 mg/m³	General population	Systemic
	DNEL	Long term Inhalation	2.33 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Short term Dermal	20 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Oral	50 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	50 mg/kg	General	Systemic

Date of revision: Version: 1 United Kingdom (UK) ENGLISH 6/20



SDS no.

39334

1	i	1			
			bw/day	population	
	DNEL	Short term	875 mg/m <sup>3</sup>	General	Systemic
		Inhalation		population	
	DNEL	Short term	1750 mg/	Workers	Systemic
		Inhalation	m³		
	DNEL	Long term Dermal	0.006 mg/	Workers	Local
	DNEL	Short term Dermal	cm <sup>2</sup> 1 mg/cm <sup>2</sup>	Workers	Local
Lubricating oils (petroleum), C20-50,	DNEL	Long term	5.4 mg/m <sup>3</sup>	Workers	Local
hydrotreated neutral oil-based	DIVLL	Inhalation	3.4 mg/m	WOIKEIS	Local
.,,	DNEL	Long term	1.2 mg/m <sup>3</sup>	General	Local
		Inhalation	g,	population	
bis(nonylphenyl)amine	DNEL	Long term Oral	0.25 mg/	General	Systemic
		3	kg bw/day	population	,
	DNEL	Long term Dermal	2.5 mg/kg	General	Systemic
		3	bw/day	population	,
	DNEL	Long term Dermal	5 mg/kg	Workers	Systemic
		· ·	bw/day		,
	DNEL	Long term Dermal	0.62 mg/	Workers	Systemic
			kg bw/day		
	DNEL	Long term	4.37 mg/m <sup>3</sup>	Workers	Systemic
		Inhalation			
Distillates (petroleum), solvent-	DNEL	Long term	5.4 mg/m³	Workers	Local
dewaxed heavy paraffinic		Inhalation			
	DNEL	Long term	1.2 mg/m <sup>3</sup>	General	Local
		Inhalation		population	
zinc bis[O-(6-methylheptyl)] bis[O-	DNEL	Long term Oral	0.24 mg/	General	Systemic
(sec-butyl)] bis(dithiophosphate)		l <u>-</u> .	kg bw/day	population	
	DNEL	Long term Dermal	0.29 mg/	General	Systemic
	DATE		kg bw/day	population	0
	DNEL	Long term Dermal	0.58 mg/	Workers	Systemic
	DNEL	Long term	kg bw/day 2.11 mg/m³	General	Systemic
	DIVEL	Inhalation	2.11 mg/m	population	Systemic
	DNEL	Long term	8.31 mg/m <sup>3</sup>	Workers	Systemic
	DINCL	Inhalation	0.01 mg/m	VVOIRGIS	Cysternic
C14-16-18 Alkyl phenol	DNEL	Long term	1.17 mg/m³	Workers	Systemic
O 14 TO TO MINY PROPERTY	DIVLL	Inhalation	1.17 mg/m	VVOINCIS	Cyclonic
	DNEL	Long term Dermal	0.3 mg/kg	Workers	Systemic
	=		bw/day		- ,

### **PNECs**

Product/ingredient name	Compartment Detail	Name	Method Detail
reaction mass of isomers of: C7-9-alkyl 3- (3,5-di-tert-butyl-4-hydroxyphenyl)propionate	Fresh water	0.0043 mg/l	-
	Marine water	0.00043 mg/l	-
	Fresh water sediment	233 mg/kg dwt	-
	Marine water sediment	23.3 mg/kg dwt	-
	Soil	189 mg/kg	-
ois(nonylphenyl)amine	Fresh water	0.1 mg/l	-
	Marine water	0.01 mg/l	-
	Fresh water sediment	132000 mg/kg dwt	-
	Marine water sediment	13200 mg/kg dwt	-
	Soil	263000 mg/kg dwt	-
	Sewage Treatment	1 mg/l	-
	Plant		
zinc bis[O-(6-methylheptyl)] bis[O-(sec- butyl)] bis(dithiophosphate)	Fresh water	0.004 mg/l	-

Date of revision : 3/4/2021 Version: 1 United Kingdom (UK) ENGLISH 7/20



SDS	no.	39334

		0.0046 mg/l	-
		0.0116 mg/kg dwt	-
	Marine water sediment	0.00116 mg/kg	-
		dwt	
	Soil	0.00528 mg/kg	-
	Sewage Treatment	100 mg/l	-
	Plant	_	
C14-16-18 Alkyl phenol	Fresh water	0.1 mg/l	-
	Marine water	0.01 mg/l	-
	Fresh water sediment	4266.16 mg/kg	-
		dwt	
	Marine water sediment	426.62 mg/kg dwt	-
	Soil	852.58 mg/kg dwt	-
	Sewage Treatment	100 mg/l	-
	Plant		

#### 8.2 Exposure controls

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

#### **Individual protection measures**

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

#### **Skin protection**

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Hydrocarbon-proof gloves

nitrile rubber Fluorinated rubber

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

In case of prolonged contact with the product, it is recommended to wear gloves complying with EN 420 and EN 374 standards, protecting at least for 480 minutes and having a thickness of 0,38 mm at least. These values are indicative only. The level of protection is provided by the material of the glove, its technical

characteristics, its resistance to the chemicals to be handled, the appropriateness of its use and its replacement frequency

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Date of revision: Version: 1 United Kingdom (UK) **ENGLISH** 8/20



SDS no. 39334

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Respirator with combination filter for vapour/particulate Type A/P1 Warning! filters have a limited use duration The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses None under normal use conditions

**Environmental exposure** 

controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

#### **Appearance**

Physical state : Liquid.

Colour : Not available. Odour : Characteristic. : Not available. **Odour threshold** рΗ : Not applicable. Melting point/freezing point : Not available. Initial boiling point and : Not available.

boiling range

Flash point

: Open cup: 223°C [ASTM D 92]

: Not available. **Evaporation rate** Flammability (solid, gas) : Not available. Upper/lower flammability or : Not available.

explosive limits

Vapour pressure

: Not available. Vapour density : Not available.

Relative density : 0.84 to 0.86 [ISO 12185]

: Insoluble in the following materials: cold water and hot water. Solubility(ies)

Partition coefficient: n-octanol/ : Not available.

water

: Not available. **Auto-ignition temperature Decomposition temperature** : Not available.

**Viscosity** : Kinematic (40°C): 0.722 cm<sup>2</sup>/s

**Explosive properties** : Not available.

Oxidising properties : This product is not considered oxidising based on chemical structure

considerations

9.2 Other information

Solubility in water : Insoluble

Date of revision: Version: 1 United Kingdom (UK) **ENGLISH** 9/20



SDS no.

39334

### **SECTION 10: Stability and reactivity**

**10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : The product is stable.

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**10.4 Conditions to avoid** : No specific data.

10.5 Incompatible materials : Strong oxidising agents

10.6 Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

### **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

#### **Acute toxicity**

Product/substance	Result	Species	Dose	Exposure	Test
Distillates (petroleum), hydrotreated heavy paraffinic	LC50 Inhalation Dusts and mists	Rat	5.1 mg/l	4 hours	OECD 403
	LD50 Dermal	Rabbit	>5000 mg/kg	-	OECD 402
	LD50 Oral	Rat	>5000 mg/kg	-	OECD 420
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	LC50 Inhalation Dusts and mists	Rat	5.53 mg/l	4 hours	OECD 403
	LD50 Dermal	Rabbit	>2000 mg/kg	-	OECD 402
	LD50 Oral	Rat	>5000 mg/kg	-	OECD 401
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert- butyl-4-hydroxyphenyl) propionate	LD50 Dermal	Rabbit - Male, Female	>2000 mg/kg	-	OECD 402
	LD50 Oral	Rat - Male, Female	>2000 mg/kg	-	OECD 401
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	LC50 Inhalation Dusts and mists	Rat	5.1 mg/l	4 hours	OECD 403
	LD50 Dermal	Rabbit	>5000 mg/kg	-	OECD 402
	LD50 Oral	Rat	>5000 mg/kg	-	OECD 401
bis(nonylphenyl)amine	LC50 Inhalation Dusts and mists	Rat	5.1 mg/l	4 hours	-
	LD50 Dermal	Rat	>2000 mg/kg	-	OECD 402
	LD50 Oral	Rat	>5000 mg/kg	-	OECD 401
Distillates (petroleum), solvent-dewaxed heavy paraffinic	LC50 Inhalation Dusts and mists	Rat	5.1 mg/l	4 hours	OECD 403
	LC50 Inhalation Vapour	Rat	80.1 mg/l	1 hours	-
	LC50 Inhalation Vapour	Rat	20.1 mg/l	4 hours	-
	LD50 Dermal	Rabbit	>5000 mg/kg	-	OECD 402
	LD50 Oral	Rat	>5000 mg/kg	-	OECD 420
Distillates (petroleum), solvent-dewaxed light	LC50 Inhalation Dusts and mists	Rat	5.53 mg/l	4 hours	-

Date of revision: Version: 1 United Kingdom (UK) ENGLISH 10/20



SDS no.

39334

paraffinic		]			l l
paramine	LD50 Dermal	Rabbit	>5000 mg/kg	_	_
	LD50 Dermal	Rabbit	>2000 mg/kg	-	OECD 402
	LD50 Oral	Rat	>5000 mg/kg	-	OECD 401
Paraffin oils (petroleum),	LC50 Inhalation Dusts	Rat	5.1 mg/l	4 hours	-
catalytic dewaxed heavy	and mists				
	LC50 Inhalation Vapour	Rat	80.4 mg/l	1 hours	-
	LC50 Inhalation Vapour	Rat	20.1 mg/l	4 hours	-
	LD50 Dermal	Rabbit	>5000 mg/kg	-	-
	LD50 Oral	Rat	>5000 mg/kg	-	-
zinc bis[O-(6-methylheptyl)]	LC50 Inhalation Dusts	Rat - Male	>2 mg/l	1 hours	OECD 403
bis[O-(sec-butyl)] bis	and mists				
(dithiophosphate)		5	0.4.00 #		0505 400
	LD50 Dermal	Rabbit -	>3160 mg/kg	-	OECD 402
	1.550.0	Male, Female	0000 //		
	LD50 Oral	Rat - Male	2600 mg/kg	-	-
C14-16-18 Alkyl phenol	LD50 Dermal	Rat	2000 mg/kg	-	-
	LD50 Oral	Rat	2000 mg/kg	-	-

#### Conclusion/Summary

: Based on available data, the classification criteria are not met.

#### **Acute toxicity estimates**

Product/substance	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Distillates (petroleum), hydrotreated heavy paraffinic	N/A	N/A	N/A	N/A	5.1
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	N/A	N/A	N/A	N/A	5.53
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	N/A	N/A	N/A	N/A	5.1
bis(nonylphenyl)amine	N/A	N/A	N/A	N/A	5.1
Distillates (petroleum), solvent-dewaxed heavy paraffinic	N/A	N/A	N/A	40.05	5.1
Distillates (petroleum), solvent-dewaxed light paraffinic	N/A	N/A	N/A	N/A	5.53
Paraffin oils (petroleum), catalytic dewaxed heavy zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis (dithiophosphate)	N/A 2600	N/A N/A	N/A N/A	20.1 N/A	5.1 N/A

#### Irritation/Corrosion

Product/substance	Result	Species	Score	Exposure	Test
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert- butyl-4-hydroxyphenyl) propionate	Skin - Oedema	Rabbit	0.1	-	OECD 404
	Eyes - Cornea opacity	Rabbit	0	-	OECD 405
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis (dithiophosphate)	Skin - Irritant	Rabbit	-	4 hours	OECD 404
	Eyes - Irritant	Rabbit	-	-	-

#### **Conclusion/Summary**

**Conclusion/Summary** 

: The supplier of one or more of the components contained within this formulation has indicated that he has data on the components and/or similar mixtures, which confirms that at the concentration used, eye irritation classification is not required

### **Sensitisation**

Date of revision: Version: 1 United Kingdom (UK) ENGLISH 11/20



SDS no.

39334

Product/substance	Route of exposure	Species	Result
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert- butyl-4-hydroxyphenyl) propionate	skin	Guinea pig	Not sensitizing

Conclusion/Summary

**Conclusion/Summary**: Based on available data, the classification criteria are not met.

#### **Mutagenicity**

Product/substance	Test	Experiment	Result
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert- butyl-4-hydroxyphenyl) propionate	OECD 471	Experiment: In vitro Subject: Bacteria	Negative
	OECD 473	Experiment: In vitro Subject: Mammalian-Animal	Negative
	OECD 474	Experiment: In vivo Subject: Mammalian-Animal	Negative
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis (dithiophosphate)	OECD 471	Experiment: In vitro Subject: Bacteria	Negative
	OECD 474	Experiment: In vivo Subject: Mammalian-Animal Cell: Somatic	Negative

**Conclusion/Summary** 

: Based on available data, the classification criteria are not met.

#### Carcinogenicity

Product/substance	Result	Species	Dose	Exposure
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert- butyl-4-hydroxyphenyl) propionate	Negative - Oral - TC	Rat - Male, Female	-	-

**Conclusion/Summary** 

: Based on available data, the classification criteria are not met.

#### **Reproductive toxicity**

Product/substance	Maternal toxicity	Fertility	Developmental toxin	Species	Dose	Exposure
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert- butyl-4-hydroxyphenyl) propionate	Negative	Negative	Negative	Rat - Male, Female	Oral	-
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis (dithiophosphate)	Negative	Negative	Negative	Rat - Male, Female	Oral	1

Conclusion/Summary

: Based on available data, the classification criteria are not met.

#### **Teratogenicity**

Date of revision: Version: 1 United Kingdom (UK) ENGLISH 12/20



SDS no. 39334

Product/substance	Result	Species	Dose	Exposure
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert- butyl-4-hydroxyphenyl) propionate	Negative - Oral	Rabbit	-	-
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis (dithiophosphate)	Negative - Oral	Rat - Male, Female	-	-

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

#### Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

Product/substance	Result
Distillates (petroleum), hydrotreated heavy paraffinic Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	ASPIRATION HAZARD - Category 1
Distillates (petroleum), solvent-dewaxed heavy paraffinic Distillates (petroleum), solvent-dewaxed light paraffinic Paraffin oils (petroleum), catalytic dewaxed heavy	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1

Information on likely routes : Not available.

of exposure

#### Potential acute health effects

Eye contact : No known significant effects or critical hazards. Inhalation : No known significant effects or critical hazards.

**Skin contact** : Defatting to the skin. May cause skin dryness and irritation.

: No known significant effects or critical hazards. Ingestion

#### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data. Inhalation : No specific data.

**Skin contact** : Adverse symptoms may include the following:

irritation dryness cracking

Ingestion : No specific data.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Short term exposure** 

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Date of revision: Version: 1 United Kingdom (UK) **ENGLISH** 13/20



**SDS no**. 39334

**Potential immediate** 

effects

: Not available.

Potential delayed effects : Not available.

#### Potential chronic health effects

Product/substance	Result	Species	Dose	Exposure
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert- butyl-4-hydroxyphenyl) propionate	Sub-acute NOAEL Oral	Rat - Male, Female	5 mg/kg	-
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis (dithiophosphate)	Sub-chronic NOAEL Oral	Rat - Male, Female	160 mg/kg	-
	Sub-chronic LOAEL Dermal	Rabbit - Male, Female	70 mg/kg	-

Conclusion/Summary

: Not available.

General

: Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/

or dermatitis.

Carcinogenicity

: During use in engines, contamination of oil with low levels of combustion products occurs. Used motor oils have been shown to cause skin cancer in mice following repeated application and continuous exposure. Brief or intermittent skin contact with used motor oil is not expected to have serious effects in humans if the oil is thoroughly removed by washing with soap and water.

Mutagenicity: No known significant effects or critical hazards.Teratogenicity: No known significant effects or critical hazards.Developmental effects: No known significant effects or critical hazards.Fertility effects: No known significant effects or critical hazards.

Other information : Not available.

### **SECTION 12: Ecological information**

### 12.1 Toxicity

Product/substance	Result	Species	Exposure	Test
Distillates (petroleum), hydrotreated heavy paraffinic	Acute EC50 >100 mg/l	Algae - Pseudokirchnerella subcapitata	48 hours	OECD 201
	Acute EC50 >10000 mg/l	Daphnia - Daphnia magna	48 hours	OECD 202
	Chronic NOEL 10 mg/l	Daphnia - Daphnia magna	21 days	-
	Chronic NOEL >1000 mg/l	Fish - Oncorhynchus mykiss	21 days	-
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	Acute EC50 >1000 mg/l	Daphnia	48 hours	OECD 202
	Chronic NOEL 10 mg/l	Daphnia	21 days	OECD 202
	Chronic NOEL >1000 mg/l	Fish	14 days	-
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl- 4-hydroxyphenyl)propionate	Acute EC50 >3 mg/l	Algae - Scenedesmus	72 hours	OECD 201
	Acute EC50 >100 mg/l Acute EC50 74.1 mg/l	Daphnia - Daphnia magna Fish	24 hours 96 hours	OECD 202
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	Acute EC50 >100 mg/l	Algae - Pseudokirchnerella subcapitata	48 hours	OECD 201

Date of revision: Version: 1 United Kingdom (UK) ENGLISH 14/20



**SDS no.** 39334

•	ı	٠.
		•

	Acute EC50 >10000 mg/l	Daphnia - Daphnia magna	48 hours	OECD 202
	Acute LC50 >10000 mg/l	Daphnia - Gammarus pulex	24 hours	OECD 202
	Acute LC50 >10000 mg/l	Daphnia - Gammarus pulex	48 hours	OECD 202
	Acute LC50 >10000 mg/l	Daphnia - Gammarus pulex	72 hours	OECD 202
	Acute LC50 >10000 mg/l	Daphnia - Gammarus pulex	96 hours	OECD 202
	Acute NOEL 101 mg/l	Algae	72 hours	OECD 201
	Acute NOEL >100 mg/l	Fish - Pimephales promelas	96 hours	OECD 203
	Chronic NOEL 10 mg/l	Daphnia - Daphnia magna	21 days	OECD 211
	Chronic NOEL >1000 mg/l	Fish - Oncorhynchus mykiss	21 days	-
bis(nonylphenyl)amine	Acute EC50 600 mg/l	Algae - Selenastrum capricornutum	72 hours	-
	Acute EC50 >100 mg/l	Daphnia - Daphnia magna	48 hours	OECD 202
	Acute EC50 >1000 mg/l	Micro-organism	0.1 days	-
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Acute EC50 >100 mg/l	Algae - Pseudokirchnerella subcapitata	72 hours	OECD 201
paraminic	Acute EC50 >10000 mg/l	Daphnia - Daphnia magna	48 hours	OECD 202
	Chronic NOEL 10 mg/l	Daphnia - Daphnia magna	21 days	OECD 211
	Chronic NOEL >1000 mg/l	Fish - Oncorhynchus mykiss	21 days	-
Distillates (petroleum), solvent-dewaxed light paraffinic	Acute EC50 101 mg/l	Algae	72 hours	-
	Acute EC50 10000 mg/l Acute NOEL 101 mg/l	Daphnia - Daphnia magna Algae - (Pseudokirchnerella	48 hours 72 hours	- OECD 201
	Acute NOEL 10 mg/l Acute NOEL ≥100 mg/l	subcapitata Daphnia - Daphnia magna Fish - Pimephales	21 days 96 hours	OECD 211 OECD 203
Paraffin oils (petroleum),	Acute EC50 10000 mg/l	promelas Daphnia	48 hours	-
catalytic dewaxed heavy	Acute NOEL 101 mg/l	Algae - Pseudokirchneriella	72 hours	-
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis (dithiophosphate)	Acute EC50 2.1 mg/l	subcapitata Algae - Selenastrum capricornutum	96 hours	OECD 201
(samophosphato)	Acute EC50 5.4 mg/l Acute LC50 4.5 mg/l	Daphnia - Daphnia magna Fish	48 hours 96 hours	OECD 202
C14-16-18 Alkyl phenol	Acute EC50 >100 mg/l	Daphnia - Daphnia magna	48 hours	OECD 202

### 12.2 Persistence and degradability

**Conclusion/Summary**: Not available.

Date of revision: Version: 1 United Kingdom (UK) ENGLISH 15/20



SDS no.

39334

Product/substance	Aquatic half-life	Photolysis	Biodegradability
Lubricating oils (petroleum), C15-30, hydrotreated	-	-	Not readily
neutral oil-based reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert- butyl-4-hydroxyphenyl)	-	-	Not readily
propionate Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	-	-	Not readily
bis(nonylphenyl)amine Distillates (petroleum), solvent-dewaxed heavy	-	-	Not readily Readily
paraffinic Distillates (petroleum), solvent-dewaxed light paraffinic	-	-	Not readily
Paraffin oils (petroleum), catalytic dewaxed heavy	-	-	Not readily
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis (dithiophosphate)	-	-	Not readily

#### 12.3 Bioaccumulative potential

Product/substance	LogK <sub>ow</sub>	BCF	Potential
Distillates (petroleum), hydrotreated heavy paraffinic	>4	-	high
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	6.1	-	high
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert- butyl-4-hydroxyphenyl) propionate	9.2	260	low
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	4.1	-	high
bis(nonylphenyl)amine	7.7	1584.89	high
Distillates (petroleum), solvent-dewaxed light paraffinic	3.1	-	low
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis (dithiophosphate)	0.9	-	low

12.4 Mobility in soil

Soil/water partition : Not available.

coefficient (Koc)

**Mobility** : Not available.

Mobility in soil : Given its physical and chemical characteristics, the product generally shows low soil

mobility The product is insoluble and floats on water. Loss by evaporation is limited

### 12.5 Results of PBT and vPvB assessment

Date of revision: Version: 1 United Kingdom (UK) ENGLISH 16/20



SDS no.

39334

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

#### **Product**

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste

According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used The following Waste Codes are only suggestions: 13 02 05\*

**Packaging** 

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions

: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

### **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	ICAO/IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Date of revision : Version: 1 United Kingdom (UK) **ENGLISH** 17/20



SDS no.

39334

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

: Not available.

### **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

#### Annex XIV - List of substances subject to authorisation

#### **Annex XIV**

None of the components are listed.

#### Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain

dangerous substances, mixtures and articles

#### Other EU regulations

Industrial emissions : Not listed

(integrated pollution prevention and control) -

Air

Industrial emissions : Not listed

(integrated pollution prevention and control) -

Water

#### Ozone depleting substances (1005/2009/EU)

Not listed.

#### Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

#### **Seveso Directive**

This product is not controlled under the Seveso Directive.

#### **National regulations**

#### **International regulations**

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### Montreal Protocol (Annexes A, B, C, E)

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

Date of revision: Version: 1 United Kingdom (UK) ENGLISH 18/20



**SDS no**. 39334

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

**Inventory list** 

Australia : All components are listed or exempted.

Canada : All components are listed or exempted.

China : All components are listed or exempted.

Europe : All components are listed or exempted.

Japan : Japan inventory (ENCS): All components are listed or exempted.

Japan inventory (ISHL): Not determined.

New Zealand : All components are listed or exempted.
Philippines : All components are listed or exempted.
Republic of Korea : All components are listed or exempted.
Taiwan : All components are listed or exempted.

Thailand : Not determined.
Turkey : Not determined.

**United States** : All components are listed or exempted.

Viet Nam : Not determined.

15.2 Chemical safety

assessment

: This product contains substances for which Chemical Safety Assessments are still

required.

#### **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Value : ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

vPvB = Very Persistent and Very Bioaccumulative

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Not classified.	

#### Full text of abbreviated H statements

H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H373	May cause damage to organs through prolonged or repeated
	exposure.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Date of revision: Version: 1 United Kingdom (UK) ENGLISH 19/20



SDS no.

39334

#### Full text of classifications [CLP/GHS]

Aquatic Chronic 2, H411 Aquatic Chronic 4, H413 Asp. Tox. 1, H304 Eye Dam. 1, H318 Skin Irrit. 2, H315 Skin Sens. 1B, H317 STOT RE 2, H373 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 4

ASPIRATION HAZARD - Category 1

SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1

SKIN CORROSION/IRRITATION - Category 2

SKIN SENSITISATION - Category 1B

SPECIFIC TARGET ORGAN TOXICITY - REPEATED

EXPOSURE - Category 2

Date of revision : 3/4/2021

Date of previous revision : No previous validation

Version : 1

#### **Notice to reader**

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Date of revision: Version: 1 United Kingdom (UK) ENGLISH 20/20