TECHNICAL SPECIFICATION

MODEL:

TUFFA 900SBFP Fire Protected Tank

CAPACITY (1):

LENGTH (mm):

WIDTH (mm):

HEIGHT (mm):

WEIGHT (kg):

MATERIAL:

BUNDED:

900

2000

625

1500

30min - 525 | 60min - 565

3mm mild steel plate



















SPECIFICATION

- ▶ Integrally fitted fire protection
- ▶ 2" BSP fill connection with cap & chain
- Vent
- Manual float level gauge
- ▶ Electronic remote reading gauge
- ▶ 1" bottom outlet (top outlet available on request)
- Overfill prevention valve
- ► Tank pack (1" 1/2" adaptor, ball valve & filter)
- Channel runners
- Central lifting eye
- ▶ Primed & painted in RAL 6005 Green

ACHIEVEMENTS

- Indepently tested to BS476: Part 22: 1987
- ▶ Independently tested to BS476 (Warrington Fire Research Centre)
- ▶ Meets Section | 5.4 of Building Regulations, Table 5.1 for Fire Protection for Oil Storage Tanks
- ▶ LABC Sytem Approval (Local Authority Building Control)

30 and 60 minute fire protection available



Tuffa UK Limited Dovefields Industrial Estate. Derby Road, Uttoxeter Staffs, ST14 8SW



... for all your liquid storage needs