



## **FORK 5** **-SYNTHETIC PLUS**

### **MAINTENANCE**

**Available grades: 5 - 10 - 15 - 20 - 30**

Fork 5 is a semi synthetic lubricant, compatible with all types of forks, for road and off-road use, designed for regular use. IPONE has selected the best synthetic bases and additives to guarantee Fork 5 has a low-friction formula, which ensures comfortable driving and improved shock absorption.



● **PACKING UNIT:**



● **TECHNICAL DATA:**

TEST	METHOD	TYPICAL VALUES					MEASURE UNITS
		FORK 5	FORK 10	FORK 15	FORK 20	FORK 30	
DENSITY AT 20 °C	ISO 12185	0,851	0,866	0,873	0,870	0,870	-
VISCOSITY AT 100 °C	ASTM D445	4	6,2	8,6	10,5	12	mm <sup>2</sup> /s
VISCOSITY AT 40 °C	ASTM D445	18,4	37,7	60,2	83,1	102,9	mm <sup>2</sup> /s
VISCOSITY INDEX (VIE)	ASTM D2270	115	111	115	110	106	-
FLASH POINT	ASTM D92	192	226	228	228	240	°C
BOILING POINT	ASTM D97	-42	< -36	-36	-27	-27	°C