

SHOWERWALL COMPACT DATA SHEET



Details of our Compact range.

COMPACT PANELS

PANEL SIZES & WEIGHTS

Square Cut	1220 x 2440mm	16kg
------------	---------------	------

DIMENSION TOLERANCES

Width	+/- 3.0mm
Height	+/- 5.0mm
Thickness	+/- 0.5mm

MATERIAL

A range of 5 colours are available. Showerwall Compact laminate is thick High pressure laminate that is produced to EN 438 standards

FIRE RATINGS / PERFORMANCE

All Showerwall compact panels are classified BS EN13501 : 2007 +A1 : 2009 with a fire rating of C , s1 , d0

DISCLAIMER

Be aware that gloss finished decors have a lower scratch resistance than textured decors and that the stated care & maintenance procedures must be followed to minimise normal wear and tear of the products.

GUARANTEE

30 year warranty against manufacturing defects in a domestic environment (subject to installation registration), and 5 years when installed in a commercial environment.

CARE & MAINTENANCE

Do

- Regularly use Showerwall cleaner to clean the panels. This contains an anti-bacterial agent.
- Replace any exposed silicone sealant periodically, or as necessary, to ensure a continual waterproof seal. Showerwall silicone remover is available to assist with this procedure.
- Rinse your Showerwall panels down after use as a multitude of various chemicals can be present within personal hygiene products used in bathrooms. Rinsing these off, avoids issues such as sealant discolouration.
- Ensure adequate ventilation is present when using your shower or bath to avoid mould and mildew growth occurring.

Don't

- Use any form of abrasive cleaner as these may result in dulling of your panel surface and accelerated wear affects.
- Use any form of bleach product to clean your Showerwall panels as harsh chemicals contained in bleaches can affect the surface of your panel and sealant.