



## Instructions for GeezerEngineering forged wheels

Warning: The installation of this product requires the skills of qualified motorcycle technicians and should be performed by qualified, professional workshops only



## The product box contains:

- Assembled 3-piece forged wheel with dual 14" floating brake rotors and titanium bolts
- internal wheel spacer
- 1 wheel bearing, right side; ABS bearing not included)
- Right and left side caliper stand-off mount
- Stainless steel mounting hardware

## Installation of wheel bearings and internal spacer

- 1. Install the left bearing first. The bolt heads in the wheel hub indicate left side of the wheel.
- 2. Insert the internal wheel spacer.
- 3. Install right side bearing.





If your bike is equipped with ABS the ABS sensor doubles as left spacer. Please slide the included O-ring over the ABS sensor. Then slide the cone cover over it.







Install tire and proceed with installing your wheel according to the OEM service manual for your year and model bike.



## **Disclaimer**

GeezerEngineering products part numbers, product packaging and corresponding printed matter are not intended to imply that any of these parts are Harley-Davidson® original equipment or endorsed by Harley-Davidson® Inc. The words, Enforcer, Rushmore, Buddy Seat, Disc Glide, Dyna Glide®, Electra Glide®, Evolution®, Fat Boy®, HD®, H-D®, Harley®, Harley-Davidson® Heritage® Softail®, Heritage® Springer®, Low Rider, Night Train®, Road Glide®, Road King®, Roadster®, Softail®, Softail® Deuce™, Sport Glide®, Sportster®, Springer®, Sturgis®, Super Glide®, Tour-Pak, Tour Glide®, Ultra Classic™ and Wide Glide® are registered trademarks of Harley-Davidson®, Inc., Milwaukee, Wisconsin, U.S.A. The words, Bad Boy®, Convertible, Duo Glide®, Hydra Glide®, V-Fire III and VROD™ are trademarks of Harley-Davidson®, Inc., Milwaukee, Wisconsin, U.S.A.

The following model designations for Harley-Davidson® motorcycles are used on this website for reference only: EL, FL, FLH, FLHR, FLHRCI, FLHS, FLHT, FLHTC, FLHTC Ultra Classic, FLHTC-I, FLHTCUI, FLHX, FLST, FLSTC, FLSTF, FLSTN, FLSTS, FLSTSC/I, FLT, FLTC, FLTC Ultra Classic, FLTCU, FLTR, FLTRI, FLTRSEI, FX, FXB, FXD, FXDB, FXDC, FXDG, FXDL, FXDS-CON, FXDWG, FXDX, FXDXT, FXE, FXEF, FXLR, FXR, FXRC, FXRD, FXRDG, FXRP, FXRS, FXRS-CON, FXRSE, FXRS-SP, FXRT, FXS, FXSB, FXST, FXSTB, FXSTC, FXSTD, FXSTD-I, FXSTS, FXSTSB, FXWG, GE, K, KH, VROD™, VRSCA, VRSCB, WL, WLA, XL, XL1100, XL1200, XL1200C, XL1200R, XL1200S, XL883, XL883C, XL883R, XLCH, XLCR, XLH, XLH1100, XLH1200, XLH1200, XLH1200S, XLH883, XLR, XLS, XLS, XLT, XLX, XLX, XR1000 and their connection to Harley-Davidson® factory part numbers, as well as any printed matter, are not intended to imply that any of these parts are Harley-Davidson® original equipment. Although the quality of most of the items listed here equals or exceeds OEM specifications, none of these items are manufactured by Harley-Davidson® Motor Company.

All parts listed on the GeezerEngineering.com website are either designed by GeezerEngineering or from independent aftermarket sources. All GeezerEngineering products are aftermarket products and are not necessarily endorsed or recommended by any other manufacturer. None of GeezerEngineering branded parts illustrated were manufactured by the original equipment manufacturer of the motorcycles they are intended for or under their supervision or control.

All other brand names or trademarks or registered trademarks used in any GeezerEngineering publication are the property of their respective holders and are used for reference purposes only. GeezerEngineering is in no way, shape or form associated with Harley-Davidson® Motor Company – neither stated nor implied. Any products with a trademark, name, word, O.E.M. number used on our web site, digital documents, printed media and videos by GeezerEngineering is strictly intended to be used solely as a reference only to usage to that particular part. All GeezerEngineering parts are designed to comply with or exceed D.O.T. standards. None of the parts and accessories are D.O.T. approved unless noted otherwise. We have total confidence in our product quality. We strongly suggest test fitting all parts prior to any modifications or painting.