EB-E20

DATASHEET / BROCHURE





With the versatility to mount just about anywhere, bright, sharp images and low maintenance, the EB-E20 is a great all-rounder for business.

The EB-E20 offers a very versatile proposition that can be mounted just about anywhere. Meanwhile long lamp life and trusted Epson durability offer peace of mind and minimal maintenance.

Bright, vivid content on a large scalable screen

Enjoy large scale presentations with crisp, clear text, as well as compelling imagery and video content, on screen sizes up to 350 inches. 3,400-lumen performance combines with a high contrast ratio of 15,000:1 to offer outstanding visual performance, even in well-lit rooms.

Years of uninterrupted meetings

With a lamp life of up to 12,000 hours in Eco mode.

Easy to use

Built-in lens shutter that allows easy restart and shut down. User friendly home screen that enables you to confidently and easily connect your device to the projector.

Multiple inputs on one display with audio

Display size matters; scalable up to 350" to enhance your viewing experience and ensure that content shown is not too small. That way everyone in your meeting has the same opportunities to share and engage.

High quality sound

This projector has a built-in 5W speaker to allow audio content to be heard clearly without the need for separate external speakers.

KEY FEATURES

- High-quality bright images 3LCD technology and equally high White and Colour Light Output
- Portable

Small and light enough to be moved easily and used in multiple rooms

- High quality sound Built-in 5W speaker for crisp, clear sound
- Low total cost of ownership Lamp life up to 12,000 hours in Eco mode
- Versatile and flexible control
 Project from many sources with HDMI



PRODUCT SPECIFICATIONS

ECHNOLOGY	
Projection System	3LCD Technology, RGB liquid crystal shutter
CD Panel	0.55 inch with C2 Fine
Color Light Output	3,400 Lumen- 2,200 Lumen (economy) In accordance with IDMS15.4
Vhite Light Output Resolution	3,400 Lumen - 2,200 Lumen (economy) In accordance with ISO 21118:2020 XGA
Aspect Ratio	4:3
Contrast Ratio	15,000 : 1
ight source	Lamp
amp	UHE, 210 W, 6,000 h durability, 12,000 h durability (economy mode)
Keystone Correction	Manual vertical: ± 30 °, Manual horizontal ± 30 °
Colour Video Processing	10 Bits
D Vertical Refresh Rate	100 Hz - 120 Hz
Colour Reproduction	Upto 1.07 billion colours
OPTICAL	
hrow Ratio	1.44 - 1.95:1
loom	Digital, Factor: 1 - 1.35
Screen Size	30 inches - 350 inches
Projection Distance Wide/Tel	e 1.76 m (60 inch screen
Projection Lens F Number	1.44
Projection Lens Focal Length	16.7 mm
Projection Lens Focus	Manual
Offset	8:1
CONNECTIVITY	
JSB Display Function	2 in 1: Image/ Sound
nterfaces	RS-232C, VGA in (2x), VGA out, HDMI in, Composite in, Jack plug out, Jack plug in (2x), Cinch
	audio out, USB 2.0
Epson iProjection App	Ad-Hoc / Infrastructure
ADVANCED FEATURES	
Security	Kensington lock, Control panel lock, Security cable hole, Password protection
D Colour Modes	Dynamic, Cinema, Presentation, sRGB, Blackboard
Other features	AV Mute Slide, CEC compatible, Digital zoom, Direct Power on/off, Document Camera
Cala a O a la a Marala a	Compatible, OSD copy function, Quick Corner, Split-Screen-Function
/ideo Color Modes	Blackboard, Dynamic, Presentation, sRGB, Theatre
GENERAL	
ower consumption	286 Watt (Normal On-Mode), 180 Watt (Eco On-Mode), 327 Watt (Normal Peak-mode), 225
	Watt (Eco Peak-Mode), 0.3 Watt (Energy saving standby)
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz
Product dimensions	309 x 282 x 87 mm (Width x Depth x Height)
Product weight	
loise Level	2.7 kg
	2.7 kg Normal: 37 dB (A) - Economy: 28 dB (A)
Supported Temperature	-
	Normal: 37 dB (A) - Economy: 28 dB (A)
Supported Temperature	Normal: 37 dB (A) - Economy: 28 dB (A) Operation 5° C - 40° C, Storage 10° C - 60° C
Supported Temperature Supported Humidity	Normal: 37 dB (A) - Economy: 28 dB (A) Operation 5° C - 40° C, Storage 10° C - 60° C Operation 20% - 80%, Storage 10% - 90%
Supported Temperature Supported Humidity	Normal: 37 dB (A) - Economy: 28 dB (A) Operation 5° C - 40° C, Storage 10° C - 60° C Operation 20% - 80%, Storage 10% - 90% Air filter, Ceiling mount, Document camera, External Speaker, Safety wire set, Soft carry case,
Supported Temperature Supported Humidity Options	Normal: 37 dB (A) - Economy: 28 dB (A) Operation 5° C - 40° C, Storage 10° C - 60° C Operation 20% - 80%, Storage 10% - 90% Air filter, Ceiling mount, Document camera, External Speaker, Safety wire set, Soft carry case, Spare lamp, Suspension adapter, WP System - ELPWP20, Wireless transmitter - ELPWT01
Supported Temperature Supported Humidity Options .oudspeaker	Normal: 37 dB (A) - Economy: 28 dB (A) Operation 5° C - 40° C, Storage 10° C - 60° C Operation 20% - 80%, Storage 10% - 90% Air filter, Ceiling mount, Document camera, External Speaker, Safety wire set, Soft carry case, Spare lamp, Suspension adapter, WP System - ELPWP20, Wireless transmitter - ELPWT01 5 Watt
Supported Temperature Supported Humidity Options Soudspeaker Room Type / Application	Normal: 37 dB (A) - Economy: 28 dB (A) Operation 5° C - 40° C, Storage 10° C - 60° C Operation 20% - 80%, Storage 10% - 90% Air filter, Ceiling mount, Document camera, External Speaker, Safety wire set, Soft carry case, Spare lamp, Suspension adapter, WP System - ELPWP20, Wireless transmitter - ELPWT01 5 Watt Boardroom, Huddle space / Portable, Meeting room / Classroom
Supported Temperature Supported Humidity Options Loudspeaker Room Type / Application Positioning Colour	Normal: 37 dB (A) - Economy: 28 dB (A) Operation 5° C - 40° C, Storage 10° C - 60° C Operation 20% - 80%, Storage 10% - 90% Air filter, Ceiling mount, Document camera, External Speaker, Safety wire set, Soft carry case, Spare lamp, Suspension adapter, WP System - ELPWP20, Wireless transmitter - ELPWT01 5 Watt Boardroom, Huddle space / Portable, Meeting room / Classroom Ceiling Mounted, Desktop
Supported Temperature Supported Humidity Options Loudspeaker Room Type / Application Positioning	Normal: 37 dB (A) - Economy: 28 dB (A) Operation 5° C - 40° C, Storage 10° C - 60° C Operation 20% - 80%, Storage 10% - 90% Air filter, Ceiling mount, Document camera, External Speaker, Safety wire set, Soft carry case, Spare lamp, Suspension adapter, WP System - ELPWP20, Wireless transmitter - ELPWT01 5 Watt Boardroom, Huddle space / Portable, Meeting room / Classroom Ceiling Mounted, Desktop

EB-E20

WHAT'S IN THE BOX

- Main unit
- Power cable
- Remote control incl. batteries

EPSON[®]

- Warranty card
- Quick Start Guide
- HDMI Cable 1.8m

OPTIONAL ACCESSORIES

- Soft Carry Case ELPKS70 V12H001K70
- Lamp ELPLP97 EB9XX/W49/X/E20/U50/EB-x05/x41/x42/EH-TW6 V13H010L97
- Air Filter ELPAF32 V13H134A32
- Ceiling Pipe (450mm) ELPFP13 V12H003P13
- Ceiling Pipe (700mm) ELPFP14 V12H003P14
- Safety Wire ELPWR01 V12H003W01
- Active Speakers (2 x 15W) ELPSP02 V12H467040
- Active Speakers (2 x 15W) ELPSP02 V12H467040DA
- Ceiling Mount (White) ELPMB23 V12H003B23

LOGISTICS INFORMATION

SKU	V11H981040
EAN code	8715946680743
Country of Origin	Philippines

* Warranty offers are not available for all countries. Please contact your local Epson representative.

For further information please contact your local Epson office or visit www.epson-europe.com Austria 01 253 49 78 333 Belgium +32 (0)2 792 04 47 Czech 800/142 052 Denmark 44 50 85 85 Finland 0201 552 091 France 09 74 75 04 04

(Cost of local call, operator charges may apply) Germany +49 (0) 2159/92 79 500 Greece +30 211 198 62 12 Hungary 06800 147 83 Ireland 01 436 7742

Italy 02-660321 10 (0,12 /min) Luxembourg +352 27860692 Middle East +9714 8872172 Netherlands +31 (0)20 708 5099 Norway +47 67 11 37 00 Poland 0-0-800 4911299 (0,16 zl/min) Portugal 707 222 111 Russia (095) 777-03-55 Slovakia 0850 111 429 South Africa (+2711)

465-9621 Spain 93 582 15 00 Sweden 0771-400135 (Mobilsamtal - 0,99 kr/min, Lokala samtal - 0,30 kr/min, Utlandssamtal - 0,89 kr/min)

Switzerland 022 592 7923 Turkey (0212) 3360303 United Kingdom 0871 222 6702

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice.

EB-E20

