EB-PU2116W



The EB-PU2116W is a high lumens 3LCD projector that's ultralightweight and compact.

The EB-PU2116W offers users significant advantages including much reduced size and weight, easier installation and set-up, simplified maintenance and great image quality. This ultra-lightweight, compact laser projector has been designed for use in large auditoriums, live events, concerts, conference rooms where it delivers high-impact immersive experiences.

Compact and lightweight

The reduced weight and size means the projector is easier to store, transport and install, saving on warehouse space as well as labour and delivery costs.

Outstanding image quality

This high lumens, 3LCD projector offers WUXGA resolution with 4K enhancement and HDR for rich textures and sharper images.

Flexibility

The EB-PU2116W's functionality enables simple installation, stacking, lens flexibility and control. It includes in-built processing for PC-free stacking which means two supported projectors can be stacked to double the brightness without the need for external computerware.

Reliability

Includes outstanding dust resistance as the hermetically sealed optical engine, and laser light source unit, ensure stable brightness output over long periods, even in high dust environments.

DATASHEET / BROCHURE































KEY FEATURES

- Ultra-lightweight and compact Easy to store, transport and install
- Stunning image displays 16,000lm, 4K Enhancement technology, WUXGA resolution
- Easy to use Simple installation, stacking, lens flexibility and control
- Fit-and-forget reliability
 Enhanced dust resistant construction IP5X certified
- Environmental benefits
 Lower power consumption, reduced packaging, reduced weight



PRODUCT SPECIFICATIONS

TECHNOLOGY

Projection System 3LCD Technology
LCD Panel 1.03 inch with C2 Fine

IMAGE

Color Light Output 16,000 Lumen - 11,200 Lumen (economy) In accordance with IDMS15.4

White Light Output 16,000 Lumen - 11,200 Lumen (economy) In accordance with ISO 21118:2020

Resolution WUXGA
High Definition 4K enhancement
Aspect Ratio 16:10

Contrast Ratio Over 2,500,000 : 1

Native Contrast 2,000 : 1 Light source Laser

Laser Light source 20,000 hours Durability High, 30,000 hours Durability Eco

Colour Video Processing 10 Bits

Colour Reproduction Upto 1.07 billion colours

HDR support HDR10, HLG

OPTICAL

Throw Ratio 0.35 - 7.41:1

Zoom Motorized, Factor: 1 - 1.6

Lens varies by lens

Lens Shift Motorized - Vertical ± 60 %, horizontal ± 18 %, varies by lens

Lens position memory 10 positions

Screen Size 60 inches - 1,000 inches, varies by lens

Projection Distance Wide)varies by lens
Projection Distance Tele)varies by lens
Projection Lens F Number varies by lens
Projection Lens Focal Length varies by lens
Projection Lens Focus Motorized
Interchangeable Lens Yes
Standard Lens Not included

CONNECTIVITY

Interfaces USB 2.0-A (2x), USB 2.0 Type B (Service Only), RS-232C, Ethernet Interface (1000 Base-T/ 100-

Base TX/10-Base-T), VGA in, DVI in, HDMI in, HDBaseT, Jack plug out, Wireless LAN IEEE 802.11a/b/g/n (optional), Near Field Communication (NFC), USB content playback, Remote

Network Protocol HTTPS, IPv6, SNMP, ESC/VP.net, PJLink

ADVANCED FEATURES

Security Kensington lock, Security bar, Password lock, Wireless LAN unit lock, Wireless LAN security,

Password protection

Other features 21:9 aspect ratio support, 4K enhancement, A/V mute, Auto Power On, Auto source search,

Direct Power on/off, Edge Blending, Lens position memory, Long light source life, OSD copy function, Point correction, Power on button, Quick Corner, Schedule Function, Split-Screen-

Function, Super resolution, Web Control, Web Remote, iProjection App

Video Color Modes Cinema, Dynamic, Natural, Presentation, DICOM SIM, Multi Projection, BT709

Projector control via: AMX, Crestron, Extron

Sealed Light Source Module Yes, IP5X rated
Sealed Optical Engine Yes, IP5X rated

EB-PU2116W

WHAT'S IN THE BOX

- Power cable
- Remote control incl. batteries
- Cable cover
- Lens connector cap
- User manual
- Warranty document



PRODUCT SPECIFICATIONS

GENERAL

Power consumption 902 Watt (Normal On-Mode), 1,083 Watt (Normal Peak-mode), 773 Watt (Eco Peak-Mode), 0.4

Watt (Energy saving standby)

Heat Dissipation 3,682 BTU/hour (max)

Supply Voltage AC 200 V - 240 V, 50 Hz - 60 Hz

Product dimensions 586 x 492 x 218 mm (Width x Depth x Height)

Product weight 24.3 kg

Noise Level Normal: 38 dB (A) - Economy: 34 dB (A)

Supported Temperature Storage -10° C - 60° C

Supported Humidity Operation 20% - 80%, Storage 10% - 90%

Included Software Epson Creative Projection, EasyMP Multi PC Projection, Epson Projector Config Tool, Epson

Projector Content Manager, Epson Projector Management, Epson Projector Professional Tool

Options Camera module, Ceiling mount, Wireless LAN unit

Positioning Ceiling Mounted, Desktop, Flying Frame

Colour White

OTHER

Warranty 36 months Carry in

Optional warranty extension available

EB-PU2116W

WHAT'S IN THE BOX

- Power cable
- Remote control incl. batteries
- Cable cover
- Lens connector cap
- User manual
- Warranty document



OPTIONAL ACCESSORIES

 Adapter - ELPAP11 Wireless LAN (5GHz) V12H005A01

Camera Unit - ELPEC01

V12HA46010

• Ceiling Mount - ELPMB68

V12H006AE0

• Extension Pole - ELPMB70 - For ELPMB68

V12H006AG0

• Truss Adaptor - ELPMB71 - For ELPMB68

V12H006AH0

• Stacking Frame - ELPMB59 - EB-PU2200 Series (EVO)

V12H996B59

• Stacking Frame - ELPMB84 - EB-PU2200 Series

V12H006AW0

• Portrait Adaptor - ELPMB78 - EB-PU Series

V12H006AQ0

• Tilt Adaptor - ELPMB81 - EB-PU Series

V12H006AT0

OPTIONAL LENSES

- Lens ELPLL08 Long throw EB-PU Series V12H004L08
- Lens FLPLM10 Mid throw 3 FB-PU Series V12H004M0A
- Lens ELPLM11 Mid throw 4 EB-PU Series V12H004M0B
- Lens ELPLM15 Mid throw EB-PU Series

V12H004M0F

- Lens ELPLU03S Short throw off axis 1 EB-PU Series V12H004UA3
- Lens ELPLU04 Short throw off axis 2 EB-PU Series

V12H004U04

• Lens - ELPLW06 - Wide zoom 2 - EB-PU Series

V12H004W06

• Lens - ELPLW08 - Wide throw - EB-PU2000 Series

V12H004W08

• Lens - ELPLX02S - UST - EB-PU2000 Series

V12H004X0B

• Lens - ELPLX02WS - UST - EB-PU2000 Series

V12H004Y0B

LOGISTICS INFORMATION

SKU	V11HA64940
EAN code	8715946703176
Country of Origin	China
Layer	1 Units

For further information please contact your local Epson office or visit www.epson-europe.com

Austria 01 253 49 78 333 Belgium +32 (0)2 792 04 47 Czech 800/142 052 Denmark 44 50 85 85 Finland 0201 552 091 France 09 74 75 04 04

(Cost of local call, operator charges may apply) Germany +49 (0) 2159/92 79 500 Greece +30 211 198 62 12 Hungary 06800 147 83 Ireland 01 436 7742 Italy 02-660321 10 (0,12 /min) Luxembourg +352 27860692 Middle East +9714 8872172 Netherlands +31 (0)20 708 5099 Norway

+47 67 11 37 00 Poland 0-0-800 4911299 (0,16 zł/min) Portugal 707 222 111 Russia (095) 777-03-55 Slovakia 0850 111 429 South Africa (+2711)

Spain 93 582 15 00 Sweden 0771-400135 (Mobilsamtal - 0,99 kr/min, Lokala samtal - 0,30 kr/min, Utlandssamtal - 0,89 kr/min) Switzerland 022 592 7923

Turkey (0212) 3360303 United Kingdom 0871 222 6702



EB-PU2116W

^{*} Warranty offers are not available for all countries. Please contact your local Epson representative.