EcoTank L6490



This multifunction A4 printer with fax delivers ultra-low printing costs and fast print speeds without the hassle of changing cartridges or toners.

Designed for home offices and small businesses this feature-rich A4 printer with fax delivers an ultra-low cost per page and ultra-fast print speeds. Thanks to the 250-sheet front paper tray, 6.1cm LCD touchscreen and 35-page automatic document feeder, you can just keep on printing.

Get more done in less time

Take your home office to the next level with this ultra-fast and efficient printer that can deliver a first page in as little as 7 seconds¹.

Feature-rich A4 EcoTank

Print, copy, scan and fax with the L6490 which features double-sided printing, a 250-sheet front paper tray and 35-page automatic document feeder. It's easy to navigate the extensive range of features with the 6.1cm LCD touchscreen.

Keep on saving

Making a saving every time you print with this EcoTank that delivers an incredibly low cost-per-page. Unlike other printers, EcoTank features large ink tanks that you fill with low-cost ink bottles.

Business-quality printing

The EcoTank 112 ink series features all pigment inks for smudge, water and highlighter resistant prints. From one set of replacement inks, you can produce up to 7,500 pages in black and 6,000 in colour²

Print from almost anywhere

With Wi-Fi and Wi-Fi Direct, you can send documents to print from smart devices using the Epson iPrint and Smart Panel apps³.

Easy to use and reliable

Filling the ink tanks is simple with the resealable, intuitive and mess-free ink bottles. Epson's unique Heat-Free PrecisionCore Technology offers improved reliability, reduced downtime and less environmental impact. No warm up time means the first page prints fast uses less power.

DATASHEET / BROCHURE



KEY FEATURES

- Ultra-fast print speeds
 Up to 17ipm⁴
- Ultra-low-cost per page Economical ink tank system
- Easy to use front ink tank
 Enjoy hassle-free refills with enhanced ink bottles
- Mobile printing and connectivity Wi-Fi, Wi-Fi Direct, Ethernet & free mobile printing apps³
- Designed for business
 A4 multifunction printer with fax, 250sheet front tray, 35-sheet ADF



PRODUCT SPECIFICATIONS

TECHNOLOGY

Printing Method PrecisionCore™ Print Head

Minimum Droplet Size 3.3 pl, With Variable-Sized Droplet Technology

Ink Technology Pigment ink Printing Resolution 4.800 x 1.200 DPI

Number of colours 4 colour

Printing Speed ISO/IEC 24734 17 pages/min Monochrome, 9.5 pages/min Colour

Maximum Printing Speed 23 pages/min Colour (plain paper 75 g/m²), 37 pages/min Monochrome (plain paper 75 g/m²)

Print from PC, MAC, Mobile Device

Colours Black [Pigment], Cvan [Pigment], Yellow [Pigment], Magenta [Pigment]

Colours Capacity Black [127ml], Cyan [70ml], Yellow [70ml], Magenta [70ml] For detailed information on printing speeds please visit http://www.epson.eu/testing.

Contact image sensor (CIS) Scanner type

Fax speed dials (max) 100 names and numbers

Page memory Up to 180 pages (ITU-T No.1 chart)

PC Fax. Auto Redial. Address Book. Broadcast Fax. Fax Preview. Polling Reception Fax Functions

PAPER / MEDIA HANDLING

Number of paper trays

Paper Formats 9 x 13 cm, 10 x 15 cm, 13 x 18 cm, 13 x 20 cm, 20 x 25 cm, 100 x 148 mm, 16:9, Letter Legal,

No. 10 (Envelope), DL (Envelope), C6 (Envelope), B5, A6 (10.5x14.8 cm), A4 (21.0x29.7 cm), A5

(14.8x21.0 cm), User defined

Duplex Yes Automatic Document Feed 35 pages

Paper Tray Capacity 250 Sheets Standard

Media Handling Automatic duplex (A4, plain paper)

GENERAL

Energy Use 12 Watt (standalone copying, ISO/IEC 24712 pattern), 0.9 Watt (sleep mode), 5.3 Watt (Ready),

0.3 Watt (Power off), TEC 0.14 kWh/week

Product dimensions 346 x 375 x 347 mm (Width x Depth x Height)

Product weight

LOGISTICS INFORMATION

SKU	C11CJ88403
EAN code	8715946689241
Country of Origin	Philippines







* Warranty offers are not available for all countries. Please contact your local Epson representative.

For further information please contact your local Epson office or visit www.epson-europe.com Austria 01 253 49 78 333 Belgium +32 (0)2 792 04 47 Czech 800/142 052 Denmark 44 50 85 85 Finland 0201 552 091 France 09 74 75 04 04

(Cost of local call, operator charges may apply) Germany +49 (0) 2159/92 79 500 Greece +30 211 198 62 12 Hungary 06800 147 83 Ireland 01 436 7742

Italy 02-660321 10 (0,12 /min) Luxembourg +352 27860692 Middle East +9714 8872172 Netherlands +31 (0)20 708 5099 Norway +47 67 11 37 00 Poland 0-0-800 4911299 (0,16 zł/min) Portugal 707 222 111 Russia (095) 777-03-55 Slovakia 0850 111 429 South Africa (+2711)

Spain 93 582 15 00 Sweden 0771-400135 (Mobilsamtal - 0,99 kr/min, Lokala samtal - 0,30 kr/min, Utlandssamtal - 0,89 kr/min) . Switzerland 022 592 7923

Turkey (0212) 3360303 United Kingdom 0871 222 6702

EcoTank L6490

WHAT'S IN THE BOX

- Warranty document
- Main unit
- Power cable
- Setup guide
- 1 set of ink (1x 127ml BK, 3x 70ml CMY)
 - + Extra Black
- Driver and utilities (CD)

INK BOTTLE COMPATIBILITY

112

112

112 112





INK BOTTLE YIELD DATA

	•	• • •
Included	13,300 pages*	5,200 pages*
Replacement	7,500 pages*	6,000 pages*

* Approx. page yield based on ISO/IEC 24711/24712 or ISO/ IEC 29102/29103. Actual yield will vary depending on images printed and usage conditions. For more information visit http://www.epson.eu/pageyield

- 1. First-Print-Out-Time (FPOT) measurement method: ISO/IEC17629 Office Category Test; paper size A4. A set of Microsoft Word, Microsoft Excel and PDF files (each set containing 4 pages) is continuously printed. Measurement is based on the average time for the first of the four single sided prints to exit the printer. Measurement starts when the print button is pressed and ends when the first page of
- 2. Quoted yields are extrapolated based on Epson original methodology from the print simulation of Test Patterns provided in ISO/IEC 24712 based on the replacement ink bottles. Quoted yields are NOT based on ISO/IEC 24711. Quoted yields may vary depending on the images that you are printing, the paper type that you are using, the frequency of your prints and environmental conditions such as temperature. During the initial printer setup, a certain amount of ink is used to fill the print head's nozzles, therefore the yield of the initial bundled set can be lower. 3. Requires a wireless connection to the internet. For
- more information, supported languages and devices please visit www.epsonconnect.eu
- 4. Determined in accordance with ISO/IEC 24734 showing the average of ESAT from the Office Category Test for default simplex. For more information visit www.epson.eu/testing
- 6. WARNING: when printing on glossy photo paper ink drying time will be considerably extended. Drying times depends also on humidity, temperature and other conditions. Do not touch the printed side until ink is completely dry. Moisture and oils from your skin can also affect print quality. Even after dry, avoid rubbing or scratching the surface of the printed paper.For Photo printing, Matte Photo paper is recommended

