EcoTank Pro L15180



Fast and feature-rich, this A3 colour multifunction printer delivers hassle-free printing at an ultra-low cost total cost of ownership.

Print, scan, copy and fax with this easy-to-use EcoTank Pro Wi-Fi printer, that delivers an exceptionally low cost-per-page and reduces your energy consumption thanks to Heat-Free technology. With fast print and scan speeds, A3 and A4 jobs can be accomplished quickly. Using Open Platform, seamlessly integrate a variety of software solutions into existing IT infrastructure to improve efficiency.

Keep on saving

Save every time you print with the L15180. Thanks to low-cost ink bottles, benefit from incredibly low costs-per-page. Epson's Heat-Free technology keeps energy consumption down to a minimum, saving on energy bills.

Time-saving features

The L15180 offers a first page out time of just 5.5 seconds¹ and print speeds up to 25 pages per minute. The automatic document feeder can scan up to 26 images per minute.

Advanced software solution compatibility

A variety of software solutions can be integrated into existing IT infrastructure to improve efficiency. This includes Epson Remote Services (ERS) which offers cloud-based device monitoring and management system that delivers advanced remote diagnostics for Epson business products.

Low user intervention

Minimising refills, this EcoTank Pro can print thousands of pages before needing more ink. Two trays offer a capacity of 500-sheets. Free yourself from manual page loading with a generous 50-sheet rear feed and ADF.

Easy to use and reliable

Selecting features is easy with the LCD colour touchscreen. And refilling the large front ink tanks is simple with the resealable, intuitive and drip-free ink bottles.

Print from almost anywhere

It's easy to print from mobiles, tablets and laptops using the L15180. With Wi-Fi and Wi-Fi Direct, you can send documents to print from smart devices using the Epson iPrint² app.

DATASHEET / BROCHURE























KEY FEATURES

- Ultra-low cost, 4-in-1 A3 printer Economical ink tank system
- Fast print and scan speeds
 Print up to 25 ppm and scan up to 26 ipm
- Easy to use front ink tank
 Enjoy hassle and mess-free refills with enhanced ink bottles
- Mobile printing and connectivity Wi-Fi, Wi-Fi Direct, Ethernet & free mobile printing apps²
- Advanced software solutions
 Seamlessly integrate software into existing IT infrastructure



PRODUCT SPECIFICATIONS

TECHNOLOGY

Printing Method PrecisionCore™ Print Head

Nozzle Configuration 800 Nozzles Black, 800 Nozzles per Color

Minimum Droplet Size 3.8 pl Ink Technology

DURABrite™ ET Office Desktop Print, Scan, Copy, Fax

PRINT

Category

Number of colours 4 colour

First Page Out Monochrome 5.5 Seconds, Colour 5.5 Seconds, According to IEEE/ISO 17629

Printing Speed ISO/IEC 24734 25 pages/min Monochrome, 25 pages/min Colour **Duplex Printing Speed** 21 A4 Pages/min Monochrome, 21 A4 Pages/min Colour

ISO/IEC 24734

All-in-One Functions

Printing Resolution 4,800 x 1,200 DPI Printing Volume 66,000 pages per month

The maximum number of printed pages per month based on the performance capabilities of

the printer, including ISO rated print speeds and paper handling capabilities. Black [Pigment], Cyan [Pigment], Yellow [Pigment], Magenta [Pigment]

Colours

Print from PC, MAC, Network, Mobile Device, USB, PC (Wired), PC (Wireless), Mobile Device (WiFi Direct)

SCAN

Double-sided scanning

Single-sided scan speed (A4 26 ipm with ADF scan

black)

Doubled-sided scan speed 11.5 ipm with ADF scan

(A4 black)

Single-sided scan speed (A4 9 ipm with ADF scan

colour)

Doubled-sided scan speed 6 ipm with ADF scan (A4 colour)

Optical Resolution

1,200 DPI (Horizontal x Vertical) Optical Resolution (ADF) 1,200 DPI (Horizontal x Vertical) BMP, JPEG, TIFF, multi-TIFF, PDF, PNG Output formats

Contact image sensor (CIS) Scanner type

FAX

Fax Transmission Speed Up to 33.6kbps / Approx. 3 sec/page

Error correction mode CCITU/ITU Group3 fax with Error Correction Mode

PC Fax, Fax to E-mail, Memory Reception, Auto Redial, Address Book, Broadcast Fax, Fax

Preview, Polling Reception

CONNECTIVITY

Network Protocol HTTPS, IPv4, IPv6, SNMP

Hi-Speed USB - compatible with USB 2.0 specification, Ethernet interface (100 Base-TX / 10 Interfaces

Base-T), Wireless LAN IEEE 802.11a/b/g/n/ac, Wi-Fi Direct, USB host

WLAN Security WEP 64 Bit, WEP 128 Bit, WPA PSK (TKIP), WPA2 PSK (AES)

EcoTank Pro L15180

WHAT'S IN THE BOX

- 1 full set of ink (Bk 127ml, CMY 70ml)
- Power cable
- Installation/safety manual
- Driver and utilities (CD)
- Warranty document
- Main unit
- Quick Start Guide



PRODUCT SPECIFICATIONS

EcoTank Pro L15180

PAPER / MEDIA HANDLING

Paper Formats A4 (21.0x29.7 cm), Legal, A5 (14.8x21.0 cm), A6 (10.5x14.8 cm), B6, B5, No. 10 (Envelope), DL

(Envelope), C6 (Envelope), C4 (Envelope), Letter, Letter Legal, A3 (29.7x42.0 cm), A3+

Automatic Document Feed 50 pages

Compatible Paper Weight 64 g/m² - 255 g/m²

Duplex Yes (A4/A3, plain paper)

Output Tray Capacity 125 Sheets

Paper Tray Capacity 250 Sheets Standard, 550 Sheets Maximum

Rear paper path (special Yes

media)

Number of paper trays 3

GENERAL

Energy Use 19 Watt (standalone copying, ISO/IEC 24712 pattern), 0.7 Watt (sleep mode), 9.7 Watt (Ready),

0.15 Watt (Power off), TEC 0.13 kWh/week

Supply Voltage AC 100 V - 240 V, 50 Hz - 60 Hz

Product dimensions 515 x 500 x 350 mm (Width x Depth x Height)

Product weight 21.5 kg

Noise Level 6.7 B (A) according to ISO 7779 pattern with Epson Premium Glossy Photo Paper / Photo RPM

mode - 52 dB (A) according to ISO 9296

mode - 52 dB (A) according to ISO 9296

Compatible Operating Android, Citrix XenApp 5.0, Citrix XenApp 6.0, Citrix XenApp 6.x, Citrix XenApp 7.6 and above,

Systems

Citrix XenApp 7.x, Citrix XenApp Version 6.5, Citrix XenApp Version 7.6, Citrix XenDesktop Version 7.6, Linux, MAC OS 10.15 + or later, Mac OS 10.10.x, Mac OS 10.11, Mac OS 10.2+, Mac OS 10.3+, Mac OS 10.4+, Mac OS 10.4.11 or later (Epson Scan Only), Mac OS 10.5+, Mac OS 10.5.8 or later, Mac OS 10.5.8 or later (requires download of driver from Epson website), Mac OS 10.5.9, Mac OS 10.6+, Mac OS 10.7x, Mac OS 10.8.x, Mac OS 10.9.x, Mac OS X, Mac OS X 10.11.x, Mac OS X 10.11.x or later, Mac OS X 10.12, Mac OS X 10.12.x, Mac OS X 10.13.x, Mac OS X 10.6.8, Mac OS X 10.6.8 or later, Windows 10 (32/64 bit), Windows 7 (32/64 bit), Windows 8 (32/64 bit), Windows 8 (32/64 bit), Windows Server 2008 R2, Windows Server 2012 R2, Windows Server 2016, Windows Vista (32/64 bit), Windows XP Professional x64 Edition SP2 or later, XP Professional x64 Edition, iOS 5.0+, iOS 6.0+, iOS 7

Included Software Epson Device Admin, Epson Scan 2, Epson Status Monitor, EpsonNet Config

Sound Power Operation: 6.7 B (A)
Noise Operation: 52 dB (A)

Mobile and Cloud printing Epson Connect (iPrint, Email Print, Remote Print Driver, Scan-to-Cloud), Apple AirPrint

services

Noise Level Operation (Roll): 52 dB (A)

Power supply 220V, 240V

ADDITIONAL FEATURES

Features Touchscreen, Direct print from USB
Panel Type: Color, Touchscreen, Diagonal: 10.9 cm

Media Handling ADF 2-sided copy (A4/A3, plain paper), ADF 2-sided fax (A4/A3, plain paper), ADF 2-sided

scan (A4/A3, plain paper), Automatic duplex (A4/A3, plain paper)

OTHER FEATURES

Emulations PCL5e, PCL6

Optional Software & Solutions Epson Device Admin, Epson Net Config, Remote Panel Tool
Security TLS, SSL, IEE 802, SNMP, FTP, IPv6, HTTPs, WPA2, WPA3, IEEE802



SUPPLIES

•	112 EcoTank Pigment Black ink bottle	C13T06C14A	7,500 pages
•	■ 112 EcoTank Pigment Cyan ink bottle	C13T06C24A	6,000 pages
•	■ 112 EcoTank Pigment Magenta ink bottle	C13T06C34A	6,000 pages
	■ 112 EcoTank Pigment Yellow ink bottle	C13T06C44A	6.000 pages

LOGISTICS INFORMATION

SKU	C11CH71407 C11CH71407BY C11CH71406
EAN code	8715946690346
Country of Origin	Indonesia

EcoTank Pro L15180

INK YIELD DATA



112 4 colour ink bottles 112

•	7,500 pages*
• • •	6,000 pages*

^{*} Approx. page yield based on ISO/IEC 24711/24712 or ISO/IEC 29102/29103. Actual yield will vary depending on images printed and usage conditions. For more information visit http://www.epson.eu/pageyield



^{*} Warranty offers are not available for all countries. Please contact your local Epson representative.

For further information please contact your local Epson office or visit www.epson-europe.com

Austria 01 253 49 78 333 Belgium +32 (0)2 792 04 47 Czech 800/142 052 Denmark 44 50 85 85 Finland 0201 552 091 France 09 74 75 04 04 (Cost of local call, operator charges may apply) Germany +49 (0) 2159/92 79 500 Greece +30 211 198 62 12 Hungary 06800 147 83 Ireland 01 436 7742

Italy 02-660321 10 (0,12 /min) Luxembourg +352 27860692 Middle East +9714 8872172 Netherlands +31 (0)20 708 5099 Norway +47 67 11 37 00

Poland 0-0-800 4911299 (0,16 zl/min) Portugal 707 222 111 Russia (095) 777-03-55 Slovakia 0850 111 429 South Africa (+2711)

Spain 93 582 15 00 Sweden 0771-400135 (Mobilsamtal - 0,99 kr/min, Lokala samtal - 0,30 kr/min, Utlandssamtal - 0,89 kr/min)

Switzerland 022 592 7923
Turkey (0212) 3360303 United Kingdom 0871 222 6702

- 1. Determined in accordance with ISO/IEC 24734 showing the average of ESAT from the Office Category Test for default simplex. For more information visit www.epson.eu/testing
- 2. Requires a wireless connection to the internet. For more information, supported languages and devices please visit www.epsonconnect.com

