LightScene EV-115



The EV-115 is an innovative and versatile 2,200 lumens laser projection solution for creating experiential displays and digital signage.

Add movement and life to retail displays, hospitality events, visitor experiences, galleries, museums, corporate environments or exhibitions, with a low visual noise projector that blends into any environment. The EV-115 brings lighting and projection together, and perfectly combines high design, high image quality and installation flexibility.

Minimalist design - maximum impact

The LightScene EV-115 allows users to unlock their creativity and project instantly appealing visuals, with sharp WXGA resolution and 2,200 lumens brightness. Thanks to its discreet design, it can be used where a traditional projector may stand out. A white version is also available.

Simple, flexible implementation

A lightweight, adaptable design means the EV-115 can be installed in a variety of ways, from a traditional ceiling mount to a freestanding floor mount, or attached to a lighting track, including recessed lighting tracks.

Signage-ready

Featuring a built-in media player with wireless content upload, allowing playlists to be loaded onto an SD card and played directly from the projector1. The EV-115 also features HDMI connectivity for simple integration into content management systems without specialist installation.


Advanced installations made easy

The GPI function supports direct sensor connectivity for creating dynamic experiences that can adapt to situational changes without the need for costly external hardware. The EV-115 also uses advanced techniques such as edge blending to achieve stunning results in larger spaces that require multiple unit installations.

Fit and forget reliability

A five-year warranty, combined with Epson's reliable laser light source technology and sealed optical engine, means that the EV-115 does not require regular maintenance.

DATASHEET / BROCHURE



KEY FEATURES

- Experiential projection Create borderless content, lighting effects and blended displays with ease
- Sensor-based content GPI function for simple sensor-based experiences
- Flexible installation Can be ceiling-mounted, freestanding or attached to a lighting track
- Signage-ready Built-in media player and simple CMS integration
- Fit and forget reliability Durable Epson laser technology supported by a five-year warranty



PRODUCT SPECIFICATIONS

TECHNOLOGY	
Projection System	3LCD Technology
LCD Panel	0.59 inch with C2 Fine
IMAGE	
Color Light Output	2,200 Lumen- 1,100 Lumen (economy) In accordance with IDMS15.4
White Light Output	2,200 Lumen - 1,100 Lumen (economy) In accordance with ISO 21118:2020
Resolution	WXGA 2
Aspect Ratio	16:10
Contrast Ratio	2,500,000 : 1
Native Contrast	2,000 : 1
Light source	Laser
Laser Light source	20,000 hours Durability High, 30,000 hours Durability Eco
Keystone Correction	Manual vertical: $\pm 45^{\circ}$, Manual horizontal $\pm 40^{\circ}$
Colour Reproduction	16.77 million colours
OPTICAL	1 20 0 10.1
Throw Ratio	1.38 - 2.19:1 Materized Factor 1, 1.59
Zoom	Motorized, Factor: 1 - 1.58
Lens Soroon Sizo	Optical
Screen Size	30 inches - 150 inches
Projection Distance Wide	0.9 m - 4.5 m
Projection Lens F Number	1.51 - 1.92
Projection Lens Focal Length	
Projection Lens Focus	Motorized
CONNECTIVITY	
Interfaces	USB 2.0-A, USB 2.0 Type B (Service Only), Ethernet interface (100 Base-TX / 10 Base-T),
	Wireless LAN b/g/g 25GHz, HDMI in, Jack plug out, SD Card Slot, SD Card playback, Wireless
	LAN a/n (5GHz)
Network Protocol	HTTPS, IPv6, SNMP, ESC/VP.net, PJLink
ADVANCED FEATURES	
ADVANCED FEATURES Security	Wireless LAN security, Password protection
	Wireless LAN security, Password protection A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone
Security	
Security	A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone
Security Other features	A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone correction, Image Shift, Long light source life, Quick Corner, Web Control, Web Remote
Security Other features Video Color Modes Projector control	A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone correction, Image Shift, Long light source life, Quick Corner, Web Control, Web Remote Dynamic, Normal
Security Other features Video Color Modes Projector control GENERAL	A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone correction, Image Shift, Long light source life, Quick Corner, Web Control, Web Remote Dynamic, Normal via: Crestron, Crestron Integrated Partner, Crestron RoomView
Security Other features Video Color Modes Projector control	A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone correction, Image Shift, Long light source life, Quick Corner, Web Control, Web Remote Dynamic, Normal via: Crestron, Crestron Integrated Partner, Crestron RoomView 124 Watt (Normal On-Mode), 149 Watt (Normal Peak-mode), 112 Watt (Eco Peak-Mode), 0.4
Security Other features Video Color Modes Projector control GENERAL Power consumption	A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone correction, Image Shift, Long light source life, Quick Corner, Web Control, Web Remote Dynamic, Normal via: Crestron, Crestron Integrated Partner, Crestron RoomView 124 Watt (Normal On-Mode), 149 Watt (Normal Peak-mode), 112 Watt (Eco Peak-Mode), 0.4 Watt (Energy saving standby)
Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage	A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone correction, Image Shift, Long light source life, Quick Corner, Web Control, Web Remote Dynamic, Normal via: Crestron, Crestron Integrated Partner, Crestron RoomView 124 Watt (Normal On-Mode), 149 Watt (Normal Peak-mode), 112 Watt (Eco Peak-Mode), 0.4 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz
Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions (default	A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone correction, Image Shift, Long light source life, Quick Corner, Web Control, Web Remote Dynamic, Normal via: Crestron, Crestron Integrated Partner, Crestron RoomView 124 Watt (Normal On-Mode), 149 Watt (Normal Peak-mode), 112 Watt (Eco Peak-Mode), 0.4 Watt (Energy saving standby)
Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions (default position)	A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone correction, Image Shift, Long light source life, Quick Corner, Web Control, Web Remote Dynamic, Normal via: Crestron, Crestron Integrated Partner, Crestron RoomView 124 Watt (Normal On-Mode), 149 Watt (Normal Peak-mode), 112 Watt (Eco Peak-Mode), 0.4 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz 530 x 470 x 250 mm (Width x Depth x Height)
Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions (default position) Dimensions: Projection Unit	A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone correction, Image Shift, Long light source life, Quick Corner, Web Control, Web Remote Dynamic, Normal via: Crestron, Crestron Integrated Partner, Crestron RoomView 124 Watt (Normal On-Mode), 149 Watt (Normal Peak-mode), 112 Watt (Eco Peak-Mode), 0.4 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz 530 x 470 x 250 mm (Width x Depth x Height) Ø175 x 260 mm (Depth)
Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions (default position) Dimensions: Projection Unit Dimensions: Power Supply	A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone correction, Image Shift, Long light source life, Quick Corner, Web Control, Web Remote Dynamic, Normal via: Crestron, Crestron Integrated Partner, Crestron RoomView 124 Watt (Normal On-Mode), 149 Watt (Normal Peak-mode), 112 Watt (Eco Peak-Mode), 0.4 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz 530 x 470 x 250 mm (Width x Depth x Height) Ø175 x 260 mm (Depth) 361 x 110 x 65 mm (Width x Depth x Height)
Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions (default position) Dimensions: Projection Unit Dimensions: Power Supply Product weight	A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone correction, Image Shift, Long light source life, Quick Corner, Web Control, Web Remote Dynamic, Normal via: Crestron, Crestron Integrated Partner, Crestron RoomView 124 Watt (Normal On-Mode), 149 Watt (Normal Peak-mode), 112 Watt (Eco Peak-Mode), 0.4 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz 530 x 470 x 250 mm (Width x Depth x Height) Ø175 x 260 mm (Depth) 361 x 110 x 65 mm (Width x Depth x Height) 5 kg
Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions (default position) Dimensions: Projection Unit Dimensions: Power Supply Product weight Noise Level	A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone correction, Image Shift, Long light source life, Quick Corner, Web Control, Web Remote Dynamic, Normal via: Crestron, Crestron Integrated Partner, Crestron RoomView 124 Watt (Normal On-Mode), 149 Watt (Normal Peak-mode), 112 Watt (Eco Peak-Mode), 0.4 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz 530 x 470 x 250 mm (Width x Depth x Height) Ø175 x 260 mm (Depth) 361 x 110 x 65 mm (Width x Depth x Height) 5 kg Normal: 34 dB (A) - Economy: 22 dB (A)
Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions (default position) Dimensions: Projection Unit Dimensions: Power Supply Product weight Noise Level Supported Temperature	A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone correction, Image Shift, Long light source life, Quick Corner, Web Control, Web Remote Dynamic, Normal via: Crestron, Crestron Integrated Partner, Crestron RoomView 124 Watt (Normal On-Mode), 149 Watt (Normal Peak-mode), 112 Watt (Eco Peak-Mode), 0.4 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz 530 x 470 x 250 mm (Width x Depth x Height) Ø175 x 260 mm (Depth) 361 x 110 x 65 mm (Width x Depth x Height) 5 kg Normal: 34 dB (A) - Economy: 22 dB (A) Operation 5° C - 40° C, Storage -10° C - 60° C
Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions (default position) Dimensions: Projection Unit Dimensions: Power Supply Product weight Noise Level Supported Temperature Supported Humidity	A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone correction, Image Shift, Long light source life, Quick Corner, Web Control, Web Remote Dynamic, Normal via: Crestron, Crestron Integrated Partner, Crestron RoomView 124 Watt (Normal On-Mode), 149 Watt (Normal Peak-mode), 112 Watt (Eco Peak-Mode), 0.4 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz 530 x 470 x 250 mm (Width x Depth x Height) Ø175 x 260 mm (Depth) 361 x 110 x 65 mm (Width x Depth x Height) 5 kg Normal: 34 dB (A) - Economy: 22 dB (A) Operation 5° C - 40° C, Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90%
Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions (default position) Dimensions: Projection Unit Dimensions: Projection Unit Dimensions: Power Supply Product weight Noise Level Supported Temperature Supported Humidity Included Software	A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone correction, Image Shift, Long light source life, Quick Corner, Web Control, Web Remote Dynamic, Normal via: Crestron, Crestron Integrated Partner, Crestron RoomView 124 Watt (Normal On-Mode), 149 Watt (Normal Peak-mode), 112 Watt (Eco Peak-Mode), 0.4 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz 530 x 470 x 250 mm (Width x Depth x Height) 0175 x 260 mm (Depth) 361 x 110 x 65 mm (Width x Depth x Height) 5 kg Normal: 34 dB (A) - Economy: 22 dB (A) Operation 5° C - 40° C, Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% Epson Creative Projection, Epson Projector Content Manager
Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions (default position) Dimensions: Projection Unit Dimensions: Power Supply Product weight Noise Level Supported Temperature Supported Humidity Included Software Options	A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone correction, Image Shift, Long light source life, Quick Corner, Web Control, Web Remote Dynamic, Normal via: Crestron, Crestron Integrated Partner, Crestron RoomView 124 Watt (Normal On-Mode), 149 Watt (Normal Peak-mode), 112 Watt (Eco Peak-Mode), 0.4 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz 530 x 470 x 250 mm (Width x Depth x Height) 0175 x 260 mm (Depth) 361 x 110 x 65 mm (Width x Depth x Height) 5 kg Normal: 34 dB (A) - Economy: 22 dB (A) Operation 5° C - 40° C, Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% Epson Creative Projection, Epson Projector Content Manager Floor stand, Lighting track mount
Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions (default position) Dimensions: Projection Unit Dimensions: Projection Unit Dimensions: Power Supply Product weight Noise Level Supported Temperature Supported Temperature Supported Humidity Included Software Options Room Type / Application	A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone correction, Image Shift, Long light source life, Quick Corner, Web Control, Web Remote Dynamic, Normal via: Crestron, Crestron Integrated Partner, Crestron RoomView 124 Watt (Normal On-Mode), 149 Watt (Normal Peak-mode), 112 Watt (Eco Peak-Mode), 0.4 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz 530 x 470 x 250 mm (Width x Depth x Height) 0175 x 260 mm (Depth) 361 x 110 x 65 mm (Width x Depth x Height) 5 kg Normal: 34 dB (A) - Economy: 22 dB (A) Operation 5° C - 40° C, Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% Epson Creative Projection, Epson Projector Content Manager Floor stand, Lighting track mount Projection Mapping, Signage / Retail, Visitor Attraction
Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions (default position) Dimensions: Projection Unit Dimensions: Projection Unit Dimensions: Power Supply Product weight Noise Level Supported Temperature Supported Humidity Included Software Options	A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone correction, Image Shift, Long light source life, Quick Corner, Web Control, Web Remote Dynamic, Normal via: Crestron, Crestron Integrated Partner, Crestron RoomView 124 Watt (Normal On-Mode), 149 Watt (Normal Peak-mode), 112 Watt (Eco Peak-Mode), 0.4 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz 530 x 470 x 250 mm (Width x Depth x Height) 0175 x 260 mm (Depth) 361 x 110 x 65 mm (Width x Depth x Height) 5 kg Normal: 34 dB (A) - Economy: 22 dB (A) Operation 5° C - 40° C, Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% Epson Creative Projection, Epson Projector Content Manager Floor stand, Lighting track mount
Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions (default position) Dimensions: Projection Unit Dimensions: Poyer Supply Product weight Noise Level Supported Temperature Supported Temperature Supported Humidity Included Software Options Room Type / Application Positioning Colour	A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone correction, Image Shift, Long light source life, Quick Corner, Web Control, Web Remote Dynamic, Normal via: Crestron, Crestron Integrated Partner, Crestron RoomView 124 Watt (Normal On-Mode), 149 Watt (Normal Peak-mode), 112 Watt (Eco Peak-Mode), 0.4 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz 530 x 470 x 250 mm (Width x Depth x Height) 0175 x 260 mm (Depth) 361 x 110 x 65 mm (Width x Depth x Height) 5 kg Normal: 34 dB (A) - Economy: 22 dB (A) Operation 5° C - 40° C, Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% Epson Creative Projection, Epson Projector Content Manager Floor stand, Lighting track mount Projection Mapping, Signage / Retail, Visitor Attraction Ceiling Mounted, Floor, Lighting Track, Wall Mounted
Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions (default position) Dimensions: Projection Unit Dimensions: Power Supply Product weight Noise Level Supported Temperature Supported Temperature Supported Humidity Included Software Options Room Type / Application Positioning Colour	A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone correction, Image Shift, Long light source life, Quick Corner, Web Control, Web Remote Dynamic, Normal via: Crestron, Crestron Integrated Partner, Crestron RoomView 124 Watt (Normal On-Mode), 149 Watt (Normal Peak-mode), 112 Watt (Eco Peak-Mode), 0.4 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz 530 x 470 x 250 mm (Width x Depth x Height) Ø175 x 260 mm (Depth) 361 x 110 x 65 mm (Width x Depth x Height) 5 kg Normal: 34 dB (A) - Economy: 22 dB (A) Operation 5° C - 40° C, Storage 10° C - 60° C Operation 20% - 80%, Storage 10% - 90% Epson Creative Projection, Epson Projector Content Manager Floor stand, Lighting track mount Projection Mapping, Signage / Retail, Visitor Attraction Ceiling Mounted, Floor, Lighting Track, Wall Mounted Black
Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions (default position) Dimensions: Projection Unit Dimensions: Poyer Supply Product weight Noise Level Supported Temperature Supported Temperature Supported Humidity Included Software Options Room Type / Application Positioning Colour	A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone correction, Image Shift, Long light source life, Quick Corner, Web Control, Web Remote Dynamic, Normal via: Crestron, Crestron Integrated Partner, Crestron RoomView 124 Watt (Normal On-Mode), 149 Watt (Normal Peak-mode), 112 Watt (Eco Peak-Mode), 0.4 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz 530 x 470 x 250 mm (Width x Depth x Height) 0175 x 260 mm (Depth) 361 x 110 x 65 mm (Width x Depth x Height) 5 kg Normal: 34 dB (A) - Economy: 22 dB (A) Operation 5° C - 40° C, Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% Epson Creative Projection, Epson Projector Content Manager Floor stand, Lighting track mount Projection Mapping, Signage / Retail, Visitor Attraction Ceiling Mounted, Floor, Lighting Track, Wall Mounted

LightScene EV-115

WHAT'S IN THE BOX

- Cable cover
- Direct mount unit
- HDMI Cable Clamp
- Power cable
- Remote control incl. batteries

EPSON[®]

- User's Manual Set
- Hexagon wrench
- Safety wire set

OPTIONAL ACCESSORIES

- Floor Stand ELPMB55B EV-105 V12H888B10
- Lighting Track Mount ELPMB66B EV-115 V12HA32140

LOGISTICS INFORMATION

ѕки	V11HA22140
EAN code	8715946689333
Country of Origin	China

* Warranty offers are not available for all countries. Please contact your local Epson representative.

For further information please contact your local Epson office or visit www.epson-europe.com Austria 01 253 49 78 333 Belgium +32 (0)2 792 04 47 Czech 800/142 052 Denmark 44 50 85 85 Finland 0201 552 091 France 09 74 75 04 04

(Cost of local call, operator charges may apply) Germany +49 (0) 2159/92 79 500 Greece +30 211 198 62 12 Hungary 06800 147 83 Ireland 01 436 7742

Italy 02-660321 10 (0,12 /min) Luxembourg +352 27860692 Middle East +9714 8872172 Netherlands +31 (0)20 708 5099 Norway +47 67 11 37 00

Poland 0-0-800 4911299 (0,16 zl/min) Portugal 707 222 111 Russia (095) 777-03-55 Slovakia 0850 111 429 South Africa (+2711) 1. Requires free Epson Projector Content Manager 465-9621

Spain 93 582 15 00 Sweden 0771-400135 (Mobilsamtal - 0,99 kr/min, Lokala samtal - 0,30 kr/min, Utlandssamtal - 0,89 kr/min) Switzerland 022 592 7923 Turkey (0212) 3360303 United Kingdom 0871 222 6702

LightScene EV-115

EPSON[®]

software or Epson Creative Projection app.

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice.