WorkForce Enterprise WF-M21000 D4TW



With print speeds of up to 100ppm, this affordable ecoresponsible mono MFP offers reliability and outstanding performance.

Print up to 120,000 pages in mono without changing the supplies¹. This reliable, low maintenance 4-in-1 device² offers high-speed performance, superior image quality, all with significant sustainability advantages over laser models.

Superior quality at high speeds

The WorkForce Enterprise WF-M21000 delivers superior image quality at print speeds of up to 100ppm and a fast first copy out time (FCOT) of 4.9 seconds³.

Super high ink yield

Print up to 120,000 in mono without changing the ink supplies.¹ This means there is even less need for user intervention. Through fewer consumables and supplies, it also produces less packaging. With ultra-low power consumption, the overall environmental impact of printing is cut dramatically.

Robust, high-end finishing capability

With advanced finishing such as booklet finisher and hole punch options, this device offers advanced finishing capability. It also offers a high paper capacity of up to 5,350 pages, increasing productivity further.


Heat-Free technology

Epson Heat-Free PrecisionCore Technology requires no heat to warm up when it is switched on or awoken from sleep, which significantly reduces energy consumption. This allows Epson's Heat-Free inkjets to deliver a fast FCOT compared to laser technology.

Advanced software solution compatibility

A variety of software solutions can be integrated into existing IT infrastructure to improve efficiency. This includes Epson's Epson Remote Services (ERS) which offers cloud-based device monitoring and management system that delivers advanced remote diagnostics for Epson business products.

DATASHEET / BROCHURE



KEY FEATURES

- Faster performance Fast FCOT of 4.9 seconds³ and print speeds of up to 100ppm
- High capacity ink yield Users can print up to 120,000 without changing the ink supplies¹
- Improved finishing capability Robust finishing such as booklet finisher and hole punch options
- Powerful scanning capability Thin paper support and improved quality of scanning
- Works with Epson Remote Services Cloud based, advanced diagnosis of Epson printers and MFPs



TECHNOLOGY		
Printing Method	PrecisionCore™ Micro TFP printhead	
Minimum Droplet Size	3.5 pl	
Ink Technology	DURABrite™ Pro Office Departmental	
Category		
All-in-One Functions	Print, Scan, Copy	
PRINT		
First Page Out	Monochrome 4.9 Seconds, According to IEEE/ISO 17629	
Printing Speed ISO/IEC 24734	4 100 pages/min Monochrome	
Duplex Printing Speed	100 A4 Pages/min Monochrome	
ISO/IEC 24734		
Printing Speed ISO/IEC 24734	1 54 pages/min Monochrome	
(A3)		
Maximum Printing Speed	100 pages/min Monochrome (plain paper 75 g/m²)	
Printing Resolution	600 x 2,400 DPI	
Printing Volume	400,000 pages per month	
	The maximum number of printed pages per month based on the performance capabilities of	
	the printer, including ISO rated print speeds and paper handling capabilities.	
Recommended Duty Cycle	8,000 - 100,000 pages per month	
Colours	Black	
Print from	PC, MAC, Network, USB, Cloud, Direct USB, PC (Wired), PC (Wireless), Mobile Device (WiFi	
	Direct), File on Device (Requires HDD/SSD)	
For detailed information on p	rinting speeds please visit http://www.epson.eu/testing.	
SCAN		
Double-sided scanning	Yes	
Single-sided scan speed (A4	200 DPI	
black)		
Scanning Speed	60 ipm (Monochrome, Single-sided, 300 dpi, ADF); 110 ipm (Monochrome, Double-sided,	

Scanning Speed	60 ipm (Monochrome, Single-sided, 300 dpi, ADF); 110 ipm (Monochrome, Double-sided,
	300 dpi, ADF); 60 ipm (Colour, Single-sided, 300 dpi, ADF); 110 ipm (Colour, Double-sided,
	300 dpi, ADF);
Optical Resolution	600 DPI x 600 DPI (Horizontal x Vertical)
Optical Resolution (ADF)	600 DPI x 600 DPI (Horizontal x Vertical)
Advanced document	Scan to Email, Scan to FTP, Scan to USB, Computer (Epson Document Capture Pro), USB
integration	Memory Device / Card
Output formats	BMP, JPEG, TIFF, multi-TIFF, PDF, PNG
Scanner type	Contact image sensor (CIS)
Optical Resolution	600 DPI x 600 DPI (Horizontal x Vertical)

WorkForce Enterprise WF-M21000 D4TW

WHAT'S IN THE BOX

- Information sheet
- Power cable
- User guide



FAX	
Type of fax	Walk-up black and white and colour fax capability
Fax Transmission Speed	Up to 33.6kbps / Approx. 3 sec/page
Error correction mode	CCITU/ITU Group3 fax with Error Correction Mode
Fax speed dials (max)	2,000 names and numbers
Page memory	Up to 550 pages/ 6MB (ITU-T No. 1 chart)
Fax Functions	PC Fax, Fax to E-mail, Memory Reception, Auto Redial, Fax to Folder, Address Book, Fax
	Preview, Polling Reception
СОРҮ	
Copy Speed	Up to 100 ipm Black
	*Simplex ADF 600 x 600 dpi (ISO/ IEC 24735)
Copy resolution (dpi)	600 x 600
Reduction / Enlargement	25 % - 400 %
Maximum number of copies	9,999
Maximum Copy Size	A3
CONNECTIVITY	
Network Printing Protocols	IPP, LDP, Port 9100, WSD
Network Management	SNMP, HTTP, DHCP, BOOTP, APIPA, DDNS, mDNS, SNTP, SLP, WSD, LLTD, Ping
Protocols	
Network Protocol	IPv4, IPv6
Network Scanning Protocols	
Interfaces	10 Base-T, Ethernet interface (100 Base-TX / 10 Base-T), Ethernet 1000, Ethernet Interface
internation	(1000 Base-T/ 100-Base TX/ 10-Base-T), Wireless LAN IEEE 802.11a/b/g/n, Wi-Fi Direct, USB
	1.0-A, USB 2.0-A, USB 3.0 Type B
WLAN Security	WEP 64 Bit, WEP 128 Bit, WPA PSK (TKIP), WPA PSK (AES)
Network Protocol	TCP/IPv4, TCP/IPv6, TCP, HTTP, HTTPS, IPv4, IPv6, IPSEC, SSL/TLS
	10F/IFV4, 10F/IFV0, 10F, 1111F, 1111F3, IFV4, IFV0, IF3E0, 33E/1E3
PAPER / MEDIA HANDLING	
Paper Formats	A3 (29.7x42.0 cm), A4 (21.0x29.7 cm), Postcard, A3+, A5 (14.8x21.0 cm), A6 (10.5x14.8 cm), B4,
	B5, B6, C4 (Envelope), C5 (Envelope), C6 (Envelope), DL (Envelope), Executive, Letter, Legal,
	HLT, No. 10 (Envelope), User defined
Automatic Document Feed	150 pages
Compatible Paper Weight	60 g/m² - 350 g/m²
Duplex	Yes (A4/A3, plain paper)
Standard Paper input	2,350 Sheets Standard, 150 Sheets MP tray, 550 Sheets paper tray
Output Tray Capacity	550 Sheets
Maximum paper input	5,350
Number of paper trays	4
PAPER FEED RASF	
Paper Input Name	RASF
Paper Formats	A3+, A3, A4, A5, A6, B4, B5, B6, C4 (Envelope), C5 (Envelope), C6 (Envelope), DL (Envelope),
	Letter, 20 x 25 cm, HLT, User defined, SRA3
Custom sizes	Min 55x 330 mm to Max 127x 1,200 mm
Custom sizes Compatible paper weight	
	Min 55x 330 mm to Max 127x 1,200 mm

WorkForce Enterprise WF-M21000 D4TW



PAPER FEED C1	
Paper Input Name	C1
Paper Formats	A3, A4, A5, B4, B5, Letter, HLT, Executive
Custom sizes	Min 140x 297 mm to Max 182x 432 mm
Compatible paper weight	60 g/m ² - 160 g/m ²
Paper Capacity 1	550 80qsm
Media type	Plain Paper, Recycled Paper, Colour Paper, Letterhead
PAPER FEED C2-C4	
Paper Input Name	C2-C4
Paper Formats	A3, A4, A5, B4, B5, Letter, HLT
Custom sizes	Min 140x 297 mm to Max 182x 432 mm
Compatible paper weight	60 g/m² - 160 g/m²
Paper Capacity 1	550 80gsm
Media type	Plain Paper, Recycled Paper, Colour Paper, Letterhead
PAPER FEED LCT	
Paper Input Name	LCT
Paper Formats	A4, Letter
Compatible paper weight	60 g/m² - 160 g/m²
Paper Capacity 1	3,000 80gsm
Media type	Plain Paper, Recycled Paper, Colour Paper, Letterhead
PAPER FEED DUPLEX	
Paper Input Name	Duplex
Compatible paper weight	60 g/m² - 160 g/m²
	oo gini - roo gini
GENERAL	
Energy Use	170 Watt (standalone copying, ISO/IEC 24712 pattern), 1.1 Watt (sleep mode), 76 Watt
	(Ready), 0.1 Watt (Power off), TEC 0.4 kWh/week
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz
Product dimensions	674 x 757 x 1,243 mm (Width x Depth x Height)
Product weight	186 kg
Compatible Operating	Mac OS 10.10.x, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Mac OS X 10.11.x, Mac OS X
Systems	10.12.x, Mac OS X 10.13.x, Mac OS X 10.6.8, Windows 10 (32/64 bit), Windows 7 (32/64 bit),
	Windows 8 (32/64 bit), Windows 8.1 (32/64 bit), Windows Server 2003 R2 x64, Windows Server
	Windows 8 (32/64 bit), Windows 8.1 (32/64 bit), Windows Server 2003 R2 x64, Windows Server 2003 SP2, Windows Server 2008 R2, Windows Server 2016, Windows Vista (32/64 bit),
	Windows 8 (32/64 bit), Windows 8.1 (32/64 bit), Windows Server 2003 R2 x64, Windows Server 2003 SP2, Windows Server 2008 R2, Windows Server 2016, Windows Vista (32/64 bit), Windows XP SP3, Windows XP SP3 or later (32-bit), Windows Server 2003 SP2 or later, XP
	2003 SP2, Windows Server 2008 R2, Windows Server 2016, Windows Vista (32/64 bit),
Sound Power	2003 SP2, Windows Server 2008 R2, Windows Server 2016, Windows Vista (32/64 bit), Windows XP SP3, Windows XP SP3 or later (32-bit), Windows Server 2003 SP2 or later, XP
Sound Power Noise	2003 SP2, Windows Server 2008 R2, Windows Server 2016, Windows Vista (32/64 bit), Windows XP SP3, Windows XP SP3 or later (32-bit), Windows Server 2003 SP2 or later, XP Professional x64 Edition SP2
	2003 SP2, Windows Server 2008 R2, Windows Server 2016, Windows Vista (32/64 bit), Windows XP SP3, Windows XP SP3 or later (32-bit), Windows Server 2003 SP2 or later, XP Professional x64 Edition SP2 Operation: 7.5 B (A)
Noise Power supply	2003 SP2, Windows Server 2008 R2, Windows Server 2016, Windows Vista (32/64 bit), Windows XP SP3, Windows XP SP3 or later (32-bit), Windows Server 2003 SP2 or later, XP Professional x64 Edition SP2 Operation: 7.5 B (A) Operation: 60 dB (A)
Noise Power supply ADDITIONAL FEATURES	2003 SP2, Windows Server 2008 R2, Windows Server 2016, Windows Vista (32/64 bit), Windows XP SP3, Windows XP SP3 or later (32-bit), Windows Server 2003 SP2 or later, XP Professional x64 Edition SP2 Operation: 7.5 B (A) Operation: 60 dB (A) 220V, 240V
Noise Power supply ADDITIONAL FEATURES Features	2003 SP2, Windows Server 2008 R2, Windows Server 2016, Windows Vista (32/64 bit), Windows XP SP3, Windows XP SP3 or later (32-bit), Windows Server 2003 SP2 or later, XP Professional x64 Edition SP2 Operation: 7.5 B (A) Operation: 60 dB (A) 220V, 240V
Noise Power supply ADDITIONAL FEATURES Features Panel	2003 SP2, Windows Server 2008 R2, Windows Server 2016, Windows Vista (32/64 bit), Windows XP SP3, Windows XP SP3 or later (32-bit), Windows Server 2003 SP2 or later, XP Professional x64 Edition SP2 Operation: 7.5 B (A) Operation: 60 dB (A) 220V, 240V Touchscreen Type: Color, Touchscreen, Diagonal: 22.7 cm
Noise Power supply ADDITIONAL FEATURES Features Panel Media Handling	2003 SP2, Windows Server 2008 R2, Windows Server 2016, Windows Vista (32/64 bit), Windows XP SP3, Windows XP SP3 or later (32-bit), Windows Server 2003 SP2 or later, XP Professional x64 Edition SP2 Operation: 7.5 B (A) Operation: 60 dB (A) 220V, 240V Touchscreen Type: Color, Touchscreen, Diagonal: 22.7 cm Duplex (A4/A3, plain paper)
Noise Power supply ADDITIONAL FEATURES Features Panel	2003 SP2, Windows Server 2008 R2, Windows Server 2016, Windows Vista (32/64 bit), Windows XP SP3, Windows XP SP3 or later (32-bit), Windows Server 2003 SP2 or later, XP Professional x64 Edition SP2 Operation: 7.5 B (A) Operation: 60 dB (A) 220V, 240V Touchscreen Type: Color, Touchscreen, Diagonal: 22.7 cm Duplex (A4/A3, plain paper) Limit access function with Epson Web Config, Secure confidential printing with PIN code
Noise Power supply ADDITIONAL FEATURES Features Panel Media Handling	2003 SP2, Windows Server 2008 R2, Windows Server 2016, Windows Vista (32/64 bit), Windows XP SP3, Windows XP SP3 or later (32-bit), Windows Server 2003 SP2 or later, XP Professional x64 Edition SP2 Operation: 7.5 B (A) Operation: 60 dB (A) 220V, 240V Touchscreen Type: Color, Touchscreen, Diagonal: 22.7 cm Duplex (A4/A3, plain paper) Limit access function with Epson Web Config, Secure confidential printing with PIN code release, LDAP Address Book, IPsec, IEEE802.1x, SSL (Server authentication), Panel Admin
Noise Power supply ADDITIONAL FEATURES Features Panel Media Handling	2003 SP2, Windows Server 2008 R2, Windows Server 2016, Windows Vista (32/64 bit), Windows XP SP3, Windows XP SP3 or later (32-bit), Windows Server 2003 SP2 or later, XP Professional x64 Edition SP2 Operation: 7.5 B (A) Operation: 60 dB (A) 220V, 240V Touchscreen Type: Color, Touchscreen, Diagonal: 22.7 cm Duplex (A4/A3, plain paper) Limit access function with Epson Web Config, Secure confidential printing with PIN code

WorkForce Enterprise WF-M21000 D4TW



OTHER FEATURES Emulations

PCL5c, PCL6, PostScript 3, PDF 1.7, ESC/P, ESC/P-R, PCL5e, ESC/Page, ESC/Page-Colour

SUPPLIES

WFE Paper Feed Roller for Cassette

Maintenance box

C12C935961 C13T671300

OPTIONAL ACCESSORIES

• EpsonNet 10/100/1000Base Tx Int C12C934471

- Cassette Lock C12C933231
- Super G3/G3 Fax Board C12C934491
- LOGISTICS INFORMATION

SKU	C11CJ87401 C11CJ87401BY
EAN code	8715946688275
Country of Origin	Indonesia



* Warranty offers are not available for all countries. Please contact your local Epson representative.

For further information please contact your local Epson office or visit www.epson-europe.com Austria 01 253 49 78 333 Belgium +32 (0)2 792 04 47 Czech 800/142 052 Denmark 44 50 85 85 Finland 0201 552 091 France 09 74 75 04 04

(Cost of local call, operator charges may apply) Germany +49 (0) 2159/92 79 500 Greece +30 211 198 62 12 Hungary 06800 147 83 Ireland 01 436 7742

Italy 02-660321 10 (0,12 /min) Luxembourg +352 27860692 Middle East +9714 8872172 Netherlands +31 (0)20 708 5099 Norway 3. 3Approx. based on internal testing; may vary depending +47 67 11 37 00 Poland 0-0-800 4911299 (0,16 zl/min) Portugal 707 222 111 Russia (095) 777-03-55 Slovakia 0850 111 429 South Africa (+2711)

465-9621 Spain 93 582 15 00 Sweden 0771-400135 (Mobilsamtal - 0,99 kr/min, Lokala samtal - 0,30 kr/min, Utlandssamtal - 0,89 kr/min)

Switzerland 022 592 7923 Turkey (0212) 3360303 United Kingdom 0871 222 6702

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice.

1. ¹Approx. page yield with the WF-M21000. Actual yield

will vary depending on images printed and usage conditions. For more information visit

www.epson.eu/pageyield. 2. ²Fax optional in certain territories at an additional cost. Please contact your local Epson office for more information.

on the number of copies selected, the output environment, as well as the settings for size, orientation, position of paper.



WorkForce Enterprise WF-M21000 D4TW