

- CAL-ROYAL'S FINEST HYDRAULIC DOOR CLOSER SERIES MEETING THE HIGHEST INDUSTRY STANDARDS, GRADE 1
- HEAVY-DUTY FULL FEATURE MULTI-SIZE COMMERCIAL DOOR CLOSER FOR USE IN OFFICE BUILDINGS, SHOPPING CENTERS AND OTHER COMMERCIAL BUILDINGS
- STANDARD BACK-CHECK FUNCTION
- FULL PLASTIC COVER IS STANDARD FEATURE (METAL OPTIONAL)
- OPTIONAL PLATED DECORATIVE COVERS ARE AVAILABLE
- OPTIONAL ADJUSTABLE DELAYED ACTION FOR HANDICAPPED OR ELDERLY

UL Listed, Conforms to Standards UL10C, UBC-7-2-1997 UL10C and UBC-7-2-1997

900 Series Door Closer

Full Cover Multi-size Full Feature Closer ANSI 156.4 Grade 1 UL Listed, Conforms to Standards UL10C and UBC7-2-1997 BHMA Certified Lifetime Warranty




ECURITIES

900 Series Door Closer

Conforms to Standards UL10C and UBC7-2-1997





DESCRIPTION

()

FEATURES

- Hydraulic Door Closer
- ANSI 156.4 Grade 1: UL Listed for fire door assemblies
- Universal application. Non-handed for standard, top-jamb or parallel arm installation
- Non-sized, 1 thru 6 FACTORY PRESET SIZE 3
- Door weights: 30-260 lbs (All Models)
- Standard adjustable back-check function
- Adjustable closing and latching speed by two separate regulating valves
- Standard full plastic cover
- Available in Alum, Duro, Gold, White, US3, 26, 26D, 10, 15, 10B, 32D, 4 and 5 Finishes
- Optional adjustable delayed action (DA) Preset at the factory for approximately 20 seconds, between 70° and 0° Delay time easily adjusted up to 1 minute.

ACCESSORIES

- Parallel arm drop bracket for non-hold open parallel arm applications to clear a surface-applied stop/holder. 904
- Parallel hold-open adjustable arm (Non handed). 901/902
- Optional Steel or Stainless Metal cover
- Optional, non-handed parallel arm features solid forged steel main arm and forearm with stop in soffit shoe. SPAS/900
- Optional, non-handed parallel arm features solid forged steel main arm and forearm provides hold-open function with templated stop/hold-open points. Handle controls hold-open function. HORSPS/900
- Optional Slide Track Arm. TRACK/900 with hold open
- Flat drop bracket 950
- Super rigid non handed parallel arm with spring loaded stop in the soffit shoe. Equivalent to LCN SPRING CUSH ARM. 900SPRNG
- Super rigid parallel arm stopper hold open, non-handed with spring loaded stop in soffit shoe. Handle controls hold open function. Equivalent to LCN SPRING H-CUSH ARM. 900HOSPRING

CROSS REFERENCES

	A. Length of Closer Body			11 ¾"	C C			0		
B. Horizontal Mounting				Holes	11 ¹ / ₈ "		FRON	B		
ina	C. Verti	cal Mour	iting H	oles	9/ " 16		FRON	E		
ing	D. Height of Closer Body						D	، ا	END VIEW	
_	E. Proje	ection fro	m Doo	r	2 ⁷ / ₈ "			Ţ		
B, EXTERIOR (and VESTIBULE) DOOR WIDTH										
	2	4"	30"	,	36"	42"	4	8"		
	900 Series	size 3	•	size 4	size	5	size 6			
	Minimur	n Door W	idth							
	INTE	RIOR D	OOR	WIDTH	I					
	2	4"	34"		38"	48"	5	4"	60"	
	900	size 2	-	size 3	size	4	size 5	size	6	_
	900 Series				►					
	Minimur	n Door W	idth				Adjusta	able Size	→ e 1 thru 6	
900H	OSPRING	<u>୍</u>		900SPR			901/9	02		
	/	× l						2/		
K	<u></u>		Ì	65	2					Ð
HOSE	RPS/900	ĺ		TRACK/	900		SPAS	900	Q	
(Leg				C		000				

Barrier free (BF) Meets ADA regulation. Size 1 thru 6. Engineered with


SIZE

reduced spring power to provide easier opening for handicapped or elderly.

c

Specify "MADE IN KOREA" when ordering "THE BUY AMERICAN ACT" compliant models

Ø



COMPARISON CHART 300 SERIES

CAL-ROYAL	CORBIN	DORMA	DOR-O-MATIC	HAGER	LCN	NORTON	RUSSWIN	SARGENT	YALE
900 FULL COVER	DC3200	8600FC	SC80FC	5200	1460FC	8501	DC3200	1431	3501

The data on this chart represents our judgment of which are most similar. Since no product is exactly alike the information has been obtained from trade sources, it is not guaranteed nor represented that any specific product exactly equals any other product. Door closer body size may be different.



6605 Flotilla St. Commerce, CA 90040 USA Tel: (323) 888-6601 Fax: (323) 888-6699 Website: www.cal-royal.com Email: sales@cal-royal.com

Ver.	3.0,	Rev.	05/15 ROYAL
©2015	A	CAL-	ROYAL