

## BEAT GREEN/20X40

Model: **BEAT GREEN/20X40**  
Reference: **29901 GREEN**  
Size: **20X40** cm  
Thickness: **10,30** mm  
Finish: **Natural**  
Body Type: **WALL TILE - GROUP BIII**  
**GL - GLAZED Ceramic Tile**

### Water absorption

EN ISO-10545-3	Water absorption	> 10%
----------------	------------------	-------

### Dimensional characteristics

EN ISO-10545-2	Surface quality	> 95%
EN ISO-10545-2	Curvature flatness	·0,5/-0,3% +2,0/-1,5 mm
EN ISO-10545-2	Thickness	± 10% / ± 0,5 mm
EN ISO-10545-2	Length and Width	± 0,5 % / ± 2,0 mm
EN ISO-10545-2	Rectangularity	± 0,5% / ± 2,0 mm
EN ISO-10545-2	Straightness of sides	± 0,3 % / ± 1,5 mm

### Mechanical characteristics

EN ISO 10545-11	Crazing resistance	Pass
EN ISO 10545-9	Thermal shock resistance	Pass
EN ISO-10545-4	Breaking strength	> 600 N
EN ISO-10545-4	Modulus of rupture	> 12 N/mm <sup>2</sup>

### Surface characteristics

EN ISO 10545-7	Visible failure at No of revolutions	-
EN-101	Surface scratch resistance	3

### Chemical characteristics

EN ISO-10545-13	High concentrations of acids and alkalis	HB/HB/GHA*
EN ISO-10545-13	Low concentrations of acids and alkalis	LB/GLA*/GLA*
EN ISO-10545-13	Household chemicals and swimming pool salts	A/A
EN ISO-10545-14	Stain resistance	5/-/5/5

## BEAT GREEN/20X40

Model: **BEAT GREEN/20X40**  
Reference: **29901**      **GREEN**  
Size: **20X40**      cm  
Thickness: **10,30**      mm  
Finish: **Natural**  
Body Type: **WALL TILE - GROUP BIII**  
**GL - GLAZED Ceramic Tile**

### Non-slip characteristics

DIN-51130	Critical angle (footwear)	-
-----------	---------------------------	---

### CE MARKING



CE Declaration of Performance: **004CPR2017-08-01**