



Model: Topping-R Avellana
Size: 32 x 99cm
Thickness: 11mm
Material type: White Body
Group: BIII annex L

TECHNICAL DATA

| | | |
|---|---|--------------------------|
| Manufacture process | Single-firing | Dry pressed ceramic tile |
| Length, width, thickness, side straightness, ortogonality, flatness | Conforms to the requisites applicable to each model as defined in standard UNE-EN 14411 | UNE EN ISO 10545 Part 2 |
| Water absorption | E > 10% | UNE EN ISO 10545 Part 3 |
| Flexion resistance (N/mm.2) y and breaking strength (N) | > 15 > 600 | UNE EN ISO 10545 Part 4 |
| Lineal thermic dilatation | < 7*10 ⁻⁶ /°C | UNE EN ISO 10545 Part 8 |
| Thermic impact resistance | Stands the test | UNE EN ISO 10545 Part 9 |
| Expansion due to moisture | < 0.6% | UNE EN ISO 10545 Part 10 |
| Cracking resistance | Stands the test | UNE EN ISO 10545 Part 11 |

CHEMICAL RESISTANCE

| | | |
|-------------------------------------|-------------------|--------------------------|
| Domestic cleaning products | Class GA | |
| Swimming pool salt | Class GA | UNE EN ISO 10545 Part 13 |
| Acids and bases (low concentration) | Minimum Class GLB | |
| Stains resistance | Minimum Class 4 | UNE EN ISO 10545 Part 14 |