

ARTE MOCHA SP/100X100/R

| | | |
|------------|--|----|
| Model: | ARTE MOCHA SP/100X100/R | |
| Reference: | MOCHA | |
| Size: | 100X100 | cm |
| Thickness: | 8,00 | mm |
| Finish: | Shaped | |
| Body Type: | PORCELAIN - GROUP BIa UGL - UNGLAZED Ceramic Tile | |

Water absorption

| | | |
|----------------|------------------|-------------------|
| EN ISO-10545-3 | Water absorption | < 0,5 % |
|----------------|------------------|-------------------|

Dimensional characteristics

| | | |
|----------------|-----------------------|---------------------------|
| EN ISO-10545-2 | Surface quality | > 95% |
| EN ISO-10545-2 | Curvature flatness | ± 0,5 % / ± 2,0 mm |
| EN ISO-10545-2 | Thickness | ± 5% / ± 0,5 mm |
| EN ISO-10545-2 | Length and Width | ± 0,6 % / ± 2,0 mm |
| EN ISO-10545-2 | Rectangularity | ± 0,5% / ± 2,0 mm |
| EN ISO-10545-2 | Straightness of sides | ± 0,5 % / ± 1,5 mm |

Mechanical characteristics

| | | |
|-----------------|--------------------------|---------------------------------|
| EN ISO 10545-11 | Crazing resistance | Pass |
| EN ISO 10545-12 | Frost resistance | Pass |
| EN ISO 10545-9 | Thermal shock resistance | Pass |
| EN ISO-10545-4 | Breaking strength | > 1300 N |
| EN ISO-10545-4 | Modulus of rupture | > 35 N/mm² |

Surface characteristics

| | | |
|----------------|--------------------------------------|--------------------------------|
| EN ISO 10545-7 | Visible failure at No of revolutions | - |
| EN ISO-10545-6 | Deep abrasion resistance | < 175 mm³ |
| EN-101 | Surface scratch resistance | 5 |

Chemical characteristics

| | | |
|-----------------|---|-----------------|
| EN ISO-10545-13 | High concentrations of acids and alkalis | HA/HA/HA |
| EN ISO-10545-13 | Low concentrations of acids and alkalis | LA/LA/LA |
| EN ISO-10545-13 | Household chemicals and swimming pool salts | A/A |

ARTE MOCHA SP/100X100/R

Model: **ARTE MOCHA SP/100X100/R**
Reference: **34704** **MOCHA**
Size: **100X100** cm
Thickness: **8,00** mm
Finish: **Shaped**
Body Type: **PORCELAIN - GROUP BIa**
UGL - UNGLAZED Ceramic Tile

Chemical characteristics

| | | |
|-----------------|------------------|----------------|
| EN ISO-10545-14 | Stain resistance | 5/-/5/5 |
|-----------------|------------------|----------------|

Non-slip characteristics

| | | |
|-----------|--|------------------|
| ANSI A137 | Dynamic coefficient of friction (DCOF) | > 0,42 |
|-----------|--|------------------|

| | | |
|-------------------|---------------------------------|----------|
| UNE-41901:2017 EX | Slip resistance (pendulum test) | 1 |
|-------------------|---------------------------------|----------|

CE MARKING



CE Declaration of Performance: **001CPR2017-08-01**