

DECLARATION OF PERFORMANCE
In accordance with Annex III of Regulation (EU) 305/2011
(Construction Product Regulation)
amended by Commission Delegated Regulation (EU) No. 574/2014

No. 000070-CPR/2014

1. Unique identification code of the product-type:

ARDEX ST

2. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Sealant for joints for facades, sanitary areas and pedestrian walkways

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11(5):

**ARDEX UK Limited,
Homefield Road,
Haverhill,
Suffolk,
CB9 8QP**

4. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**System 3
System 3 for reaction to fire**

- 6a. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

EN 1561-2012-12

**The notified body MATERIALPRUGUNGSAMT NORDRHEIN-WESTFALEN (MPA NRW)
with the identification number 0432 performed the test according to:
EN15651-2012-12, parts 1, 3 and 4.
The notified body MATERIALPRUFUNGSAMT NORDRHEIN-WESTFALEN (MPA NRW) with the
identification number 0432 performed the reaction to fire.**

- 6b. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not applicable

7. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire:	Class E	EN 15651-1:2012-12 EN 15651-3:2012-12 EN 15651-4:2012-12
Resistance to flow:	≤ 3mm	
Loss of volume:	≤ 10 %	
Tensile properties at maintained extension:	Passed (NF)	
Tear resistance:	Passed (NF)	
Tensile properties: 1) Secant modulus At + 23°C: At - 30°C:	≥ 0.4 MPa ≤ 0.9 MPa	
Tensile properties at maintained extension in cold climate at -30°C:	Passed (NF)	
Adhesion/cohesion at maintained extension after water immersion at 23°C:	Passed (NF)	
Microbiological growth:	0	
Durability:	Passed	
Release of dangerous substances:	See SDS	

8. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No. 305/2011 amended by Commission Delegated Regulation (EU) No. 574/2014, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Ian Smith
Laboratory Manager

Haverhill

05/04/19 R1