



BURAL SOLAR

Thermosiphon Solar Water Heater



	Description	KD160HP	KD200HP	KD300HP
TANK	Type	Closed loop (indirect system)		
	Weight (Kg)	67	78	118
	Dimensions (mm)	Ø600×1000	Ø600×1200	Ø600×1800
	Model	160L	200L	300L
	Insulation	PU foam		
	Outside cover	Painted and galvanised steel		
	Insulation thickness (mm)	50 mm		
	Inner coating	Enamel		
	COLLECTOR	Overall area (m ²)	1,8	2,3
Weight (kg)		26	34	52
Housing material		Aluminum frame		
Housing treatment		Anodized		
Back sheet material		Aluminum		
Absorber sheet		Blue high-selective coated full-plate laser welded absorber		
Connections		3/4" brass female thread		
Transparent cover		4 mm tempered glass		
Insulation		Mineral wool		
Heat transfer medium		Mixture of glycol + water		
Mounting set		Flat roof / Pitched roof		
Mounting set material		Galvanised steel		
Accessories & fittings		Corrugated stainless steel flexible hoses.		
Safety group		Solar safety valve, one-way valve, safety valve for DHW		

*sizes and specifications are subject to change without any prior notice.



Bundesamt
für Wirtschaft und
Ausfuhrkontrolle

BURAL SOLAR INDUSTRY LTD.

Address: Serbest Bölge 12. Cadde No:24-A, Melikgazi 38070, KAYSERI/TURKEY

E-mail: info@bural.com.tr

www.bural.com.tr