



PRODUCT INFORMATION SHEET

ALL STONE SEALER

HIGH GLOSS SURFACE SEAL



Description

ALL-STONE SEALER is an acrylic emulsion water borne sealer used for the sealing of slate, terracotta, sandstone, limestone, clay and cement pavers.

ALL-STONE SEALER inhibits water and oil based stains while maintaining the natural appearance of the surface being sealed.

Features and Benefits

- ❖ Excellent adhesion to "chalky" surfaces, lightly soiled concrete, masonry and slate tiles.
- ❖ Good resistance to abrasion, water, detergents and oil based stains.
- ❖ Rapid hardness development.
- ❖ Fast set and tack-free times.
- ❖ Provides a water based alternative to solvent borne acrylics.
- ❖ Excellent gloss and levelling characteristics enabling surfaces to be sealed ranging from extremely porous tiles to dense tiles.
- ❖ Ideal for Sealing Slate, Sandstone, Limestone, Clay and Cement Pavers

Method of Use

1. In order to determine the compatibility of **ALL-STONE SEALER** with your floor A test area of one or two tiles should be attempted before sealing the entire floor. If this finish meets your requirements continue to seal the remaining tiles.
2. Ensure that the surface to be sealed is completely clean and dry. Any stains, soil, cement or grouting present on the surface should be removed prior to sealing using LIFT OFF and TILE KLEEN as per instructions.

The Product Information Sheet supersedes all previous issues for this product. Information contained herein is offered in good faith as being true and accurate to the best of our knowledge, but as the conditions of use are beyond our control, no guarantees are either stated or implied. Where health or safety data given discloses a risk to the user or the environment, it is the responsibility of the purchaser to pass on the information to employees who may be using the product, ensuring that adequate safety procedures are used, including good industrial hygiene.



PRODUCT INFORMATION SHEET

ALL STONE SEALER

HIGH GLOSS

SURFACE SEAL

Method of Use (con)

3. Newly laid areas require 4-6 weeks to allow mortar and grout to cure prior to sealing.
4. Allow the tiles to dry thoroughly prior to sealing by leaving for at least 24 hours after cleaning and washing.
5. Do not seal hot surfaces - all surfaces must be cool.
6. Apply three or four even generous coats of **ALL-STONE SEALER** using a paint brush or lambswool applicator. Allow approximately 4 hours between applications.
7. Allow 24 hours for product to cure before allowing full use of the treated surface.
8. In order to gain maximum benefit from the use of **ALL-STONE SEALER** it is recommended that all spills and soiling materials be removed from treated floors as soon as possible after the spill using Tile Kleen.
9. Re-application of **ALL-STONE SEALER** may be necessary every 12 months or as necessary dependent on the traffic and soiling.
10. Brushes and application equipment may be cleaned with a hot solution of TILE KLEEN. Reseal container after use to prevent deterioration of the product.
11. As this product is used under conditions beyond our control, the seller will not be responsible for results obtained. Liability is restricted to the replacement of any material if proven faulty and the manufacturer is not responsible for any loss or damage arising from incorrect usage. Determining the suitability of the product for any intended usage shall be the sole responsibility of the user.

Coverage: 1 Litre will cover approx. 8-20 square metres per coat depending on the porosity of the tiles.

WARNING: Do not use ALL-STONE SEALER on surfaces in areas that are exposed to ground water or salt water from swimming pools. These areas can accumulate salt deposits, causing efflorescence and flaking of the sealer

Packaging

◆ 1 Litre Bottles ◆ 5 Litre polyethylene drums ◆ 15 Litre polyethylene drums

Health Hazard Information

See separate Health and Safety Data Sheet, available on request.

The Product Information Sheet supersedes all previous issues for this product. Information contained herein is offered in good faith as being true and accurate to the best of our knowledge, but as the conditions of use are beyond our control, no guarantees are either stated or implied. Where health or safety data given discloses a risk to the user or the environment, it is the responsibility of the purchaser to pass on the information to employees who may be using the product, ensuring that adequate safety procedures are used, including good industrial hygiene.