

Material Safety Data Sheet

SECTION 1. PRODUCT IDENTIFICATION

Product name: *Multi-Purpose Interior Filler*
Synonym: Interior Filler
Product Codes: **3500, 3515**

Physical Form: Paste
Odour: Mild Acrylic Odour
CAS No.: Mixture
Flammability: Material may not burn in wet state

Manufacturer: UNI-PRO PAINTING EQUIPMENT
Supplier Address: Units 9-12, 144-150 Canterbury Road, Kilsyth VIC 3137
Supplier Contact: Customer Service
Telephone: 03 9761 7900
Fax: 03 9761 6522

SECTION 2. COMPOSITION AND HAZARDOUS COMPONENTS

Chemical Name	CAS Number	APPROX WT%
Latex Emulsion	--	5%
Water	--	22.5%
Ethylene Glycol	107-21-1	0.3%
Mineral Spirits	64742-48-9	0.5%
Titanium Dioxide	13463-67-7	2%
Mineral Filler	--	69.2%
Additives	--	0.5%

SECTION 3. HAZARD IDENTIFICATION

Ingestion: None known.
Skin Contact: Uncured product contact may irritate the skin.
Eye Contact: Uncured product contact irritates eyes.
Inhalation: May cause mild respiratory irritation.

SECTION 4. FIRST AID MEASURES

Take off all contaminated clothing immediately.

In case of ingestion: Seek medical advice immediately.
In case of skin contact: Wipe with paper towel and immediately clean with water and soap.
In case of eyes contact: Immediately flush with water, seek medical advice if necessary.

Material Safety Data Sheet

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:	Water, foam, CO2, dry power and all standard fire-fighting media.
Unsuitable extinguishing media:	Unknown.
Hazardous decomposition:	Not specified.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Methods for cleaning up:	Take up mechanically.
---------------------------------	-----------------------

SECTION 7. HANDLING AND STORAGE

Handling:	Ensure good ventilation during processing. Wear safety shoes.
Protection against fire/ explosion:	General rules of fire prevention should be observed.
Storage:	Keep container tightly closed and dry.
Cautions:	Extreme heavy in drum form if product packed in 200L drum.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Ingredients with limited values to be controlled:	Not indicated.
Local exhaust:	Recommended.
General ventilation:	Recommended.
Hand protection:	Suitable protective gloves.
Eye protection:	Safety / protective glasses.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Form:	Paste
Specific gravity:	1.65
Colour:	
Viscosity:	Not indicated.
Odour:	Mild Acrylic Odour
Volatile % (25°C):	< 26.3%
VOC:	Less than 40g/ Liter [after deduct exempted solvent (water)]
Solubility in water:	Yes
Boiling point:	100°C
Flash point:	None known.
Ignition temperature:	None known.

Note: the above information is not intended for use in preparing specification.

Material Safety Data Sheet

SECTION 10. STABILITY AND REACTIVITY

Chemical stability:	Stable.
Incompatibility (material to be avoid):	None known.
Conditions to be avoid:	None known.
Dangerous reactions:	None known.
Dangerous products of decomposition:	No dangerous decomposition products known.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity:	Not determined.
Primary irritant effect on the skin:	Irritant for skin and mucous membranes.
On the eye:	Irritant effect.
Additional Toxicological information:	When used and handled according to specification, the product does not have any harmful effects according to our experience and the information provided to us.

SECTION 12. ECOLOGICAL INFORMATION

Complete information not yet available.

SECTION 13. DISPOSAL CONSIDERATIONS

For cured sealant landfill may be suitable.
With respect to local regulation, dispose of to suitable incineration plant.

SECTION 14. TRANSPORT INFORMATION

Proper shipping name:	Latex based Putty Filler (Joint Compound)
Hazard technical name:	Not available.
Hazard class:	Not available.

No dangerous goods under the transport regulation.

SECTION 15. REGULATORY INFORMATION

Labeling (EC):	This product is not subject to the labeling requirements of EC directives.
-----------------------	--

SECTION 16. OTHER INFORMATION

Date of last review: 16th May 2019

THE DATA ARE OFFERED IN GOOD FAITH AS TYPICAL VALUES AND NOT AS A PRODUCT SPECIFICATION. NO WARRANTY, EITHER EXPRESSED OR IMPLIED, IS HEREBY MADE. THE RECOMMENDED INDUSTRIAL HYGIENE AND SAFE HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THESE RECOMMENDATIONS IN THE SPECIFIC CONTENT OF THE INTENDED USE AND DETERMINE WHETHER THEY ARE APPROPRIATE.