

Cleaning - Protecting - Maintaining Quarry Tiles unglazed

Unglazed quarry tiles are extremely hard wearing and easy to maintain. Just rinsing the surface with water from time to time is not enough though - only the proper treatment ensures a well-maintained appearance.

Overview of the 3 Steps *for more detailed instructions, please refer to Page 2*

1

Initial cleaning of newly installed surfaces *used surfaces: Page 2*

Lithofin KF Cement Residue Remover removes grout residues and builders dirt.



Please Note:
allow grout lines to cure for several days before cleaning. Pre-wet the surface to avoid damage to grout lines.



Dilute product 1:5 with water.



Distribute and allow to work for 5 minutes, then scrub with a brush or broom.



Remove the solution from the surface.



Rinse well with plenty of clear water.



Allow to dry.

Coverage:
1Ltr./20m²

Necessary equipment: bucket, mop, broom, brush and scrubber, squeegee or wet-and-dry vacuum


2

Protecting against stains

Lithofin STAINSTOP >W< -invisible- protects against oil and water and simplifies maintenance.



Please note.




Pour product into bucket or basin.




Evenly apply with a brush or lamb's wool applicator.



Remove all excess with a squeegee and dry towel.



Allow to dry for approx. 45 minutes.



Protect from water for 24 hours.

Coverage:
1Ltr./15m²

Necessary equipment: bucket, lamb's wool applicator or brush, squeegee, towel

3

Regular maintenance


Use Lithofin KF Vitra-Clean regularly for well-maintained surfaces.



Add one squirt (20ml) to one bucket of water.



Wipe surface with solution and micro-fibre mop. Do not rinse.



Allow to dry. Do not walk on surface during drying time.

Necessary equipment: bucket, mop

Please follow the detailed instructions on the product labels. *for additional information, please refer to Page 2*

1 Cleaning and refurbishing used or extremely dirty surfaces

- ◆ Before treating used surfaces, the tile must be thoroughly cleaned. All deposits and care product residues must be removed from the surface, grout lines and from the pores.
- ◆ **Indoors:** dilute Lithofin KF Intensive Cleaner up to 1:5 with water and apply generously to the surface. Allow to work for 5 to 10 minutes.
- ➔ Brush well with a broom, brush or a scrubbing machine and allow another 5 minutes working time.
- ➔ Add water while brushing and remove the solution from the surface.
- ➔ Rinse twice with clear water in order to remove all residues from the surface.
- ◆ **Outdoors:** in case of dark spots and stubborn dirt deposits, apply Lithofin MN Outdoor Cleaner with a scrubbing brush and allow to work overnight. Rinse off with plenty of clear water the next day.
- ➔ Allow the surface to dry for several days before applying the protective treatment.



Other, stubborn types of dirt

grout residues, builders' dirt, calcium deposits	Lithofin KF Cement Residue Remover
oil and grease films, wax, sealants, fresh paint	Lithofin WAX-OFF
deep oil stains	Lithofin OIL-EX
algae, moss and green deposits	Lithofin ALGEX
heavy dirt deposits, tree matter, mould, etc.	Lithofin KF Mildew-Away or Lithofin MN Outdoor Cleaner

2 Additional information about protective treatments

- ◆ Impregnators such as Lithofin STAINSTOP >W< render the surface water and oil repellent.
- ◆ This protective effect reduces staining and facilitates every-day maintenance.
- ◆ The surface becomes easier to maintain and stays beautiful for many years.
- ◆ Lithofin STAINSTOP >W< provides optimal protection without altering the surface appearance.
- ◆ We recommend touching up the protective treatment after 4 to 5 years.

Please note:

- ◆ **Always test the product in an inconspicuous area.** Non-absorbent or wet surfaces cannot be treated.
- ◆ Use impregnators only on completely dry surfaces. Otherwise, the product will not be able to penetrate into the surface.

3 Additional care

- ◆ Occasionally use Lithofin KF Intensive Cleaner on surfaces subjected to heavy wear. Depending on the degree of dirt, dilute product up to 1:10 with water. Apply with a brush or broom for 10 to 20 minutes scrubbing occasionally. Do not allow to dry. Remove solution and dirt and then rinse with plenty of water. Protective treatments may have to be reapplied after this deep clean.

Please Note:

- △ Please follow the detailed instructions on the product labels.

If you require advice or are in any way unsure about these instructions, please call our
Technical Support Line at
AUS: (03) 8552 6000 / NZ: (9) 475 0495

△ This information should be considered to be informal and non-binding. The products must be used according to local conditions and materials. Instructions must be read carefully and followed closely. Where no previous experience is available, or in cases of doubt, test the product in an inconspicuous area. (AUS/NZ6.16gps/7.14)

Your LITHOFIN-Dealer:

© 2016 Lithofin AG

■ The Professional Solution

Australia: CDK Stone Pty. Ltd. • Moorabbin, VIC 3189 • Phone (03) 8552 6000 • Fax (03) 8552 6001 • www.lithofin-australia.com
New Zealand: CDK Stone NZ Ltd. • Rosedale • Auckland • Phone (9) 475 0495 • Fax (9) 479 2424 • www.lithofin.co.nz
Manufactured in Germany by: LITHOFIN AG • 73240 Wendlingen • e-mail: info@lithofin.de