

TECHNICAL DATA SHEET (TDS)

SPECIAL PREPARATION FOR POLISHING

IDProductCode001



Pag | 1

Paste wax to polish marble, granite, terrazzo, engineered stone and polishable stones.

Product description:

Product in a paste form for polishing any kind of stone. Its special chemical composition allows it to dry quickly in order to proceed fast with following operations to be made on the stone. The results of this treatment is a brilliant shine that lasts for long time. It is studied to "cover" variation of colors of the material and imperfections due to the previous polishing. Special Preparation is also suggested when is necessary to renew the original polishing of old material that has lost the original shine. SPECIAL PREPARATION is available in white (transparent) and black colors, in order to polish and enhance colors of different kind of materials, even dark or black ones.

Chemical characteristics:

Appearance	Creamy Paste
Color	See color chart
Odor	Characteristic
Specific gravity at 20° C (68° F)	1,40±0,05
Hydro-solubility	Not soluble
pH	N.A.
Shelf life at 20°C (68° F) away from heat, moisture, sunlight.	24 months in original container unopened.

Colors available



WHITE CLEAR



BLACK

The colors represented in this card are only indicative and are different from the original as it is a digital image.

Instruction for use

Surface must be clean and dry; stains, mildew, crusting must be scraped off otherwise they will be harder to remove after protection. Application can be done by brush, by roller or by spray gun. It is suggested, when possible, to apply the product by cloth directly on the surface to be polished.

Suggestion for use and recommendations:

- To facilitate penetration of the preparation is suggested to warm the slab to be treated in order to open porosities and to facilitate the penetration of the polisher deeply into the slab.
- The longer the preparation remains on the surface the better will be the final result.
- To delay drying time of the polisher we suggest to dilute the preparation with turpentine-based solvent by 20%.
- In case of floor application pay attention that the floor could become slippery; the slipperiness will decrease after some days because of the subsequent cleaning and washing of the floor; the floor will maintain an excellent shine also after maintenance.
- We suggest not to apply the preparation on synthetic materials as plastic, rubber, linoleum etc...
- Before use read carefully recommendations printed on the label and always make a preliminary test.



All data indicated in this leaflet are the results of tests and experiments carried out in our laboratories and through reliable operators in the stone business and have to be considered reliable. Because of the many factors which can influence them, the information here reported do not constitute implicit or formal guarantees. The end user undertakes the responsibility in the usage of the product making sure to experiment the product characteristic as preventive measure. Bellinzoni srl reserves the right to make changes to the products shown in this card, at any time without prior notice. The pictures shown are approximate, as a printed reproduction causes inevitable differences.


TDS N°
001

TECHNICAL DATA SHEET (TDS)

Application surfaces

Marble, granite, terrazzo, agglomerated and stones.

Pag | 2 Application tools



Steel wool



Cloth



Angle grinder



Single Disc Machine



Grinder



Harm polisher

Coverage

For polishing of marble and granite above grit 800, with 1 kg (35 oz.) of product is possible to polish 25/30 m² (270/350 sq.ft.)

Safety procedures

As far as the proper working procedures is concerned, we recommend to consult Material Safety Data Sheets issued according to E.U. rules and to follow your national laws concerning safety in the working place. MSDS is available on our web site www.bellinzoni.com

Packing

Item N° WHITE CLEAR	Item N° BLACK	Packing	Pcs
001APB00350	001APN00350	250 ml (8,50 fl.oz)	30
001APB01300	001APN01300	1,30 kg (45 oz.)	15
001APB06	001APN06	6,00 kg (13,20 lb)	3
001APB20	001APN20	20,00 kg (44 lb)	1

The composition of the tins is Steel (ACC). After use, comply with the local and national regulations currently in force regarding recycling. Our packing is conformed as per U.N. rules for inland transport (A.D.R.) and by sea (I.M.O.) for transportation via air refer to updated rules (I.A.T.A.). For further information regarding transport please check MSDS.

H.S. Code

34.04.9000

Trademark and Origin of the good

BELLINZONI® is a registered trademark of Bellinzoni company. The law considers a trademark to be a form of property and any misuse can be persecuted by law. Bellinzoni s.r.l. declares that our product SPECIAL PREPARATION IN PASTE is MADE IN ITALY.

Video



All data indicated in this leaflet are the results of tests and experiments carried out in our laboratories and through reliable operators in the stone business and have to be considered reliable. Because of the many factors which can influence them, the information here reported do not constitute implicit or formal guarantees. The end user undertakes the responsibility in the usage of the product making sure to experiment the product characteristic as preventive measure. Bellinzoni srl reserves the right to make changes to the products shown in this card, at any time without prior notice. The pictures shown are approximate, as a printed reproduction causes inevitable differences.



TDS N°
001