



PRODUCT INFORMATION SHEET

Re-Issue Date: 03/06/2021
Page 1 of 3

VICTOR

High Gloss Sealer Finish

Description

VICTOR is a floor polish sealer based upon new high performance materials with innovative polymer technology.

VICTOR is recommended for sealing of vinyl, lino, rubber, cork, timber and all other floor surfaces where an easily maintained high gloss surface is required.

Application

Apply two to three coats of **VICTOR** onto vinyl floor tiles for a superior gloss finish.

Application can be either by conventional or spray buff method.

VICTOR will produce a far longer gloss retention than polishes made with conventional polymers.

VICTOR provides excellent black heel and scuff resistance

Performance Advantages

- Achievement of "wet look" gloss.
- Ability to use low and high speed spray buffing
- Decreased labour and equipment costs for end users through a less frequent need to buff, burnish and recoat; and a reduction in the number of floor stripping operations.
- Low ammonia odour.
- Excellent recoatability.
- Low sensitivity to humidity during application.
- Unsurpassed repairability.
- Black heel mark wipeability.
- Very good resistance to powdering and dusting.
- Low tack free time.

The Product Information Sheet supersedes all previous issues for this product. Information contained herein is offered in good faith as being true and accurate to the best of our knowledge, but as the conditions of use are beyond our control, no guarantees are either stated or implied. Where health or safety data given discloses a risk to the user or the environment, it is the responsibility of the purchaser to pass on the information to employees who may be using the product, ensuring that adequate safety procedures are used, including good industrial hygiene.



PRODUCT INFORMATION SHEET

Re-Issue Date: 03/06/2021
 Page 2 of 3

VICTOR

High Gloss Sealer Finish

Product Specifications

Mop Application Test: **VICTOR** vs. a Conventional High Gloss Polish

Conditions: Vinyl and Vinyl Composition Tiles: Three coats applied with a cotton/rayon mop at 21°C/65% relative humidity. Polishes were recoated 10 minutes after each tack-free dry time.

	Formulation VICTOR	Conventional Standard High Gloss Polish

Total Solids (%)	25	25
Application		
<u>First Coat</u>		
Tack Free Time (Mins)	23	35
<u>Second Coat</u>		
Tack Free Time (Mins)	23	32
Leveling	VG-Exc	VG
<u>Third Coat</u>		
Tack Free Time (Mins)	23	30
Drag	Nil	Slight
Leveling	Exc	VG
Haze	Nil	Heavy
<u>Fourth Coat</u>		
Tack Free Time (Mins)	20	32
Drag	Nil	Moderate
Leveling	VG-Exc	VG
Gloss (Visual)	Exc	VG-Exc
Haze	Nil	Heavy (Crater)

The Product Information Sheet supersedes all previous issues for this product. Information contained herein is offered in good faith as being true and accurate to the best of our knowledge, but as the conditions of use are beyond our control, no guarantees are either stated or implied. Where health or safety data given discloses a risk to the user or the environment, it is the responsibility of the purchaser to pass on the information to employees who may be using the product, ensuring that adequate safety procedures are used, including good industrial hygiene.



PRODUCT INFORMATION SHEET

Re-Issue Date: 03/06/2021
Page 3 of 3

VICTOR

High Gloss Sealer Finish

Packaging

- ◆ 5 Litre polyethylene drums
- ◆ 15 Litre polyethylene drums

Health Hazard Information

See separate Health and Safety Data Sheet, available on request.

The Product Information Sheet supersedes all previous issues for this product. Information contained herein is offered in good faith as being true and accurate to the best of our knowledge, but as the conditions of use are beyond our control, no guarantees are either stated or implied. Where health or safety data given discloses a risk to the user or the environment, it is the responsibility of the purchaser to pass on the information to employees who may be using the product, ensuring that adequate safety procedures are used, including good industrial hygiene.