

## Lithofin MN Polish (liquid wax)

### Description

A special product from the LITHOFIN-Range for marble, natural and engineered stone (MN). Solvent based polishing liquid containing high quality waxes.

**Note:** Lithofin MN Liquid Wax is free of hazardous (environmentally and health-wise) chlorinated hydrocarbons (CHC) such as trichlorethene. The application of Lithofin MN Polish differs slightly from products containing such substances, the results are nearly identical.

### Properties

High quality raw materials guarantee optimal protective and maintenance properties, easy polishing and high durability. The first application already produces a polishable film, which can be brought to a high gloss through polishing by hand or machine. Lithofin MN Polish improves the stone's appearance by enhancing the colour structure and facilitates regular maintenance through its water repellent effect.

#### Technical Data:

Density: approx. 0.9 g/cm<sup>3</sup>

Appearance: liquid, colourless, clear

Odour: aromatic

pH-Value: n.a.

Flash Point: >23°C

Solubility in Water: not soluble

**Durability:** resistant to regular household dirt and salt, not resistant to petrol and similar substances. Depending on the level of wear and tear, the product's effect will last for several months.

### Field of Use

For the initial treatment of natural and concrete stone. Improves the appearance of the surface while protecting it. Can also be used to touch up matt and dull spots.

**Surfaces:** all finely honed and polished natural stones such as marble, limestone, travertine, slate, granite, etc. as well as engineered stone, aggro marble and terrazzo.

### Directions for Use

Shake bottle before use. Thinly and evenly apply Lithofin Polish with a clean cloth and allow the product to dry. Then polish with a soft linen cloth or polishing pad. Highly absorbent surfaces may have to be treated more than once. **Please Note:** the surface to be treated must be completely clean and dry. Protect surfaces sensitive to solvents. Lithofin MN Polish is suitable for indoor use only. Well honed surfaces are a prerequisite for good results. In case the application is patchy, polish off with steel wool (000) or a nylon pad.

Layer forming products affect the slip resistant properties of the surface. We highly recommend trying the product in an inconspicuous area prior to use.

Lithofin MN Polish can be removed with Lithofin MN Power-Clean or in extremely stubborn cases with Lithofin WAX-OFF.

On smaller surfaces, use Lithofin MN Polish Cream.

**Application Temperature:** the temperature of the surface should be between 15°C and 25°C. Switch off under floor heating.

**Coverage:** approx. 15 to 20m<sup>2</sup> per litre depending on the surface.

**Drying Time:** can be polished after 5 to 10 minutes, fully dry after approx. 60 minutes.

### Storage

Keep closed and dry at room temperature. When stored in temperatures below 18°C, the product may flake out. In that case, warm the product up (e.g. by placing the bottle in a warm water bath) and shake until it turns clear. Shelf life of up to three years.

### Environmental Protection

Contains solvents, free of chlorinated hydrocarbons.

**Disposal:** liquid product is classified as special waste.

Containers are made of environmentally friendly tin plate.

Clean containers can be recycled through collection systems.

### Safety

**Contents:** naphtha hydrodesulphurized heavy (30% to 60%); xylene (10% to 30%); auxiliary agents.

**Label according to EU-Directive 1999/45/EG:** Xn, harmful; N, harmful to the environment.

**Risk and Safety Phrases:** Flammable. Harmful by inhalation and in contact with skin. Irritating to skin. Harmful: may cause lung damage if swallowed. Keep out of the reach of children. Do not breathe vapour. Avoid contact with skin. If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

**First Aid Procedures:** remove contaminated soaked clothing immediately. In case of inhalation, take in fresh air. In the event of symptoms refer for medical treatment. In case of contact with skin wash off immediately with soap and water. In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice. In case of ingestion, do not induce vomiting. If swallowed by mistake drink plenty of water and seek medical treatment.

**Emergency Procedures:** in case of spill or other release, take up with absorbent material (e.g. sand, sawdust, general-purpose binder). In case of fire formation of dangerous gases possible. Suitable extinguishing material: foam, dry powder, carbon dioxide, sand.

**Additional Information** is listed on the Material Safety Data Sheet.

ADR2003		
Unit	Label	Notes on freight papers
a	UN1993	none, due to limited quantities

### Packaging

a.) 1 litre bottle with child-proof cap (12 per box)

This information should be considered to be informal and non-binding. The products must be used according to local conditions and materials. Always test the product in an inconspicuous area. (AUS/NZ7.11gps/12.07)

  
**stonedoctoraustralia**

**Property of: Lithofin AG, Germany.  
 Sold By: Stone Doctor Australia.**

**278 Burnley Street, VIC 3121, Australia.**

**Phone:03-9429 1223**

**Email: admin@stonedoctor.com.au**