










FEATURES

- Aluminum Fascia
- Arm & Mount Pan w/ Standard Matte Silver Powder Coat Finish
- Indirect Lighting Source
- Aluminum Mounting Plate Mounts to Wall Surface (Centered Over and Attached to J-box)
- LED Light Source
- Surge Protector (Optional)
- UL Class 2 Driver
- Dimmable @ 120V and 277V
- ADA Compliant
- CSA Listed Dry Location For Wall Mount
- LED Light Fixture
- Mounting Hardware Included

LINE DRAWING

LINE DRAWING NOT TO SCALI



FINISHES

Antique

Copper















NHL-DLS-LED Architectural Indoor

PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	



Fixture Core

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
NHL-DLS	L16.4-ZE500 - 16.4W Strips @ 500mA 4-Wire Dimming Driver (Dimmable 0-10V)	UNV=120-277V (50 / 60Hz)	Not Applicable
	L16.0-LT500 - 16.0W Strips @ 500mA 2-Wire Dimming Driver (Leading & Trailing Edge)		
ORDER INFO			
NHL-DLS	L16.4-ZE500	120-277V	Not Applicable
Example ^			

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
Not Applicable ORDER INFO	AC - Antique Copper AS - Antique Silver SM - Matte Silver (Standard) SN - Sand SW - Swedish Steel TB - Textured Black	27K - 2700K Color Temp 30K - 3000K Color Temp 35K - 3500K Color Temp 40K - 4000K Color Temp 50K - 5000K Color Temp	S - Surge Protector 120/277V
51.5E1.111.5			
Not Applicable	AC	27K	S

PROD SOURCE NHL-DLS L16.4 • 30K - 3000K Color Temp • 2378 LED Source Lumens • 145 LED Source Lumens Per Watt

REPLACE	MENT PART	PART NO	NOTES			
					Don't see the configuratio Call us today at (732) 833	