














FEATURES

- Steel Fascia w/ Textured Black Polyester Powder Coat Finish
- Luminous White 75% DR Acrylic Diffuser
- Steel Mounting Pan w/ Hi-Reflectance White Powder Coat Finish
- Aluminum Reflector
- Mounts Directly to 4" Junction Box (By Others)
- Constant Current
- Dimmable to 10% From 120V to 230V
- · CSA Listed Wet Location
- Emergency Battery Available
- LED Light Fixture
- · Mounting Hardware Included

LINE DRAWING



FINISHES

Antique Antique Bronze Matte Metallic Copper Silver Mist Silver Black Sand Swedish Textured Textured Textured Steel Black White **Bronze**



Œ	LED	Į.

PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	·

Fixture Core

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
NHL-RLB -	L20.0-ZE700 - 20.0W @ 700mA Line Voltage 4-Wire Dimming Driver (Dimmable 0 - 10V)	UNV=120V-277V	Not Applicable
	L25.0-ZE875 - 25.0W @ 875mA Line Voltage 4-Wire Dimming Driver (Dimmable 0 - 10V)	(50 / 60Hz)	
ORDER INFO	L35.0-ZE1150 - 35.0W @ 1150mA Line Voltage 4-Wire Dimming Driver (Dimmable 0 - 10V)		
NHL-RLB	L20.0-ZE700	UNV	Not Applicable

Example ^ (may not represent a manufacturable product)

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
TWB	AC - Antique Copper AS - Antique Silver BT - Bronze Mist BN - Brushed Nickel SM - Matte Silver MB - Metallic Black SN - Sand SW - Swedish Steel TB - Textured Black (Standard) BZ - Textured Bronze TW - Textured White	27K - 2700K Color Temp 30K - 3000K Color Temp 35K - 3500K Color Temp 40K - 4000K Color Temp	F - Fused TP - Tamper Resistant Screws EB - Integral Emergency Battery (Please Specify Voltage)
ORDER INFO			
TWB	AC AC	27K	F

Example ^ (may not represent a manufacturable product)

PROD	SOURCE	30K SPECS		
NHL-RLB	L20.0	30K - 3000K Color Temp 2309 LED Source Lumens 115.5 LED Source Lumans Per Watt		
	L25.0	30K - 3000K Color Temp 2887 LED Source Lumens 115.5 LED Source Lumens Per Watt		
	L35.0	30K - 3000K Color Temp 3926 LED Source Lumens 112.2 LED Source Lumens Per Watt		

REPLACEMENT PART	PART NO		
White 75% DR Acrylic	3051160		
Lens			

NOTES

Don't see the configuration you are looking for? Call us today at (732) 833-8086