NHL-SLS LED

Architectural Indoor













FEATURES

- Aluminum Fascia
- Arm & Mount Pan w/ Standard Matte Silver Powder Coat Finish
- Indirect Lighting Source
- Aluminum Mounting Plate Mounts to Wall Surface (Centered Over and Attached to J-box)
- LED Light Source
- Surge Protector (Optional)
- UL Class 2 Driver
- Dimmable @ 120V and 277V
- ADA Compliant
- CSA Listed Dry Location For Wall Mount
- LED Light Fixture
- Mounting Hardware Included

LINE DRAWING





FINISHES

Antique Sand Swedish Antique Bronze Matte Mist Copper Silver Silver Steel Textured Textured Textured Black **Bronze** White

NHL-SLS LED

Architectural Indoor



3	yt.	III	Co	re

PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	·

PRODUCT CODE SOURCE/WATTAGE		VOLTAGE	DIMMING DRIVER
NHL-SLS	L16.4-ZE500 - 16.4W Strips @ 500mA 4-Wire Dimming Driver (Dimmable 0-10V) L16.0-LT500 - 16.0W Strips @ 500mA 2-Wire Dimming Driver (Leading & Trailing Edge)	UNV=120-277V (50 / 60Hz)	Not Applicable
ORDER INFO	(11 8 1 1 8 181)		
NHL-SLS	L16.4-ZE500	UNV	Not Applicable
Example ^			

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
Not Applicable ORDER INFO	AC - Antique Copper AS - Antique Silver SM - Matte Silver (Standard) SN - Sand SW - Swedish Steel TB - Textured Black	27K - 2700K Color Temp 30K - 3000K Color Temp 35K - 3500K Color Temp 40K - 4000K Color Temp 50K - 5000K Color Temp	S - Surge Protector 120/277V
Not Applicable	AC	27K	S

PROD	SOURCE	30K SPECS		
NHL-SLS	L16.4	OK SPECS OUT TO SOUR COLOR TEMP OUT TO SOURCE LUMENS OUT TO SOURCE LUMENS HAS LED SOURCE LUMENS PER WATT		

REPLACEMENT PART	PART NO	NOTES
		Don't see the configuration you are looking for?
		Call us today at (732) 833-8086