

Wall Bracket LSTW

NHL-LSTW

Job Name:			
Type:			

FEATURES / SPECIFICATIONS:

Finishes Available:

White

Diffuser Options:

- Acrylic
- Clear prismatic
- Standard
- Smooth White
- Optional

Optional Features:

• Slide-on one-piece end (regular one-piece end is standard). Baffles and dividers are avilable for up, down, and/or front light. Ends with tapped holes to accommodate tamper-proof or regular screws

Lengths:

• Available in 2' & 4' lengths

Wattages:


22W/35W/44W

Lumens:

• 3050, 5050, 6100 Values based at 4000k

Dimming:

• 0-10v Dimming Standard



APPLICATIONS:

Wall or ceiling in corridors, stairweels and bathrooms

ACCESSORIES

CON =Convenience Outlet

EM = Emergency Ballast

JB =Joiner Bands

PCW =Pull Chain Swich

PL13 =PL13 Night Light

SEN =Occupancy Sensor (Consult Factory for Options)

ORDERING CODE:

Fill in the boxes with the options you need fax it to us at: 732-833-8085

NHL-LSTW

Length:

2 =2' Length

4 = 4' Length

22W 22 Watts 35W 35 Watts 44W 44 Watts

Wattage:

Color Temp:

35K =3 500K

35K =3,500K **40K** =4,000K **50K** =5,000K Voltage:

UNV =120-277

Options:

CON =Convenience Outlet
EM =Emergency Ballast
JB =Joiner Bands
PCW =Pull Chain Swich

PL13 =PL13 Night Light SEN =Occupancy Sensor (Consult Factory for Options)

