

# **Wall Bracket LSTWS**

**NHL-LSTWS** 

Job Name:		
Type:		

# **FEATURES / SPECIFICATIONS:**

#### **Finishes Available:**

White

### **Diffuser Options:**


- Acrylic
- Clear prismatic
- Standard
- Smooth White
- Optional

## **Optional Features:**

 Slide-on one-piece end (regular one-piece end is standard). Baffles and dividers are available for up, down, and/or front light. Ends with tapped holes to accommodate tamper-proof or regular screws

## Lengths:

 Available in 2' & 4' lengths



# Wattages:


• 22W/35W/44W

#### Lumens:

• 3000,5000, 6000

#### **Dimming:**

• 0-10v Dimming Standard



# **APPLICATIONS:**

Wall or ceiling in corridors, stairwells and bathrooms

ADA Compliant - less that 4" off wall.

# **ACCESSORIES**

CON =Convenience Outlet

EM = Emergency Ballast

JB =Joiner Bands

PCW =Pull Chain Swich

PL13 =PL13 Night Light

SEN =Occupancy Sensor (Consult Factory for Options)

# **ORDERING CODE:**

Fill in the boxes with the options you need fax it to us at: 732-833-8085

NHL-LSTWS

Length:

**2** =2' Length **4** =4' Length Wattage:

22W 22 Watts 35W 35 Watts 44W 44 Watts Color Temp:

35K =3,500K 40K =4,000K 50K =5,000K Voltage:

**UNV** =120-277

Options:

CON =Convenience Outlet
EM =Emergency Ballast
JB =Joiner Bands
PCW =Pull Chain Swich
PL13 =PL13 Night Light
SEN =Occupancy Sensor (Consult Factory for Options)

