

Wall Bracket LSTWV

NHL-LSTWV

Job Name:			
Туре:			

FEATURES / SPECIFICATIONS:

Finish:

White

Features:

- 16-guage body and ends
- · Tapped holes which accomodate tamper-resistant screws

Lens Options:

• .125" Clear Polycarbonate lens tamper and impact resistant - standard. • .125 100% DR clear prismatic lens

Optional Features:

- · Battery backup: Holes for test switch, indicator light and emergency ballast
- CFL

Lengths:

• Available in 2' & 4' lengths

Wattages:


• 22W/35W/44W

Lumens:

• 3000, 5000, 6000

Dimming:

0-10v Dimming standard



APPLICATIONS:

Public areas High abuse lighting Locker rooms Stairwells Corridors Wall or Ceiling **Bathrooms**

APPLICATIONS:

CON =Convenience Outlet

JB =Joiner Bands

PCW =Pull Chain Swich

PL13 =PL13 Night Light

SEN =Occupancy Sensor (Consult Factory for Options)

ORDERING CODE:

Fill in the boxes with the options you need fax it to us at: 732-833-8085

NHL-LSTWV

Length:

2 =2' Length 4 =4' Length

Wattage:

22W 22 Watts 35W 35 Watts 44W 44 Watts Color Temp:

3/16 DIA. X 1/2 K.D.

35K =3,500K 40K =4,000K **50K** =5,000K Voltage:

UNV =120-277

Options:

CON =Convenience Outlet EM =Emergency Ballast JB =Joiner Bands PCW = Pull Chain Swich PL13 =PL13 Night Light SEN =Occupancy Sensor (Consult Factory for Options)

