



Dejavoo  Systems

Z9



**DEPENDABLE**

Global market leader in secured contact and contactless payment. RoHS, CE, FCC & BSMI certified. Tested to perform even under extreme conditions.



**ADAPTABLE**

Offering the full range of payment, communications and connectivity options. Up to 4 SAM, expansive memory for multi-app support. Ergonomic compact design fits any working space. Cost efficient, Linux open architecture OS allows flexibility in the integration of business applications.



**SECURED**

PCI PTS, EMV L1 L2, Visa payWave, MasterCard PayPass, American Express, & JCB J/ Speedy certified.



**INTUITIVE**

3.5 touch screen or 2.4 color LCD screen with in-built contactless reader enriches user experience. Large backlit keypad and LCD screen provides ease of pin entry in all lighting conditions. Full range of communications / connectivity options & ultra performance of Li-Polymer battery enable efficient payment transactions anywhere.



Z9 Mobile Series		Z9 GPRS	Z9 Wireless
<b>Processor</b>		32 bits high performance secure Microprocessor, @ 400MHz	
<b>Memory</b>	Flash/ DDR RAM	128 MB/ 64 MB (Up to 256 MB/ 128 MB)	
	Micro-SD Socket		
<b>Display</b>		3.5" color TFT-LCD 320x480 pixels	
<b>Capacitive Touch Screen</b>			
<b>Card Reader</b>	Magnetic Strip	ISO 7810, 7811 & 7813 Triple track, Bi-Directional	
	Contact Card	User Card ISO 7816 ID-1 1.8V/3V/5V T=0, T=1	
	Card	SAM Card (up to 4) 2	
	Contactless (Optional)	ISO 14443 Type A, B, ISO 18092 NFC and Mifare® & SONY® Felica Working frequency 13.56MHz	
<b>Communications Interface (Optional)</b>	Handset	UMTS, GPRS, CDMA, WiFi, Bluetooth, USB	
	Base	Ethernet, Dial-Up Modem, Bluetooth, 3x RS232, USB	
<b>Indicator</b>	LED- 4 LEDs	X	
	Audio- Buzzer	Ⓞ	
<b>Keypad</b>	Standard Keys	15	
	Function Keys	X	
<b>Power Supply</b>		9V/ 4A	
<b>Dimensions (L/W/H)</b>	Handset	160 mm x 78 mm x 67 mm	
	Base	137.6 mm x 81 mm x 48.8 mm	
<b>Weight</b>	Handset	335g	
	Base	140g	
<b>Printer With Graphical Capabilities</b>		57 mm x 40 mm, 100 mm/ sec	
<b>Environment</b>	Operating Temperature	0 °C to 50 °C	
	Storage Temperature	-20 °C to 70 °C	
	Operating Humidity	5% to 90% non-condensing	
	Storage Humidity	5% to 95% non-condensing	
<b>Certifications</b>	Security& Payment	PCI PTS, EMV L1 L2, TQM, PBOC L1 L2 Visa payWave, MasterCard PayPass, American Express, & JCB J/ Speedy	
	Safety, EMC	CE, FCC, BSMI, RoHS	
<b>Software</b>		SDK, KMS, TMS, Simulator, CTOS library, ISO 8583 library, Crypto library	
<b>Crypto</b>		TRNG, DES, T'DES, AES, RSA, MK/SK, DUKPT, T'DES DUKPT	

\*\*Product technical specifications are subject to change. For latest information, visit <http://www.dejavoo.com>

Dejavoo Systems  
1129 Northern Blvd Suite 303  
Manhasset NY, 11030 USA  
+1-877-358-6797

[www.dejavoo.com](http://www.dejavoo.com)

