



Braille XC22.5-1125M6 Motorsport Lithium Battery

At only 4.0 KG, the XC22.5-1125M6 Motorsport Lithium Battery is a high-performance upgrade from a traditional lead acid battery. Offering significant weight reduction, more power output and lasting up to 5 times longer than lead acid batteries!

BENEFITS:

- Superior starting capabilities with high cranking amp output per kg
- Fast and efficient recharge, up to 5 times faster than lead acid batteries
- Can be used in "Total Loss" (no alternator) applications
- 3-5 times longer service life vs lead-acid batteries
- Engineered for high shock and vibration applications
- Up to 2/3 weight reduction for equivalent cranking performance

| | | | |
|------------------------|--------------------|-----------------------|----------------------|
| 1125 10 SECONDS (A) | 4.0 WEIGHT (KG) | 22.5 CAPACITY (Ah) | 288 CAPACITY (Wh) |
|------------------------|--------------------|-----------------------|----------------------|

PRODUCT INFORMATION

+ Physical Specs

| | |
|-------------------|---------|
| Battery Chemistry | LFP |
| Length (mm) | 254 |
| Width (mm) | 83 |
| Height (mm) | 156 |
| Weight (kg) | 4.0 |
| Terminal Type | M6 stud |
| Polarity | Right + |

+ Technical Specs

| | | | |
|---------------------------------------|------|-----------------------------|--------------|
| 5 Second Pulse Cranking Amps | 1698 | Charging Temperature | 0C to 50C |
| 10 Second Pulse Discharge Current (A) | 1125 | Discharge Temperature Range | -20C to +60C |
| Voltage | 12 | Storage Temperature | -20C to +60C |
| Capacity (Ah) | 22.5 | | |
| Capacity (Wh) | 288 | | |
| Continuous Discharge Current (A) | 450 | | |

+ Charging

| | |
|----------------------------|---------------|
| Recharge Voltage | 14.4V - 14.6V |
| Maintenance Charge Voltage | 13.8V |



Rev 05-23



Follow Us:



@braillebattery

www.braillebattery.eu