



**FLEX SEAL®** is a rubberized sealant spray coating that sprays out as a liquid, seeps into cracks and holes, then dries to a watertight, flexible coating. It's the easy way to coat, seal, and stop leaks fast.

## WHAT DOES IT DO?

- Seeps into cracks & holes
- Dries into a watertight, flexible, pliable coating
- Thick, durable, mastic coating
- Helps stop vibrations & deaden noise
- Helps protect surface from corrosion
- When applied properly, lasts for years
- Will not lose its strength
- Withstands normal hydrostatic water pressure
- Won't sag or drip in summer heat nor crack and peel in winter
- Dries to the touch in 2-3 hours
- Cures by evaporation and fully cures in 24 to 48 hours
- Dries to a satin finish
- Once dry – can be painted with high-quality latex paint

## TEMPERATURES

- **Storage:** 60° F to 100° F
- **Apply to surfaces:** 0° F to 100° F
- **Withstands:** -20° F to 140° F

## HOW DO I USE IT?

- Clean surface free of grease, dirt, & oil
- Shake can vigorously for 1 minute before use
- Spray in short bursts in an even sweeping motion
- Spray 8" to 12" from surface in a well-ventilated area ONLY
- Apply multiple, thin, even coats, allowing each coat to dry before applying the next
- Spray a larger area than source of leak
- Feather the edges
- Can be applied on wet or dry surfaces
- After use, flip can upside down, spray a couple bursts to clear nozzle
- Remove any excess with dry paper towel
- Use pumice soap to clean hands

## NOT RECOMMENDED:

- Not designed to withstand extreme heat, pressure, or harsh chemicals
- Do not use to seal gas/oil tanks (flammable materials)
- Not tested for safe use with plants & animals
- Do not use on potable water containers
- Not tested for food safety
- Not recommended for underfoot applications
- Do not use on Styrofoam
- Not affiliated with GAF. Not for use by professional roofers

## SIZES & COVERAGE

- 2 oz. covers approx. 2 ft<sup>2</sup>
- 14 oz. covers approx. 12 ft<sup>2</sup>
- 17 oz covers approx. 15 ft<sup>2</sup>

## RECOMMENDED SURFACES

- Wood • Metal • Tile • Concrete • Masonry • Fabric • Glass • Plastic
- Aluminum • Porcelain • Drywall • Rubber • Cement
- May not be compatible with some plastics, vinyl, rubbers





**FLEX SEAL LIQUID®** is liquid rubber, in a can! Unlike traditional paints, Flex Seal Liquid starts out as a thick liquid, that can seep into cracks and holes to form a watertight, weatherproof seal. Easy to use, just brush, roll, dip, or pour to stop leaks fast.

## WHAT DOES IT DO?

- Dries into a super strong, flexible, watertight coating
- Blocks out air, water, & moisture
- Self-leveling
- Mildew & chemical resistant
- Resists rain, snow, sun, hail, UV degradation
- Prevents rust & corrosion
- Resists extreme temps, natural weathering
- Durable, breathable, & weatherproof
- Expands, contracts, flexes, stretches in Summer & Winter
- Withstands normal hydrostatic water pressure
- Safe to use around plants
- Dries to touch in 6 to 12 hours
- Cures by absorbing moisture & fully cures within 24 to 48 hours
- Wet areas take longer to cure

## TEMPERATURES

- **Storage:** 60° F to 100° F
- **Apply to surfaces:** 32° F to 120° F
- **Withstands:** -80° F to 350° F

## HOW DO I USE IT?

- For better adhesion, etch surface with sandpaper or steel wool
- Best to apply on a clean, dry surface that is free of grease, dirt, & oil
- Apply in multiple thin even coats, allowing each coat to dry before applying the next (If you apply too thick only outer layers will cure)
- Always brush or roll over a larger area than the leak
- Cures faster in hot summer and slower in cold winter
- Apply 24 hours before heavy rain
- Clean up uncured Liquid with dry cloth, paper towel, or mineral spirits
- When pouring, apply no more than ¼" layer at a time
- In roofing applications, apply 2-3 coats using a ¾" nap roller
- To avoid skinning, replace lid securely immediately after use (if skin forms, remove before use, do not stir)

## COLORS

Black • White • Clear • Gray

## NOT RECOMMENDED:

- Not designed to withstand extreme heat, pressure, or harsh chemicals
- Do not use to seal gas/oil tanks (flammable materials)
- Do not use on potable water containers
- Not tested for food safety
- Do not use for underfoot applications
- Do not dilute with solvents or water
- Do not use water to clean residue
- Cannot be painted over / top-coated with anything but Flex Seal Liquid
- Do not shake

## SIZES & COVERAGE

- Large = 16 oz = 18.75 ft<sup>2</sup>
- Jumbo = 32 oz = 37.5 ft<sup>2</sup>
- Giant = 128 oz = 150 ft<sup>2</sup>
- MAX = 320 oz = 375 ft<sup>2</sup>

## RECOMMENDED SURFACES

- Concrete • Glass • Brick • Stucco • Masonry • Wood • Copper
- Plastic • Tile • Fabrics • Wires • Vinyl • Fiberglass • Ceramic • Porcelain
- Metal • Aluminum • Natural Stones • Foam • Asphalt • EIFS • TPO
- PVC • EPDM • CSPE • Hypalon Polyurethanes





**FLEX SHOT®** is a revolutionary, super-thick, rubber sealant that can be used to caulk, bond, and seal virtually anything. Use it to fill huge cracks and holes, or stop tough leaks instantly. It comes our nice and thing to cling to almost any surface, then turns into a stretchy rubber seal that's virtually indestructible. The included extension tube makes even hard-to-reach repairs perfect every time.

## • WHAT DOES IT DO?

- Caulks, bonds, & seals virtually everything
- Formula expands & contracts
- Completely waterproof
- No caulking gun required
- No running, dripping, or mess
- Dries faster than many other caulks & sealants
- Can be applied on wet surfaces
- Mildew resistant (white & almond)
- Withstands normal hydrostatic water pressure
- Will not fade, dry, crack, yellow, or deteriorate due to contact with household cleaners.
- Can be used again and again
- Forms a tack-free skin in 20 mins
- Cures by absorbing moisture, & fully cures within 24 hours
- Will seal approx. 40 Linear feet (depending on size of bead)

## • HOW DO I USE IT?

- Start with clean, dry surface free of grease, dirt, & oil
- Cut nozzle to desired length
- Hold can at a 45° angle & depress side of nozzle
- Can be smoothed with finger within 20 mins of applying
- How to make a Flex Shot patch:
  1. On wax paper, apply product making a patch
  2. Let it cure for 24 hours
  3. Remove cured patch from wax paper and cover hole sealing perimeter with more Flex Shot
- Clean uncured product with dry cloth, paper towel, or isopropyl alcohol
- Cured product can be peeled away
- After use, squeeze a small bead to plug and seal remaining product

## • TEMPERATURES

- **Storage:** 60° F to 100° F
- **Apply to surfaces:** 0° F to 150° F
- **Withstands:** -76° F to 350° F

## • NOT RECOMMENDED:

- Not designed to withstand extreme heat, pressure, or harsh chemicals
- Do not use to seal gas/oil tanks (flammable materials)
- Not tested for safe use with plants & animals
- Do not use on potable water containers
- Not tested for food safety
- Do not use in standing water
- Do not paint over
- Do not remove rubber plug on bottom of can

## • COLORS

- Black
- Clear
- White
- Almond

## • RECOMMENDED SURFACES

- Porcelain • Tile • Glass • Fiberglass • Wood • Granite
- Marble • Fabric • Upholstery • Paper • Stone • Metal
- And just about any other surface free of grease & oil

