



FLEX CAULK is a high-performance, hybrid polymer caulk that can handle a wide array of applications. Delivered through our Trigger Flow Nozzle™, there's no need for a caulking gun. Flex Caulk is available in both Hybrid polymer and Silicone formulations.

• WHAT DOES IT DO?

- Trigger Flow Nozzle™, no need for a caulking gun.
- Greater degree of adhesion over Flex Shot.
- Flex Caulk Hybrid can be applied to wet or damp surfaces. Flex Caulk Silicone works best on dry, smooth, non-porous surfaces.
- Flex Caulk Hybrid is fully paintable.
- Virtually odorless.
- Indoor and outdoor applications.
- Chemical, UV, and mildew resistant.
- Will not shrink, crack, or peel.
- Snap & Save cap eliminates waste.
- Excellent temperature range.
- Resistant to extreme weather.
- Solvent-free.
- Flex Caulk Silicone is NSF (51) approved and may be used on equipment with food contact applications. It should not be used in contact with drinking water.

• TEMPERATURES

Hybrid Formula:

- Apply to surfaces = 0°F to 150°F
- Withstands = -75°F to 220°F.

Silicone Formula:

- Apply to surfaces = 0°F to 150°F
- Withstands = -70°F to 400°F.

• LAUNCH DATE

- 03/2024 (Hybrid)
- 04/2025 (Silicone)

• HOW DO I USE IT?

- Area must be free of dirt, grease, and oil.
- Remove tab before initial use.
- Remove Snap & Save cap.
- Adjust the flow setting to the desired amount, somewhere between min and max (min setting recommended to start).
- Flow setting and the speed you move the nozzle controls bead thickness. For the most consistent bead size, make sure that the trigger is fully pressed.
- Hold at a 45° angle, push trigger down to begin flow of caulk.
- Keep pushing trigger while moving the nozzle across the area using a smooth, even motion.
- Material can be smoothed within 10 minutes of application.
- Remove excess caulk with a clean, dry rag or paper towel. Do not use water.
- Forms a skin in approximately 10 minutes, cures in 24 hours
- Store in a cool, dry place and do not store above 120° F.
- After use, wipe off tip and secure Snap & Save cap tightly on the nozzle.

• COVERAGE:

- Approximately 30 – 35 linear feet depending on the bead size.

• NOT RECOMMENDED:

- Not designed to withstand extreme heat or pressure.
- Do not use to seal gas/oil tanks (flammable materials).
- Not tested for safe use with plants and animals.
- Flex Caulk Silicone is NOT paintable
- Flex Caulk Hybrid has not been tested for its safe use around.

• RECOMMENDED SURFACES:

- Flex Caulk Hybrid has outstanding bonding and adhesion to most common materials found around the home, including difficult substrates both porous and non-porous.
- Asphalt, Brick, Ceramic, Cinderblock, Concrete, Drywall, Fiberglass, Foam, Glass, Granite, Laminate, Marble, Metal, Plastic, Porcelain, Wood.

• SIZES

- White – 9 oz.
- Clear – 6.6 oz.
- Silicone – 6.5 oz.

