

FLEX TAPE ADHESIVE REMOVER® is an easy-to-use aerosol spray, specially formulated to remove the super strong adhesive bond of FLEX TAPE® and other tough adhesives.

WHAT DOES IT DO?

- Removes Flex Tape and other tapes, such as masking, duct, double-sided, painters, gaffer, scotch, and packing tape, decals, stickers, labels, tar or asphalt, glue residue, gum, bugs, ink, lipstick, marker, paint transfers, pine tar, soot, dirt, tree sap, vinyl tinted windows, wallpaper, wax, weather stripping, etc.
- When applied properly, will not cause surfaces to crack, peel, fade, or yellow.

STORAGE

- Store in a cool, dry location. Flex Tape Adhesive Remover should never be exposed to temperatures over 120°F.
- Shelf life is 2 years, with proper storage.

• HOW DO I USE IT?

- Always use protective gloves and goggles
- Lift one edge of the Flex Tape and spray directly underneath backing onto adhesive
- Use pliers to help grab and pull up Flex Tape
- Spray directly on adhesive as you pull Flex Tape from the surface
- Once Flex Tape has been removed, spray directly on any excess adhesive residue
- Let it stand 10 seconds and wipe with a clean cloth
- Repeat until area is free of adhesive as needed. A stiff brush may also help to remove residue

TEMPERATURES

Should never be exposed to temperatures over 120°F.

NOT RECOMMENDED:

- Does not work on Flex Glue's super strong adhesive formula
- Do not use in direct contact with drinking water. Product is harmful if swallowed or ingested
- Has not been tested for use around plants or animals
- Do not use near heat, sparks, pilot lights, or any other source of ignition
- Do not smoke while using product
- · Avoid contact with skin and eyes
- If left on surface too long, it could penetrate other topcoats.

SIZES & COVERAGE

- 5 oz Large Can
- 12 oz Jumbo Can





RECOMMENDED SURFACES

- Wood Glass Tile Concrete Aluminum Metal Stone Stucco
- Plaster Copper Fabric Fiberglass Ceramic Steel Porcelain
- Cement May not be compatible with certain plastics, vinyl, paints