

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

EVO-STIK POLYURETHANE WOOD GLUE Supercedes Date: 11-Aug-2022 Revision date 14-Jul-2023 Revision Number 1.01

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	
Product Name	EVO-STIK POLYURETHANE WOOD GLUE
Other means of identification	
Pure substance/mixture	Mixture
1.2. Relevant identified uses of the	substance or mixture and uses advised against
Recommended use	Adhesives
Uses advised against	Coatings (aprotic) Consumer applications that require heating above room temperature before or during use are not supported
Reason why uses advised against	Use advised against in Chemical Safety Assessment per REACH Annex I point 7 2.3

1.3. Details of the supplier of the safety data sheet

Company Name
Bostik SA
420 rue d'Estienne d'Orves
92700 Colombes
FRANCE
Tel: +33 (0)1 49 00 90 00

E-mail address

SDS.box-EU@bostik.com

1.4. Emergency telephone number

Emergency Telephone	
Ireland	Bostik: +353 (1) 8624900 (Monday- Friday 9am-5pm)
United Kingdom	Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)
Europe	112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Acute toxicity - Inhalation (Dusts/Mists)	Category 4 - (H332)
Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Respiratory sensitisation	Category 1 - (H334)
Skin sensitisation	Category 1 - (H317)
Carcinogenicity	Category 2 - (H351)
Specific target organ toxicity — single exposure	Category 3 - (H335)
Category 3 Respiratory irritation	
Specific target organ toxicity — repeated exposure	Category 2 - (H373)

2.2. Label elements

Contains 4,4'-Methylenediphenyl diisocyanate

EVO-STIK POLYURETHANE WOOD GLUE

Supercedes Date: 11-Aug-2022

Revision date 14-Jul-2023 Revision Number 1.01



Signal word Danger

Hazard statements

- H315 Causes skin irritation
- H317 May cause an allergic skin reaction
- H319 Causes serious eye irritation
- H332 Harmful if inhaled
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled
- H335 May cause respiratory irritation
- H351 Suspected of causing cancer
- H373 May cause damage to organs through prolonged or repeated exposure

EU Specific Hazard Statements

EUH204 - Contains isocyanates. May produce an allergic reaction

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P201 - Obtain special instructions before use

- P260 Do not breathe mist/vapours/spray
- P271 Use only outdoors or in a well-ventilated area
- P280 Wear protective gloves/protective clothing/eye protection/face protection
- P302 + P352 IF ON SKIN: Wash with plenty of water and soap
- P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P342 + P311 - If experiencing respiratory symptoms: Call a POISON CENTER or doctor

P405 - Store locked up

P501 - Dispose of contents/ container to an approved waste disposal plant

Special provisions concerning the labelling of certain mixtures

As from 24 August 2023 adequate training is required before industrial or professional use. Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

Additional information

This product requires tactile warnings if supplied to the general public.

2.3. Other hazards

No information available.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU	CAS No.	Classification	Specific	M-Factor	M-Factor	REACH
	Index No).		according to	concentration limit		(long-ter	registration
			Regulation (EC) No.	(SCL)		m)	number
			1272/2008 [CLP]				
4,4'-Methylenediphenyl	(615-005-00-	101-68-8	Acute Tox. 4 (H332)	STOT SE 3 :: C>=5%	-	-	01-2119457014-
diisocyanate	9)		Skin Irrit. 2 (H315)	Skin Irrit. 2 :: C>=5%			47-XXXX
40 - <80 %	(615-035-00-		Eye Irrit. 2 (H319)	Eye Irrit. 2 :: C>=5%			
	2)		Resp. Sens. 1 (H334)	Resp. Sens. 1 ::			
	202-966-0		Skin Sens. 1 (H317)	C>=0.1%			
			Carc. 2 (H351)				
			STOT SE 3 (H335)				
			STOT RE 2 (H373)				
Morpholine,	229-194-7	6425-39-4	Eye Irrit. 2 (H319)	-	-	-	01-2119969278-
4,4'-(oxydi-2,1-ethanediy							20-XXXX
I)bis-							
1 - <5 %							

Full text of H- and EUH-phrases: see section 16

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No	Oral LD50 mg/kg	Dermal LD50 mg/kg		Inhalation LC50 - 4 hour -	Inhalation LC50 - 4 hour -
					dust/mist - mg/L	vapour - mg/L	gas - ppm
4,4'-Methylenediphenyl diisocyanate	(615-005-00-9) (615-035-00-2) 202-966-0	101-68-8	-	-	1.5	-	-
Morpholine, 4,4'-(oxydi-2,1-ethanedi yl)bis-	229-194-7	6425-39-4	-	-	-	-	-

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Notes

See section 16 for more information

Chemical name	Notes
4,4'-Methylenediphenyl diisocyanate - 101-68-8	C,2

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice

Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get

	medical advice/attention.			
Inhalation	May cause allergic respiratory reaction. If breathing has stopped, give artificial respiration. Get medical attention immediately. Remove to fresh air. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Get immediate medical attention.			
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.			
Skin contact	May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a doctor. Wash off immediately with soap and plenty of water for at least 15 minutes.			
Ingestion	May produce an allergic reaction. Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Get immediate medical attention.			
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. See section 8 for more information. Avoid breathing vapours or mists.			
4.2. Most important symptoms and	effects, both acute and delayed			
Symptoms	May cause allergy or asthma symptoms or breathing difficulties if inhaled. Coughing and/ or wheezing. Itching. Rashes. Hives. May cause redness and tearing of the eyes. Burning sensation. Difficulty in breathing.			
4.3. Indication of any immediate me	edical attention and special treatment needed			
Note to doctors	May cause sensitisation in susceptible persons. Treat symptomatically.			
SECTION 5: Firefighting mea	asures			
5.1. Extinguishing media				
Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.			
Unsuitable extinguishing media	No information available.			
5.2. Special hazards arising from the substance or mixture				
Specific hazards arising from the chemical	Product is or contains a sensitiser. May cause sensitisation by inhalation. May cause sensitisation by skin contact.			
Hazardous combustion products	Carbon dioxide (CO2). Nitrogen oxides (NOx). Hydrogen cyanide. Isocyanates.			
5.3. Advice for firefighters				
Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.			
SECTION 6: Accidental relea	ase measures			

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away

EVO-STIK POLYURETHANE WOOD GLUE

Supercedes Date: 11-Aug-2022

	from and upwind of spill/leak. Avoid breathing vapours or mists.
Other information	Refer to protective measures listed in Sections 7 and 8.
For emergency responders	Use personal protection recommended in Section 8.
6.2. Environmental precautions	
Environmental precautions	Prevent further leakage or spillage if safe to do so.
6.3. Methods and material for conta	ainment and cleaning up
Methods for containment	Keep from any possible contact with water.
Methods for cleaning up	Take up mechanically, placing in appropriate containers for disposal.
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.
6.4. Reference to other sections	
Reference to other sections	See section 8 for more information. See section 13 for more information.
SECTION 7: Handling and st	orage
7.1. Precautions for safe handling	-
Advice on safe handling	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse. Avoid breathing vapours or mists.
General hygiene considerations	Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and immediately after handling the product.
7.2. Conditions for safe storage, in	cluding any incompatibilities
Storage Conditions	Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children. Keep away from water or moist air.
Recommended storage temperature	Keep at temperatures between 5 and 25 °C. Keep at temperatures between 10 and 35 °C.
7.3. Specific end use(s)	
Specific use(s) Adhesives.	
Risk Management Methods (RMM)	The information required is contained in this Safety Data Sheet.
Other information	Observe technical data sheet.
SECTION 8: Exposure contro	ols/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	Ireland	United Kingdom
4,4'-Methylenediphenyl diisocyanate	-	TWA: 0.005 ppm	TWA: 0.02 mg/m ³

EVO-STIK POLYURETHANE WOOD GLUE

Supercedes Date: 11-Aug-2022

Revision date 14-Jul-2023 Revision Number 1.01

101-68-8	TWA: 0.02 mg/m ³	STEL: 0.07 mg/m ³
	STEL: 0.015 ppm	Sen+
	STEL: 0.07 mg/m ³	
	Sens+	

Derived No Effect Level (DNEL)

No information available

Derived No Effect Level (DN	EL)					
4,4'-Methylenediphenyl diisocyanate (101-68-8)						
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor			
worker Short term Systemic health effects	Dermal	50 mg/kg bw/d				
worker Short term Systemic health effects	Inhalation	0.1 mg/m³				
worker Short term Local health effects	Dermal	28700 μg/cm²				
worker Short term Local health effects	Inhalation	0.1 mg/m³				
worker Long term Systemic health effects	Inhalation	0.05 mg/m³				
worker Long term Local health effects	Inhalation	0.05 mg/m³				

Morpholine, 4,4'-(oxydi-2,1-ethanediyl)bis- (6425-39-4)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects worker	Inhalation	7.28 mg/m³	
Long term Systemic health effects worker	Dermal	1 mg/kg bw/d	

Derived No Effect Level (DNEL)					
4,4'-Methylenediphenyl diiso	4,4'-Methylenediphenyl diisocyanate (101-68-8)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
Consumer Short term Systemic health effects	Dermal	25 mg/kg bw/d			
Consumer Short term Systemic health effects	Inhalation	0.05 mg/m³			
Consumer Short term Systemic health effects	Oral	20 mg/kg bw/d			
Consumer Short term Local health effects	Dermal	17200 µg/cm²			
Consumer Short term Local health effects	Inhalation	0.05 mg/m³			
Consumer	Inhalation	0.025 mg/m ³			

EVO-STIK POLYURETHANE WOOD GLUE

Supercedes Date: 11-Aug-2022

Long term Systemic health effects			
Consumer	Inhalation	0.025 mg/m ³	
Long term			
Local health effects			

Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)	
4,4'-Methylenediphenyl diisocyanate (101-68-8)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	1 mg/l
Marine water	0.1 mg/l
Soil	1 mg/kg dry weight
Sewage treatment plant	1 mg/l
Freshwater - intermittent	10 mg/l

Morpholine, 4,4'-(oxydi-2,1-ethanediyl)bis- (6425-39-4)		
Environmental compartment	Predicted No Effect Concentration (PNEC)	
Freshwater	0.1 mg/l	
Marine water	0.01 mg/l	
Freshwater sediment	8.2 mg/kg dry weight	
Marine sediment	0.82 mg/kg dry weight	
Freshwater - intermittent	1 mg/l	
Sewage treatment plant	100 mg/l	
Soil	1.58 mg/kg dry weight	

8.2. Exposure controls

Engineering controls	Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be exhausted directly at the point of origin.
Personal protective equipment	
Eye/face protection	Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166
Hand protection	Wear protective gloves. Gloves must conform to standard EN 374. Nitrile rubber. Butyl rubber. Glove thickness > 0.4 mm. The breakthrough time for the mentioned glove material is in general greater than 60 min. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Gloves must conform to standard EN 374
Skin and body protection Respiratory protection Recommended filter type:	Suitable protective clothing. Suitable protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Organic gases and vapours filter conforming to EN 14387.

Environmental exposure controls Do not allow into any sewer, on the ground or into any body of water.

SECTION 9: Physical and chemical properties

9.1.	Info	ormation	on basic	phy	ysical	and	<u>chemical</u>	pro	perties	_
	-							-		

Physical state	Liquid
Appearance	Gel
Colour	Cream
Odour	Musty.
Property	Values
Melting point / freezing point	< 10 °C

Remarks • Method None known

EVO-STIK POLYURETHANE WOOD GLUE

Supercedes Date: 11-Aug-2022

Revision date 14-Jul-2023 Revision Number 1.01

Initial boiling point and boiling	> 330 °C	
range		
Flammability	Not applicable for liquids .	
Flammability Limit in Air		None known
Upper flammability or explosive	No data available	
limits		
Lower flammability or explosive	No data available	
limits		
Flash point	> 200 °C	CC (closed cup)
Autoignition temperature	>600 °C	
Decomposition temperature		None known
рН	No data available	None known.
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	> 21 mm²/s	@ 40°C
Dynamic viscosity	No data available	
Water solubility	Insoluble in water. Slightly soluble.	
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	0.01	
Relative density	1.10	
Bulk Density	No data available	
Density	No data available	
Relative vapour density	8.5	
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	
9.2. Other information		
Solid content (%)	No information available	
VOC content	No data available	ailable

9.2.1. Information with regards to physical hazard classes Not applicable

9.2.2. Other safety characteristics No information available approx

SECTION 10: Stability and reactivity

10.1. Reactivity

 Reactivity
 No information available.

 10.2. Chemical stability
 Reacts with water.

 Stability
 Reacts with water.

 Explosion data
 None.

 Sensitivity to mechanical impact
 None.

 Sensitivity to static discharge
 None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Hazardous polymerisation Hazardous polymerisation may occur.

10.4. Conditions to avoid

EVO-STIK POLYURETHANE WOOD GLUE

Supercedes Date: 11-Aug-2022

Conditions to avoid	Excessive heat. Exposure to water.		
10.5. Incompatible materials			
Incompatible materials	Strong acids. Strong bases. Strong oxidising agents.		
10.6. Hazardous decomposition pr	oducts		
Hazardous decomposition products	Carbon monoxide. Carbon dioxide (CO2). Nitrogen oxides (NOx). Thermal decomposition can lead to release of irritating and toxic gases and vapours. Hydrogen cyanide.		

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available. May cause sensitisation in susceptible persons. (based on components). May cause irritation of respiratory tract. Harmful by inhalation.
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
Skin contact	Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). May cause sensitisation by skin contact. Causes skin irritation.
Ingestion	Specific test data for the substance or mixture is not available. May cause additional affects as listed under "Inhalation". Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.
Symptoms related to the physical	, chemical and toxicological characteristics

Symptoms	Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing,
	tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain, or
	flushing. Coughing and/ or wheezing. Itching. Rashes. Hives. Redness. May cause
	redness and tearing of the eyes.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document ATEmix (oral) >5000 mg/kg

0 0
>5000 mg/kg
>20000 ppm
2.54 mg/l
>20 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
4,4'-Methylenediphenyl diisocyanate	=31600 mg/kg (Rattus) = 9200 mg/kg (Rattus)	LD 50 > 9400 mg/kg (Oryctolagus cuniculus) OECD 402	1.5 mg/L (Rattus) 4 h
Morpholine,	LD50 =2025 mg/Kg (Rattus)	LD50 >3000 mg/Kg	-

EVO-STIK POLYURETHANE WOOD GLUE

Supercedes Date: 11-Aug-2022

4,4'-(oxydi-2,1-ethaned	liyl)bis-	(Oryctolagus cuniculus)			
Delayed and immediat	e effects as	well as chronic effects fr	om short and long-t	erm exposure	
Skin corrosion/irritatio	on	Classification based on d	ata available for ingre	edients. Causes skin	irritation.
	-	Classification based on d	ata available for ingre	edients. Causes serio	ous eye irritation.
4,4'-Methylenediphenyl Method	diisocyanate Species	(101-68-8) Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	Eye	0.1 mL	24 hours	Non-irritant

May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an Respiratory or skin sensitisation allergic skin reaction.

Method	Species	Exposure route	Results
OECD GD 39	Rat	Inhalation	Sensitizing
Germ cell mutagenicity	Based on available data, the classification criteria are not met.		

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component Information

4,4'-Methylenediphenyl diisocyanate (101-68-8)				
Method	Species	Results		
OECD Test No. 453: Combined Chronic Toxicity/Carcinogenicity Studies	Rat	Limited evidence of a carcinogenic effect		
Chemical name		European Union		
4,4'-Methylenediphenyl diisocya	nate	Carc. 2		

Reproductive toxicity Based on available data, the classification criteria are not met.

- STOT single exposure May cause respiratory irritation.
- STOT repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No information available. Endocrine disrupting properties

EVO-STIK POLYURETHANE WOOD GLUE

Supercedes Date: 11-Aug-2022

11.2.2. Other information

Other adverse effects

No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
4,4'-Methylenediphenyl diisocyanate 101-68-8	ErC50 (72h) >1640 mg/L Algae (scenedesmus subspicatus) (OECD 201)	>1000 mg/l Danio rerio	-	EC50 (24H) >1000 mg/L Daphnia magna		
4,4'-(oxydi-2,1-ethanedi yl)bis-	EC50 (72h) >100 mg/L Algae (Pseudokirchner ella subcapitata) Static	LC50 (96h) >2150 mg/L (Danio rerio) Static	-	EC50 (48h) >100 mg/L (Daphnia magna) Static		

12.2. Persistence and degradability

Persistence and degradability No information available.

4,4'-Methylenediphenyl diisocyanate (101-68-8)

Method	Exposure time	Value	Results
OECD Test No. 302C: Inherent	28 days	0% biodegradation	Not readily biodegradable
Biodegradability: Modified MITI Test		-	
(11)			

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
4,4'-Methylenediphenyl diisocyanate	4.51
Morpholine, 4,4'-(oxydi-2,1-ethanediyl)bis-	0.5

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment

The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

Chemical name	PBT and vPvB assessment
4,4'-Methylenediphenyl diisocyanate	The substance is not PBT / vPvB
Morpholine, 4,4'-(oxydi-2,1-ethanediyl)bis-	The substance is not PBT / vPvB

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

EVO-STIK POLYURETHANE WOOD GLUE Supercedes Date: 11-Aug-2022

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods	
Waste from residues/unused products	Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Do not reuse empty containers.
European Waste Catalogue	07 02 08 other still bottoms and reaction residues 08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances 15 01 10*: Packaging containing residues of or contaminated by dangerous substances
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special precautions for user	
Special Provisions	None
IMDG	
14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Marine pollutant	NP
14.6 Special precautions for user	
Special Provisions	None
14.7 Maritime transport in bulk	
according to IMO instruments	
Transport in bulk according to	Annex II of MARPOL and the IBC Code Not applicable
<u>Air transport (ICAO-TI / IATA-DGR)</u>	
14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
11C Cussial pressuitions for user	

None

Section 15: REGULATORY INFORMATION

14.6 Special precautions for user

Special Provisions

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EVO-STIK POLYURETHANE WOOD GLUE

Supercedes Date: 11-Aug-2022

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No	Restricted substance per REACH
		Annex XVII
4,4'-Methylenediphenyl diisocyanate	101-68-8	56[a].
		75.
		74.
Diisocyantes		74

56. If product supplied to the general public with substance $\ge 0.1\%$, then gloves must be provided with the product. **74** If product supplied to the industrial or professional users with total monomeric diisocyanates $\ge 0.1\%$, then its packaging must mention "As from 24 August 2023 adequate training is required before industrial or professional use".

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Ozone-depleting substances (ODS) regulation (EC) 1005/2009 Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

EVO-STIK POLYURETHANE WOOD GLUE

Supercedes Date: 11-Aug-2022

Revision date 14-Jul-2023 Revision Number 1.01

H332 - Harmful if inhaled

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled

H335 - May cause respiratory irritation

H351 - Suspected of causing cancer

H373 - May cause damage to organs through prolonged or repeated exposure

Notes relating to the identification, classification and labelling of substances

Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers

Notes relating to the classification and labelling of mixtures

Note 2: The concentration of isocyanate stated is the percentage by weight of the free monomer calculated with reference to the total weight of the mixture

SVHC: Substances of Very High Concern for Authorisation:

PBT: Persistent, Bioaccumulative, and Toxic (PBT) Chemicals

vPvB: Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE: Specific target organ toxicity - Repeated exposure STOT SE: Specific target organ toxicity - Single exposure

EWC: European Waste Catalogue

LOW: List of Wastes (see http://ec.europa.eu/environment/waste/framework/list.htm)

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IATA: International Air Transport Association

ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG: International Maritime Dangerous Goods

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

Legend SECTION 8: Exposure controls/personal protection

TWĂ	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
AGW	Occupational exposure limit value	BGW	Biological limit value
Ceiling	Maximum limit value	*	Skin designation

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - Vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	Calculation method
mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Acute aquatic toxicity	Calculation method
Chronic aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method

Key literature references and sources for data used to compile the SDS

European Food Safety Authority (EFSA)

European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA_RAC)

European Chemicals Agency (ECHA) (ECHA_API)

EPA (Environmental Protection Agency)

Acute Exposure Guideline Level(s) (AEGL(s))

International Uniform Chemical Information Database (IUCLID)

National Institute of Technology and Evaluation (NITE)

EVO-STIK POLYURETHANE WOOD GLUE

Supercedes Date: 11-Aug-2022

Revision date 14-Jul-2023 Revision Number 1.01

NIOSH (National Institute for Occupational Safety and Health)
Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications
Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme
Organisation for Economic Co-operation and Development Screening Information Data SetPrepared ByProduct Safety & Regulatory AffairsRevision date14-Jul-2023Training AdviceAS FROM 24 AUGUST 2023 ADEQUATE TRAINING IS REQUIRED BEFORE
INDUSTRIAL OR PROFESSIONAL USE
For further information, please contact:
https://www.safeusediisocyanates.eu/Further informationNo information available

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) Regulation (EC) No. 1272/2008 and Regulation (EC) No. 1907/2006 as amended by Regulation (EU) No. 2020/878

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet