



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

**RITO ALL WEATHER CLEAR**  
Supersedes Date: 06-Jan-2023

Revision date 08-Nov-2023  
Revision Number 2

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product Name RITO ALL WEATHER CLEAR

### Other means of identification

Pure substance/mixture Mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesives and/or sealants

Uses advised against None known

### 1.3. Details of the supplier of the safety data sheet

#### Company Name

Bostik GmbH  
Niederlassung Schwepnitz  
Industriestraße 1-7  
D-01936 Schwepnitz  
Germany  
Tel. +49 (0)35797 646 0  
Fax +49 (0)35797 646 190

E-mail address SDS.box-EU@bostik.com

### 1.4. Emergency telephone number

**Ireland** NPIC - National Poison Information Centre  
Members of the Public: +353 (01) 8092166 (8.00 am to 10.00 pm - 7 days a week)  
Healthcare Professionals: +353 (01) 8092566 (24 hour service)

**United Kingdom** Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)

**Europe** 112

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Classification according to  
Regulation (EC) No. 1272/2008  
[CLP]

<b>Specific target organ toxicity — single exposure</b>	Category 3 - (H336)
Category 3 Narcotic effects	
<b>Flammable liquids</b>	Category 3 - (H226)

### 2.2. Label elements

Contains n-Butyl acetate

# SAFETY DATA SHEET

RITO ALL WEATHER CLEAR  
Supersedes Date: 06-Jan-2023

Revision date 08-Nov-2023  
Revision Number 2



**Signal word**  
Warning

**Hazard statements**  
H336 - May cause drowsiness or dizziness  
H226 - Flammable liquid and vapour

### Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand  
P102 - Keep out of reach of children  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P261 - Avoid breathing vapours  
P280 - Wear protective gloves and eye/face protection  
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower  
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P312 - Call a POISON CENTER or doctor/physician if you feel unwell  
P405 - Store locked up  
P501 - Dispose of contents/ container to an approved waste disposal plant

### 2.3. Other hazards

Harmful to aquatic life.

### PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

**Endocrine Disruptor Information** This product does not contain any known or suspected endocrine disruptors.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical name	EC No (EU Index No).	CAS No..	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	REACH registration number
Distillates (petroleum), hydrotreated heavy paraffinic (IPC346 <3% DMSO) >25 - <40 %	265-157-1 (649-467-00-8)	64742-54-7	Asp. Tox. 1 (H304)	-	-	-	01-2119484627-25-XXXX
n-Butyl acetate >25 - <40 %	204-658-1 (607-025-00-)	123-86-4	STOT SE 3 (H336) Flam. Liq. 3 (H226)	-	-	-	01-2119485493-29-XXXX

# SAFETY DATA SHEET

RITO ALL WEATHER CLEAR  
Supersedes Date: 06-Jan-2023

Revision date 08-Nov-2023  
Revision Number 2

	1)		(EUH066) [B]				
Silica, amorphous 1 - <2.5 %	231-545-4	7631-86-9	[B]	-	-	-	01-2119379499- 16-XXXX
Bis(2,2,6,6-tetramethyl-4- -piperidyl) sebacate 0.1 - <0.3 %	258-207-9	52829-07-9	Eye Dam. 1 (H318) Repr. 2 (H361f) Aquatic Acute 1 (H400) Aquatic Chronic 2 (H411)	-	-	-	01-2119537297- 32-XXXX

**Full text of H- and EUH-phrases: see section 16**

Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes  
[B] - Substance with a Community workplace exposure limit

## Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Distillates (petroleum), hydrotreated heavy paraffinic (IPC346 <3% DMSO)	265-157-1 (649-467-00-8)	64742-54-7	-	-	-	-	-
n-Butyl acetate	204-658-1 (607-025-00-1)	123-86-4	-	-	0.74	-	-
Silica, amorphous	231-545-4	7631-86-9	-	-	-	-	-
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	258-207-9	52829-07-9	-	-	-	-	-

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## Notes

See section 16 for more information

Chemical name	Notes
Distillates (petroleum), hydrotreated heavy paraffinic (IPC346 <3% DMSO) - 64742-54-7	L

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>General advice</b>	Show this safety data sheet to the doctor in attendance.
<b>Inhalation</b>	Remove to fresh air. IF exposed or concerned: Get medical advice/attention.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated

# SAFETY DATA SHEET

RITO ALL WEATHER CLEAR  
Supersedes Date: 06-Jan-2023

Revision date 08-Nov-2023  
Revision Number 2

clothes and shoes.

**Ingestion** Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Call a doctor.

**Self-protection of the first aider** Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information.

## 4.2. Most important symptoms and effects, both acute and delayed

**Symptoms** Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

**Effects of Exposure** No information available.

## 4.3. Indication of any immediate medical attention and special treatment needed

**Note to doctors** No information available.

## **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

**Suitable Extinguishing Media** Dry chemical. Carbon dioxide (CO<sub>2</sub>). Water spray. Alcohol resistant foam.

**Unsuitable extinguishing media** No information available.

### 5.2. Special hazards arising from the substance or mixture

**Specific hazards arising from the chemical** Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

**Hazardous combustion products** Carbon oxides. Silicon dioxide.

### 5.3. Advice for firefighters

**Special protective equipment and precautions for fire-fighters** Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.

**Other information** Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

**For emergency responders** Use personal protection recommended in Section 8.

### 6.2. Environmental precautions

**Environmental precautions** Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or

# SAFETY DATA SHEET

RITO ALL WEATHER CLEAR  
Supersedes Date: 06-Jan-2023

Revision date 08-Nov-2023  
Revision Number 2

spillage if safe to do so. Prevent product from entering drains.

## 6.3. Methods and material for containment and cleaning up

**Methods for containment** Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

**Methods for cleaning up** Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

## 6.4. Reference to other sections

**Reference to other sections** See section 8 for more information. See section 13 for more information.

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

**Advice on safe handling** Use personal protection equipment. Avoid contact with skin and eyes. Avoid breathing vapours or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. In case of insufficient ventilation, wear suitable respiratory equipment.

**General hygiene considerations** Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

### 7.3. Specific end use(s)

**Specific use(s)**  
Adhesives and/or sealants.

**Risk Management Methods (RMM)** The information required is contained in this Safety Data Sheet.

**Other information** Observe technical data sheet.

## **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

#### Exposure Limits

Chemical name	European Union	Ireland	United Kingdom
n-Butyl acetate	TWA: 241 mg/m <sup>3</sup>	STEL: 150 ppm	TWA: 150 ppm

# SAFETY DATA SHEET

**RITO ALL WEATHER CLEAR**  
**Supersedes Date:** 06-Jan-2023

**Revision date** 08-Nov-2023  
**Revision Number** 2

123-86-4	TWA: 50 ppm STEL: 723 mg/m <sup>3</sup> STEL: 150 ppm	STEL: 723 mg/m <sup>3</sup>	TWA: 724 mg/m <sup>3</sup> STEL: 200 ppm STEL: 966 mg/m <sup>3</sup>
Silica, amorphous 7631-86-9	TWA: 0.1 mg/m <sup>3</sup>	TWA: 6 mg/m <sup>3</sup> TWA: 2.4 mg/m <sup>3</sup> STEL: 18 mg/m <sup>3</sup> STEL: 7.2 mg/m <sup>3</sup>	TWA: 6 mg/m <sup>3</sup> TWA: 2.4 mg/m <sup>3</sup> STEL: 18 mg/m <sup>3</sup> STEL: 7.2 mg/m <sup>3</sup>

**Derived No Effect Level (DNEL)** No information available

<b>Derived No Effect Level (DNEL)</b>			
<b>n-Butyl acetate (123-86-4)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	300 mg/m <sup>3</sup>	
worker Short term Systemic health effects	Inhalation	600 mg/m <sup>3</sup>	
worker Long term Local health effects	Inhalation	300 mg/m <sup>3</sup>	
worker Short term Local health effects	Inhalation	600 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Dermal	11 mg/kg bw/d	

<b>Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Short term Long term Systemic health effects	Inhalation	2.82 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Dermal	1.6 mg/kg	

<b>Derived No Effect Level (DNEL)</b>			
<b>n-Butyl acetate (123-86-4)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	35.7 mg/m <sup>3</sup>	
Consumer Short term Systemic health effects	Inhalation	300 mg/m <sup>3</sup>	
Consumer Long term Local health effects	Inhalation	35.7 mg/m <sup>3</sup>	
Consumer Short term Local health effects	Inhalation	300 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Dermal	6 mg/kg bw/d	

# SAFETY DATA SHEET

RITO ALL WEATHER CLEAR  
Supersedes Date: 06-Jan-2023

Revision date 08-Nov-2023  
Revision Number 2

Consumer Short term Systemic health effects	Dermal	6 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	2 mg/kg bw/d	

<b>Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Dermal	0.8 mg/kg	
Consumer Long term Systemic health effects	Oral	0.4 mg/kg	

## Predicted No Effect Concentration (PNEC)

<b>Predicted No Effect Concentration (PNEC)</b>	
<b>n-Butyl acetate (123-86-4)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.18 mg/l
Marine water	0.018 mg/l
Freshwater - intermittent	0.36 mg/l
Sewage treatment plant	35.6 mg/l
Freshwater sediment	0.981 mg/l
Marine sediment	0.0981 mg/l
Soil	0.0903 mg/l

<b>Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.018 mg/l
Marine water	0.0018 mg/l
Freshwater sediment	29 mg/kg
Marine sediment	2.9 mg/kg
Soil	5.9 mg/kg

## 8.2. Exposure controls

**Engineering controls** Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be exhausted directly at the point of origin.

### Personal protective equipment

#### Eye/face protection

Tight sealing safety goggles.

#### Hand protection

Wear protective gloves. Recommended Use: Butyl rubber. Glove thickness > 0.4 mm. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time for the mentioned glove material is in general greater than 60 min. Gloves must conform to standard EN 374

#### Skin and body protection

Suitable protective clothing.

**Environmental exposure controls** No information available.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**Physical state** Liquid  
**Appearance** Paste

# SAFETY DATA SHEET

RITO ALL WEATHER CLEAR  
Supersedes Date: 06-Jan-2023

Revision date 08-Nov-2023  
Revision Number 2

Colour	Colourless	
Odour	Solvent.	
<b>Property</b>	<b>Values</b>	<b>Remarks • Method</b>
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	126 °C	
Flammability	Not applicable for liquids	
Flammability Limit in Air		None known
Upper flammability or explosive limits	7.5	
Lower flammability or explosive limits	1.2	
Flash point	27 °C	CC (closed cup)
Autoignition temperature	No data available	None known
Decomposition temperature		None known
pH	6.2	
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	> 21 mm <sup>2</sup> /s	
Dynamic viscosity	15000 mPa s	
Water solubility	No data available.	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	1.5	
Relative density	No data available	None known
Bulk Density	No data available	
Density	0.93 g/cm <sup>3</sup>	
Relative vapour density	4	
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	
<b>9.2. Other information</b>		
Solid content (%)	No information available	
VOC content		223.2 g/L

9.2.1. Information with regards to physical hazard classes  
Not applicable

9.2.2. Other safety characteristics  
No information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reactivity No information available.

### 10.2. Chemical stability

Stability Stable under normal conditions.

### Explosion data

Sensitivity to mechanical impact None.  
Sensitivity to static discharge Yes.

### 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.



# SAFETY DATA SHEET

RITO ALL WEATHER CLEAR  
Supercedes Date: 06-Jan-2023

Revision date 08-Nov-2023  
Revision Number 2

## 10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks.

## 10.5. Incompatible materials

Incompatible materials None known based on information supplied.

## 10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

## **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Information on likely routes of exposure

##### Product Information

**Inhalation** May cause drowsiness or dizziness.  
**Eye contact** Based on available data, the classification criteria are not met.  
**Skin contact** Based on available data, the classification criteria are not met.  
**Ingestion** Based on available data, the classification criteria are not met.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

#### Acute toxicity

#### Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) >5000 mg/kg  
ATEmix (dermal) >5000 mg/kg  
ATEmix (inhalation-gas) >20000 ppm  
ATEmix (inhalation-dust/mist) >5 mg/l  
ATEmix (inhalation-vapour) >20 mg/l

#### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Distillates (petroleum), hydrotreated heavy paraffinic (IPC346 <3% DMSO)	>15 g/kg (Rattus)	> 5000 mg/kg (Oryctolagus cuniculus)	-
n-Butyl acetate	>10650 mg/kg (Rattus)	> 17600 mg/kg (Oryctolagus cuniculus)	=390 ppm (Rattus) 4 h
Silica, amorphous	=7900 mg/kg (Rattus)	> 5000 mg/kg (Oryctolagus cuniculus)	>2.2 mg/L (Rattus) 1 h
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	LD50 (Rattus) > 2000 mg/kg OECD 423	LD50 (Rattus) > 3 170 mg/kg OECD 402	=500 mg/m <sup>3</sup> (Rattus) 4 h

# SAFETY DATA SHEET

RITO ALL WEATHER CLEAR  
Supersedes Date: 06-Jan-2023

Revision date 08-Nov-2023  
Revision Number 2

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** Based on available data, the classification criteria are not met.

n-Butyl acetate (123-86-4)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal		4 hours	Non-irritant

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			Non-irritant

**Serious eye damage/eye irritation** Based on available data, the classification criteria are not met.

n-Butyl acetate (123-86-4)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	Corneal	0.1 mL		Product score 1 Non-irritant

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye			Eye Damage

**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig		No sensitisation responses were observed

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Method	Species	Results
OECD Test No. 414: Pre-natal Development Toxicity Study	Rat, Rabbit	reproductive toxicant

**STOT - single exposure** May cause drowsiness or dizziness.

# SAFETY DATA SHEET

RITO ALL WEATHER CLEAR  
 Supersedes Date: 06-Jan-2023

Revision date 08-Nov-2023  
 Revision Number 2

**STOT - repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

### 11.2.2. Other information

**Other adverse effects** No information available.

## SECTION 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity** Harmful to aquatic life.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Distillates (petroleum), hydrotreated heavy paraffinic (IPC346 <3% DMSO) 64742-54-7	-	LC50: >5000mg/L (96h, Oncorhynchus mykiss)	-	EC50: >1000mg/L (48h, Daphnia magna)		
n-Butyl acetate 123-86-4	EC50: =674.7mg/L (72h, Desmodosmus subspicatus)	LC50 96 h 17 - 19 mg/L (Pimephales promelas flow-through)	EC50 = 70.0 mg/L 5 min EC50 = 82.2 mg/L 15 min EC50 = 959 mg/L 18 h EC50 = 98.9 mg/L 30 min	EC50 48 h = 44 mg/L (Daphnia magna)		
Silica, amorphous 7631-86-9	EC50: =440mg/L (72h, Pseudokirchneriella subcapitata)	LC50: =5000mg/L (96h, Brachydanio rerio)	-	EC50: =7600mg/L (48h, Ceriodaphnia dubia)		
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9	EC50 72Hr 0.705 mg/l (Pseudokirchneriella subcapitata)	LC50 (96h) = 5.29 mg/l (Oryzias latipes)	-	LC50 48Hr 8.58 mg/l (Daphnia magna)		

### 12.2. Persistence and degradability

**Persistence and degradability** No information available.

n-Butyl acetate (123-86-4)

Method	Exposure time	Value	Results
OECD Test No. 301D: Ready Biodegradability: Closed Bottle Test (TG 301 D)	28 days	83%	Readily biodegradable

Silica, amorphous (7631-86-9)

Method	Exposure time	Value	Results
			The methods for determining biodegradability are not applicable to inorganic

# SAFETY DATA SHEET

RITO ALL WEATHER CLEAR  
Supersedes Date: 06-Jan-2023

Revision date 08-Nov-2023  
Revision Number 2

			substances
--	--	--	------------

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Method	Exposure time	Value	Results
OECD Test No. 303: Simulation Test - Aerobic Sewage Treatment -- A: Activated Sludge Units; B: Biofilms	28 days	Total organic carbon (TOC)	24 % Moderate

## 12.3. Bioaccumulative potential

### Bioaccumulation

#### Component Information

Chemical name	Partition coefficient
n-Butyl acetate	2.3
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	0.35

## 12.4. Mobility in soil

**Mobility in soil** No information available.

## 12.5. Results of PBT and vPvB assessment

**PBT and vPvB assessment** The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

Chemical name	PBT and vPvB assessment
Distillates (petroleum), hydrotreated heavy paraffinic (IPC346 <3% DMSO)	The substance is not PBT / vPvB
n-Butyl acetate	The substance is not PBT / vPvB
Silica, amorphous	The substance is not PBT / vPvB
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	The substance is not PBT / vPvB

## 12.6. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

## 12.7. Other adverse effects

No information available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**Waste from residues/unused products** Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

**Contaminated packaging** Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

**European Waste Catalogue** 08 04 09\* waste adhesives and sealants containing organic solvents or other dangerous substances  
15 01 10\*: Packaging containing residues of or contaminated by dangerous substances

**Other information** Waste codes should be assigned by the user based on the application for which the product was used.

## SECTION 14: Transport information

# SAFETY DATA SHEET

RITO ALL WEATHER CLEAR  
Supersedes Date: 06-Jan-2023

Revision date 08-Nov-2023  
Revision Number 2

## Land transport (ADR/RID)

14.1 UN number or ID number	UN1133
14.2 UN proper shipping name	Adhesives
14.3 Transport hazard class(es)	3
Labels	3
14.4 Packing group	III
Description	UN1133, Adhesives, 3, III, (D/E)
14.5 Environmental hazards	Not applicable
14.6 Special precautions for user	
Special Provisions	None
Classification code	F1
Tunnel restriction code	(D/E)
Limited quantity (LQ)	5 L
ADR Hazard Id (Kemmler Number)	30

**Note:** Exempted from ADR according to 2.2.3.1.5 for receptacles with a maximum capacity of 450 litres

## IMDG

14.1 UN number or ID number	UN1133
14.2 UN proper shipping name	Adhesives
14.3 Transport hazard class(es)	3
14.4 Packing group	III
Description	UN1133, Adhesives, 3, III, (27°C c.c.)
14.5 Marine pollutant	NP
14.6 Special precautions for user	
Special Provisions	223, 955
Limited Quantity (LQ)	5 L
EmS-No.	F-E, S-D

14.7 Maritime transport in bulk according to IMO instruments

Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

**Note:** Simplification possible according to IMDG Code 2.3.2.5 for receptacles with a maximum capacity of 450 litres

## Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	UN1133
14.2 UN proper shipping name	Adhesives
14.3 Transport hazard class(es)	3
14.4 Packing group	III
Description	UN1133, Adhesives, 3, III
14.5 Environmental hazards	Not applicable
14.6 Special precautions for user	
Special Provisions	A3
Limited quantity (LQ)	10 L
ERG Code	3L

## **Section 15: REGULATORY INFORMATION**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

# SAFETY DATA SHEET

RITO ALL WEATHER CLEAR  
Supersedes Date: 06-Jan-2023

Revision date 08-Nov-2023  
Revision Number 2

## Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

### **SVHC: Substances of Very High Concern for Authorisation:**

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

### **EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction**

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

### **Substance subject to authorisation per REACH Annex XIV**

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

### **Dangerous substance category per Seveso Directive (2012/18/EU)**

P5c - FLAMMABLE LIQUIDS

### **Ozone-depleting substances (ODS) regulation (EC) 1005/2009**

Not applicable

### **Persistent Organic Pollutants**

Not applicable

## National regulations

### 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at  $>10$  tpa. No Chemical Safety Assessment has been carried out for this mixture

## **SECTION 16: Other information**

### Key or legend to abbreviations and acronyms used in the safety data sheet

#### **Full text of H-Statements referred to under section 3**

EUH066 - Repeated exposure may cause skin dryness or cracking  
H226 - Flammable liquid and vapour  
H304 - May be fatal if swallowed and enters airways  
H318 - Causes serious eye damage  
H336 - May cause drowsiness or dizziness  
H361f - Suspected of damaging fertility  
H400 - Very toxic to aquatic life  
H411 - Toxic to aquatic life with long lasting effects

#### **Notes relating to the identification, classification and labelling of substances**

**Note L:** The harmonised classification as a carcinogen applies unless it can be shown that the substance contains less than 3 % of dimethyl sulphoxide extract as measured by IP 346 ('Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions – Dimethyl sulphoxide extraction refractive index method' Institute of Petroleum, London), in which case a classification in accordance with Title II of this Regulation shall be performed also for that hazard class

SVHC: Substances of Very High Concern for Authorisation:

PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances

# SAFETY DATA SHEET

**RITO ALL WEATHER CLEAR**  
**Supersedes Date:** 06-Jan-2023

**Revision date** 08-Nov-2023  
**Revision Number** 2

vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances  
STOT RE: Specific target organ toxicity - Repeated exposure  
STOT SE: Specific target organ toxicity - Single exposure  
EWC: European Waste Catalogue  
LOW: List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)  
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road  
IATA: International Air Transport Association  
ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air  
IMDG: International Maritime Dangerous Goods  
RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

## Legend SECTION 8: Exposure controls/personal protection

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
AGW	Occupational exposure limit value	BGW	Biological limit value
Ceiling	Maximum limit value	Sk*	Skin designation

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - Vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	Calculation method
mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Acute aquatic toxicity	Calculation method
Chronic aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method
Flammable liquids	On basis of test data

## Key literature references and sources for data used to compile the SDS

European Food Safety Authority (EFSA)  
European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA\_RAC)  
European Chemicals Agency (ECHA) (ECHA\_API)  
EPA (Environmental Protection Agency)  
Acute Exposure Guideline Level(s) (AEGl(s))  
International Uniform Chemical Information Database (IUCLID)  
National Institute of Technology and Evaluation (NITE)  
NIOSH (National Institute for Occupational Safety and Health)  
Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications  
Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme  
Organisation for Economic Co-operation and Development Screening Information Data Set

<b>Prepared By</b>	Product Safety & Regulatory Affairs
<b>Revision date</b>	08-Nov-2023
<b>Revision note</b>	First time release
<b>Training Advice</b>	No information available
<b>Further information</b>	No information available

# SAFETY DATA SHEET

RITO ALL WEATHER CLEAR  
Supersedes Date: 06-Jan-2023

Revision date 08-Nov-2023  
Revision Number 2

---

## Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Regulation (EC) No. 1272/2008 and Regulation (EC) No. 1907/2006 as amended by Regulation (EU) No. 2020/878

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**