

**Branches**

Sandbach	t. + 44 (0) 1270 902020
Basingstoke	t. + 44 (0) 118 9819522
Ireland	t. + 353 (0) 719638796

**Data Sheet**

# Wood Fibre Fillerboard

## Bitumen Impregnated

Multi purpose bituminous Wood Fibre Fillerboard for is used as an expansion joint filler for concrete slab and wall construction.

**Performance and Composition**

Width	Sheet = 1220mm   Strips = 100, 150 & 200mm
Length	2440mm
Thickness	12, 20 & 25mm
Thickness Tolerance	+/- 1.2mm
Density	220 - 300 kg/cbm
Humidity	4 - 6.5%
Heat Condition Coefficient	0.052 W/mk
Swelling after 2hrs in Water	Approx 6%
Hygienic Class	E 1
Sound Absorptions	Approx 40 dB
Transverse Internal Bend	1.2 N/mm <sup>2</sup>
Flammability Class	B 2
European Norms	EN 13986 & EN622-4
American Norms	ASTM D 1751 acc. to compression, extrusion, recovery Test procedure acc. to ASTM D 545 99
Contents of Bitumen	More than 10%
Certification of Production	ISO 9001:2000
Ingredients	Wood fibre, Bitumen, Water Repellent, Paraffin

**Packaging Strips**

Size (mm)	Pack quantity	Packs per Pallet
12 x 100	20	54
12 x 150	10	72
12 x 200	10	54
20 x 100	12	60
20 x 150	6	80
20 x 200	6	60
25 x 100	10	54
25 x 150	5	72
25 x 200	5	54

**Packaging Sheets**

Size (mm)	Pallet quantity
12	95
20	63
25	45

**Head Office**

Units 1-3 Shannon Industrial Estate, Lodge Road, Sandbach, Cheshire, CW11 3HP  
e. info@euroacc.co.uk ■ w. www.@euroacc.co.uk