Conquer the outdoors and extend the riding season for all year fun.

O ELECIRIC BIKES

26" x 4.8" efatbike OUTLAND **TORNGAT RS1**

ALL SEASON RIDING POWERHOUSE

Enhanced control and handling capability over sand, snow and through mud with a dynamic motor system delivering all the advantages of electric assist while maintaining a traditional riding experience.



130Nm/500W mid motor with Torque/Cadence sensing and throttle delivers a powerful and intuitive natural riding experience.

POWER AND RANGE

720Wh battery providing up to 60km (37mi)* range with 4.8" tires. Ready everyday with plug and play charging and all day range.

PEDAL ASSIST SYSTEM

5 Levels of power assisted pedaling.



SITS NORMAN





POWER ON DEMAND THROTTLE



Configurable to CLASS 1 CLASS 3 capable where permitted **

OUTLAND TORNGAT RS1


26" x 4.8" eFATBIKE

FRAMESET					
FRAME	Hydroformed Alloy, 26 Fatbike frame, internal cable routing head tube ported, removable down tube battery with security lock				
COLOR FORK	Red and Black RST RENEGADE 26" suspension, 120mm travel, lockout, Thru Axle				
DRIVETRAIN		COMPONENTS			
SHIFTERS CHAINRINGS CHAIN REAR DERAILLEUR CASSETTE WHEELS	SHIMANO ALTUS 8-speed Rapidfire Plus 34T with Narrow Wide teeth KMC E8-S SHIMANO ACERA 8-speed SHIMANO ACERA 8-speed 11-32T	HANDLEBAR GRIPS STEM SEAT POST SADDLE BRAKE LEVERS BRAKE CALIPERS ROTORS	700mm, 28mm rise, 31.8n VELO, Rubber palm rest, 1 41mm with 3 degree rise, 31.6mm (350mm) SELLE ROYAL Viento TEKTRO HDE350 with pov TEKTRO HDE350 Hydrauli 180mm	32mm 31.8mm clamp dia. ver cut off switch	
TIRES RIMS	MAXXIS Minion M346(F) M347(R) 26"x4.8" 26"x95mm Fat bike rim				
ELECTRIC TECHNOLOGY					
DISPLAY UNIT MOTOR TORQUE BATTERY RANGE PEDAL ASSIST SYSTEM THROTTLE SENSOR CLASS ACCESSORIES INCLUDED Front LED light XC-259A (powered by		Mode, Total distance odd	· · /	diagnostics	
NOTES					
BIKE WEIGHT (without battery) BATTERY WEIGHT	26.9kg (59.3 lbs) W 3.5kg (7.7 lbs)	VEIGHT CAPACITY	125kg (275 lbs)		



DISCOVERY TORNGAT RS1 GEOMETRY





ASEAT TUBE LENGTH480mmHBOTTOM BRACKET HEIGHT324mmBSEAT TUBE ANGLE73°IBOTTOM BRACKET DROP59mmCEFFECTIVE TOP TUBE LENGTH605mmICHAINSTAY LENGTH494mmDSTACK678mmKCRANK LENGTH170mmEREACH401mmIWHEELBASE1188mmFHEAD TUBE LENGTH150mmMSADDLE HEIGHT (MIN/MAX)89cm / 104cm (35" / 41")GHEAD TUBE ANGLE68.5°NSTAND OVER HEIGHT76.5cm (30.1")	FRAME SIZE	48m (19")		
© EFFECTIVE TOP TUBE LENGTH 605mm U CHAINSTAY LENGTH 494mm D STACK 678mm K CRANK LENGTH 170mm E REACH 401mm WHEELBASE 1188mm F HEAD TUBE LENGTH 150mm SADDLE HEIGHT (MIN/MAX) 89cm / 104cm (35" / 41")	A SEAT TUBE LENGTH	480mm	H BOTTOM BRACKET HEIGHT	324mm
D STACK 678mm K CRANK LENGTH 170mm E REACH 401mm L WHEELBASE 1188mm F HEAD TUBE LENGTH 150mm SADDLE HEIGHT (MIN/MAX) 89cm / 104cm (35" / 41")	B SEAT TUBE ANGLE	73°	BOTTOM BRACKET DROP	59mm
E REACH 401mm L WHEELBASE 1188mm F HEAD TUBE LENGTH 150mm M SADDLE HEIGHT (MIN/MAX) 89cm / 104cm (35" / 41")	C EFFECTIVE TOP TUBE LENGTH	605mm	J CHAINSTAY LENGTH	494mm
F HEAD TUBE LENGTH 150mm SADDLE HEIGHT (MIN/MAX) 89cm / 104cm (35" / 41")	D STACK	678mm	K CRANK LENGTH	170mm
	E REACH	401mm	U WHEELBASE	1188mm
G HEAD TUBE ANGLE 68.5° N STAND OVER HEIGHT 76.5cm (30.1")	F HEAD TUBE LENGTH	150mm	M SADDLE HEIGHT (MIN/MAX)	89cm / 104cm (35" / 41")
	G HEAD TUBE ANGLE	68.5°	N STAND OVER HEIGHT	76.5cm (30.1")

