

CORE eXtreme 3.1EZ SPECIFICATIONS

STEP THROUGH FAT TIRE ELECTRIC BIKE

FRAMESET	
FRAME	Hydroformed 6061 Aluminum step through fat bike frame with smooth welds. Balanced geometry & increased rigidity. Fender/rack mounts, internal cable routing, Electronic Access Port. Removable integrated battery with security lock.
COLOR	White and Orange
FORK	RST suspension, 75mm travel, with lockout & quick release
DRIVETRAIN	
SHIFTERS	SHIMANO 8-speed Rapidfire shift
CHAINRINGS	Zephyr 38T with Narrow Wide teeth
CHAIN	KMC X8 EPT
REAR DERAILLEUR	SHIMANO ACERA 8-speed
CASSETTE	8-speed 11-34T
COMPONENTS	
HANDLEBAR	Riser handlebar, 700mm, 30mm rise, 31.8mm dia.
GRIPS	VELO grip
STEM	Alloy 60mm with 10 degree rise, 31.8mm clamp dia.
SEAT POST	Alloy Suspension Post 30.4mm with quick release (350mm)
SADDLE	SELLE ROYAL Viento
BRAKE LEVERS	TEKTRO HD-E350
BRAKE CALIPERS	TEKTRO hydraulic disc
ROTORS	180mm
WHEELS	
TIRES	26"x4.5" KENDA Juggernaut Sport fat tires
RIMS	iGO single wall alloy with cutouts
ACCESSORIES	
INCLUDED	Front & Rear LED Lights (powered by main battery) with Reflectors Rear Cargo Rack with Increased Capacity, Pannier Ready Front & Rear Fenders Water Bottle Bosses Kickstand (removable) Wellgo Flat Grip Pedals In Frame Cable Routing

LCD Backlit, Main Power, USB charging Port, Diagnostic, Battery Status, Light Switch, Power-assist Level Selector, Walk Assist Control, Speedometer, Max Speed, Avg Speed Odometer, Trip Timer BAFANG 500W geared brushless hi-torque rear hub motor up to 80Nm 20A 48V, 12 MOSFET hi-power cut off 3000mAh Lithium-lon removable battery 48V 12Ah 576Wh 55km (34mi) * 9 Levels of power assisted pedaling Any time on demand thumb throttle
Walk Assist Control, Speedometer, Max Speed, Avg Speed Odometer, Trip Timer BAFANG 500W geared brushless hi-torque rear hub motor up to 80Nm 20A 48V, 12 MOSFET hi-power cut off 3000mAh Lithium-Ion removable battery 48V 12Ah 576Wh 55km (34mi) * 9 Levels of power assisted pedaling
BAFANG 500W geared brushless hi-torque rear hub motor up to 80Nm 20A 48V, 12 MOSFET hi-power cut off 3000mAh Lithium-Ion removable battery 48V 12Ah 576Wh 55km (34mi) * 9 Levels of power assisted pedaling
up to 80Nm 20A 48V, 12 MOSFET hi-power cut off 3000mAh Lithium-Ion removable battery 48V 12Ah 576Wh 55km (34mi) * 9 Levels of power assisted pedaling
20A 48V, 12 MOSFET hi-power cut off 3000mAh Lithium-Ion removable battery 48V 12Ah 576Wh 55km (34mi) * 9 Levels of power assisted pedaling
3000mAh Lithium-Ion removable battery 48V 12Ah 576Wh 55km (34mi) * 9 Levels of power assisted pedaling
48V 12Ah 576Wh 55km (34mi) * 9 Levels of power assisted pedaling
12Ah 576Wh 55km (34mi) * 9 Levels of power assisted pedaling
576Wh 55km (34mi) * 9 Levels of power assisted pedaling
55km (34mi) * 9 Levels of power assisted pedaling
9 Levels of power assisted pedaling
Any time on demand thumb throttle
Electronic 32 pulse cadence sensor Integrated into the bottom bracket
Class2 **
110/220V Smart charger, LED status, CUL, 2A
46cm (18") Step Through accommodates a rider from 5' to over 5'6"
74.5cm / 94cm (29.3" / 37")
30.7kg (67.7 lbs)
3.3kg (7.3 lbs)
100 kg (220 lbs)

^{*}Actual range may vary depending on Ah of battery rider weight and other riding conditions.

Class 1 - Pedal assist motor with maximum assisted speed 32km/h (20mph)
Class 2 - Pedal assist motor and throttle with maximum assisted speed 32km/h (20mph)
Class 3 - Throttle and/or pedal assist motor with maximum assisted speed 45km/h (28mph)
all classes allow a maximum motor power of 750W(US) or 500W(Canada)

This bike is sold factory configured to CLASS 2 specifications.

Tool Kit Battery Charger

^{**}electric bike class regulation: