



ETEC Lub 4T 10W-30



Lubricant for HONDA motorbikes

100% Synthetic

TYPE OF USE

100% Synthetic high performance lubricant specially designed for HONDA motorbikes : street and road bikes, trails, off-road bikes, enduro,..., fitted with 4 stroke engines, integrated gearbox or not, wet or dry clutch; engines requiring a low viscosity grade, engines meeting Euro 2 or Euro 3 emission regulation, fitted with exhaust gas after treatment systems : catalytic converters, air injection into exhaust pipe,...

Other uses : street bikes without catalytic converter, scooters, maxi-scooters,...

Must be used only when manufacturers recommend this type of lubricant. When in doubt, always refer to the owner's manual.

PERFORMANCES

APPROVALS

Honda Japan under N° EU MOT 2009-00127
JASO MA under N° M033MOT082

STANDARD

API SJ

High performance engine oil developed in Japan with HONDA R&D engineers in order to meet the most stringent requirements of HONDA motorbikes.

100% Synthetic lubricant, result of the research and development between MOTUL and HONDA :

- Viscosity grade 30 at high temperature with dedicated technology, for improved fuel consumption of HONDA motorbikes and therefore CO₂ emission reduction. Provides oil consumption reduction.
- Low Phosphorus and Sulfur content for better operating conditions and duration of catalytic converters required to meet the latest emission regulations.
- Viscosity grade 10W at cold temperature for better engine wear protection during cold start and optimal anti-wear protection to ensure gears life time.
- Increase oil film shear resistance at high temperature for better gearbox protection and smoother gearshift.
- Specific additivation for perfect metallic material compatibility with HONDA gearboxes and wet clutches design to insure optimal protection.
- JASO MA approved to guarantee a perfect lock up of wet clutch.

RECOMMENDATION

Drain interval: refer to manufacturers' recommendations and tune to your own use.

Can be mixed with synthetic or mineral oils.

PROPERTIES

Viscosity grade	SAE J 300	10W-30
Density at 20°C (59°F)	ASTM D1298	0.856
Viscosity at 40°C (104°F)	ASTM D445	65.6 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	10.1 mm ² /s
Viscosity index	ASTM D2270	139
Pour point	ASTM D97	-30°C / -22°F
Flash point	ASTM D92	240°C / 464°F
TBN	ASTM D2896	8.2 mg KOH/g

Nous nous réservons le droit de modifier les caractéristiques générales de nos produits pour faire bénéficier notre clientèle de l'évolution de la technique.

Les spécifications de nos produits ne sont définitives qu'à compter de la commande laquelle est soumise à nos conditions générales de vente et de garantie.

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel : 33 1 48 11 70 00 - Fax : 33 1 48 33 28 79. Web Site: www.motul.fr