



INBOARD TECH 4T 10W-40

Oil for Marine engines

**Inboard 4 stroke Diesel engines
supercharged or turbocharged**

Technosynthese®

TYPE OF USE

All recreational and professional 4 stroke engines fitted on boats, along coast or on rivers.
Latest generation Diesel inboard engines, supercharged, turbocharged or naturally aspirated, direct injection "Common rail" or "unit pump injector" type, running with low/medium Sulphur content fuels up to 1%: BAUDOUIN, CATERPILLAR, CUMMINS, IVECO, LOMBARDINI, MERCUISER, MTU, NANNI, MAN, PERKINS, VETUS-DEUTZ, VOLKSWAGEN, VOLVO PENTA, YAMAHA, YANMAR...
Gasoline Inboard engines: CRUSADER, MERCUISER, VOLVO PENTA, YAMAHA...
Also suitable for invertors (HURTH, TECHNODRIVE...) according to manufacturer recommendations.

PERFORMANCES

STANDARDS	Diesel:	ACEA E7 (E5 and E3), API CI-4 / CH-4 / CG-4 / CF-4 (exceeds API CD – CE – CF)
	Gasoline:	API SG, SF
SPECIFICATIONS		CATERPILLAR ECF-1, CUMMINS 20071-20072-20076-20077-20078, MAN M 3275, Global DHD-1, MTU Type II, VOLVO VDS-3 / VDS-2

Technosynthese® lubricant reinforced with synthetic base stocks providing at the same time outstanding resistance at high temperature, easier flowing at cold temperature and longer oil life time.
Protects against corrosion due to moisture and salt, neutralizes acid combustion residues from fuels, increases engine life time.
Prevents emulsion with water.
Reinforced in detergents and dispersants to guaranty engine cleanliness and prevents from deposit build ups on pistons and into engine sump.
SAE 10W grade at cold temperature drastically improves wear protection at cranking and fuel economy when frequent startups.
Anti-friction properties to minimize fuel consumption.

RECOMMENDATIONS

Oil change: According to manufacturers' recommendations ant to be adjusted according to use and oil test results.
Can be mixed with synthetic or mineral oils.

PROPERTIES

Viscosity grade	SAE J300	10W-40
Density at 20°C (68°F)	ASTM D1298	0.872
Viscosity at 40°C (104°F)	ASTM D445	101.0 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	14.9 mm ² /s
Viscosity index	ASTM D2270	154
Flash point	ASTM D92	230°C / 446°F
Pour point	ASTM D97	-30°C / -22°F
TBN	ASTM D 2896	11.6 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty. – Made in France

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 – Tel: 33 1 48 11 70 00 – Fax: 33 1 48 33 28 79. Web Site: www.motul.com

11/17