



# Scooter Power 4T 10W-30 MB

**4 Stroke engine oil Scooters and Maxi Scooters**

**100% Synthetic – JASO MB – Low Emissions**

## TYPE OF USE

Specifically designed for powerful and recent scooters and maxi-scooters fitted with 4 stroke engines, any engine displacement, with or without catalytic converters, without wet clutch.

All scooters used for daily commuting and urban riding.

Suitable for all type of gasoline fuels, leaded or unleaded, with or without Ethanol, biofuels.

## PERFORMANCES

STANDARDS                      API SN / SM / SL / SJ  
SPECIFICATIONS              JASO MB under N° M033MOT170

100% Synthetic engine oil, reduces engine internal friction, improves mechanical efficiency.

Improved oil resistance for excellent high temperature protection particularly indicated for city use: full load during long periods and stop & go use with difficult cooling.

Approved JASO MB lubricant ensures optimal scooter performance and fuel economy. Compared to a JASO MA lubricant, JASO MB lubricant provides real energy saving performance, up to 3% gains in fuel consumption compared to a 20W-50 JASO MA lubricant and up to 2% savings compared to a 10W-30 JASO MA oil, in urban/city conditions and start & stop driving mode.

By reducing fuel consumption, this JASO MB lubricant contributes to reducing greenhouse gases relative to CO<sub>2</sub> emissions and allows reduction of polluting emissions (Low Emissions).

The SAE 10W-30 viscosity grade corresponds to the most recent manufacturers' recommendations, especially HONDA for some of their models, and improves engine starts when cold and therefore reduces wear.

Very low volatility to reduce oil consumption.

Ensures engine cleanliness, detergent and dispersant properties, and resistance to viscosity increase from unburned deposits produced by the engine. High ageing resistance.

Anti-oxidation, Anti-corrosion, Anti-foam properties.

## RECOMMENDATION

Drain interval: refer to manufacturers' recommendations and tune to your own use.

Can be mixed with synthetic or mineral oils.

## PROPERTIES

Viscosity grade	SAE J 300	<b>10W-30</b>
Density at 20°C (68°F)	ASTM D1298	0.851
Viscosity at 40°C (104°F)	ASTM D445	72.8 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	10.8 mm <sup>2</sup> /s
Viscosity Index	ASTM D2270	141
Pour point	ASTM D97	-34°C / -29°F
Flash point	ASTM D92	228°C / 442°F
TBN	ASTM D2896	7.1 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 Aubervilliers Cedex - BP 94 – FRANCE. Tel: 33 1 48 11 70 00 – Fax: 33 1 48 33 28 79 – Web Site: [www.motul.com](http://www.motul.com)

01/20