



TRANSLUBE

Lubricant for Outboard Propeller Box

Anti-emulsion

TYPE OF USE

Anti-emulsion gearing oil, specially formulated to lubricate outboard propeller boxes :
EVINRUDE, FORCE, JOHNSON, MARIMER, MERCURY, SEAGULL, SELVA, SUZUKI, TOHATSU,
YAMAHA.

PERFORMANCES

Meets US STEEL 224 specification requirements.
High lubricating power to reduce frictions and wear.
Perceptibly reduces box working noise.
Extreme pressure, anti-foam, anti-corrosion.
Good anti-emulsion properties.

RECOMMENDATIONS

Drain period : according to manufacturers' recommendations and to be adapted according to your own use.

A draining once a year is recommended in any case.

Not to be used in electrical reverse gear system.

PROPERTIES

Viscosity grade	SAE J 300	90
Density at 20°C (68°F)	ASTM D1298	0.883
Viscosity at 40°C (104°F)	ASTM D445	150 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	15 mm ² /s
Viscosity index VIE	ASTM D2270	100
Flash point	ASTM D92	252°C / 485°F
Pour point	ASTM D97	-12°C / -53°F
Desemulsion	ASTM D2711	(free water) 47.6 ml
Emulsion		none

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - TEL : 33 1 48 11 70 00 - FAX : 33 1 48 33 28 79 - Web Site : www.motul.fr

09/10