



## Industrial, Heavy Insulated High Temperature Heating Tape

**HTS/Amptek® Heavy Industrial Fabric Duo-Tape® Features:**

- For use on Conductive (Metal) Surfaces.
- Longer Length AMOX™ 1200°F (649°C) High Temp Construction.
- AWD = Leads one end  
AWM = Leads each end.
- 4 ft. Hi Temperature Sleeved Leads with Lug Terminals.
- Medium Watt Density 8.7 W/in<sup>2</sup> (1.3) W/cm<sup>2</sup>

**Do not use with moisture:**  
Contact HTS/Amptek® for optional configurations, Watts and Volts.

Cut-Away Configuration	Max Temp	Size		Watts	Leads (1.2M)	Cat. No. (120V)	Cat. No. (240V)	USD		
		Imperial	Metric							
<b>AMOX™ High Temp. (1200cF/ 650cC) Heavy Insulated Heating Tape, Medium Watt Density 8.67 WSI</b>										
		0.5' x 4'	1.3 x 120 cm	208	One End	AWD -051-040	AWD -052-040	198.00		
		0.5' x 6'	1.3 x 180 cm	312	One End	AWD -051-060	AWD -052-060	203.00		
		0.5' x 8'	1.3 x 240 cm	416	One End	AWD -051-080	AWD -052-080	225.00		
		0.5' x 10'	1.3 x 300 cm	520	One End	AWD -051-100	AWD -052-100	245.00		
		0.5' x 12'	1.3 x 360 cm	624	Each End	AWM-051-120	AWD-052-120	268.00		
		0.5' x 16'	1.3 x 480 cm	832	Each End	AWM-051-160	AWD-052-160	321.00		
		0.5' x 20'	1.3 x 600 cm	1040	Each End	AWM-051-200	AWD-052-200	374.00		
		0.5' x 24'	1.3 x 720 cm	1248	Each End		AWM-052-240	433.00		
		0.5' x 32'	1.3 x 960 cm	1664	Each End		AWM-052-320	499.00		
		1.0' x 4'	2.5 x 120 cm	416	One End	AWD -551-040	AWD -552-040	239.00		
		1.0' x 6'	2.5 x 180 cm	624	One End	AWD -551-060	AWD -552-060	259.00		
		1.0' x 8'	2.5 x 240 cm	832	One End	AWD -551-080	AWD -552-080	283.00		
		1.0' x 10'	2.5 x 300 cm	1040	One End	AWD -551-100	AWD -552-100	307.00		
		1.0' x 12'	2.5 x 360 cm	1248	Each End	AWM-551-120	AWD -552-120	336.00		
		1.0' x 16'	2.5 x 480 cm	1664	Each End	AWM-551-160	AWD-552-160	383.00		
		1.0' x 20'	2.5 x 600 cm	2080	Each End	AWM-551-200	AWD-552-200	432.00		
		1.0' x 24'	2.5 x 720 cm	2498	Each End		AWM-552-240	493.00		
		1.0' x 32'	2.5 x 960 cm	3328	Each End		AWM-552-320	600.00		
		<b>MEDIUM WATT DENSITY</b>								

## Industrial, Silicone Rubber Extruded Heating Tape



**HTS/Amptek® SRD Heavy Industrial Silicone Rubber Duo-Tape® Features:**

- For use on Conductive (Metal) Surfaces.
- Silicone Rubber, longer length, Extruded construction.
- For use in areas with Moisture present.
- 4 ft. Silicone Rubber Sleeved Leads on One End.
- Low Watt Density 2.5 W/in<sup>2</sup> (.388) W/cm<sup>2</sup>

**No connector provided:**  
Contact HTS/Amptek® for optional configurations, Watts and Volts.

**Longer lead wires:** 48' Standard lead wire length for all Tapes. For longer lengths contact HTS/Amptek®

Cut-Away Configuration	Max Temp	Size		Watts	Leads (1.2M)	Cat. No. (120V)	Cat. No. (240V)	USD
		Imperial	Metric					
<b>AMOX™ High Temp. (450cF/ 232cC) Heavy Insulated Heating Tape, Low Watt Density 2.5 WSI</b>								
		0.5' x 6'	1.3 x 180 cm	90	One End	SRD-051-060	SRD-052-060	239.00
		0.5' x 8'	1.3 x 240 cm	120	One End	SRD-051-080	SRD-052-080	261.00
		0.5' x 10'	1.3 x 300 cm	150	One End	SRD-051-100	SRD-052-100	275.00
		0.5' x 12'	1.3 x 360 cm	180	One End	SRD-051-120	SRD-052-120	304.00
		0.5' x 16'	1.3 x 480 cm	240	One End	SRD-051-160	SRD-052-160	360.00
		0.5' x 20'	1.3 x 600 cm	300	One End	SRD-051-200	SRD-052-200	437.00
		0.5' x 24'	1.3 x 720 cm	360	One End	SRD-051-240	SRD-052-240	535.00
		0.5' x 32'	1.3 x 960 cm	480	One End	SRD-051-320	SRD-052-320	631.00
		0.5' x 42'	1.3 x 1280 cm	630	One End	SRD-051-420	SRD-052-420	709.00
		0.5' x 52'	1.3 x 1580 cm	780	One End	SRD-051-520	SRD-052-520	818.00
		1.0' x 6'	2.5 x 180 cm	180	One End	SRD-101-060	SRD-102-060	316.00
		1.0' x 8'	2.5 x 240 cm	240	One End	SRD-101-080	SRD-102-080	350.00
		1.0' x 10'	2.5 x 300 cm	300	One End	SRD-101-100	SRD-102-100	363.00
		1.0' x 12'	2.5 x 360 cm	360	One End	SRD-101-120	SRD-102-120	393.00
		1.0' x 16'	2.5 x 480 cm	480	One End	SRD-101-160	SRD-102-160	440.00
		1.0' x 20'	2.5 x 600 cm	600	One End	SRD-101-200	SRD-102-200	489.00
		1.0' x 24'	2.5 x 720 cm	720	One End	SRD-101-240	SRD-102-240	578.00
		1.0' x 32'	2.5 x 960 cm	960	One End		SRD-102-320	731.00
		1.0' x 42'	2.5 x 1280 cm	1260	One End		SRD-102-420	818.00
		1.0' x 52'	2.5 x 1580 cm	1560	One End		SRD-102-520	938.00
<b>LOW WATT DENSITY</b>								

**Special Length, Width, Watts or Volts:** Heating tapes may be fabricated to operate on all common voltages, from 12 to 480, and with watt densities from 0.1 to 8 WSI. Contact HTS/Amptek® for knowledgeable design assistance. info@heatingtapes.com

**HTS/Amptek Company**  
4727 S Main St.  
Stafford, TX 77497 USA  
+1.281.340.9800