



ROTAX® ENGINE	900 ACE	900 ACE Turbo	
Engine details	Liquid-cooled, four- stroke D.O.H.C.	Liquid-cooled, four- stroke D.O.H.C., turbocharged	
Cylinders	3	3	
Displacement	899.0 cc	899.0 cc	
Bore	74 mm	74 mm	
Stroke	69.7 mm	69.7 mm	
Maximum engine speed	7250 RPM	7750 RPM	
Carburation	EFI	EFI	
Recommended fuel type	Unleaded	Unleaded	
Minimum octane	95	95	
Fuel tank	42	42 liters	

Black	
3240 mm	
1200 mm	
1500 mm	
996 mm	
500 mm	
3923 mm	
44 mm PowderMax	

Tactical Grey/Viper Red/

## **POWERTRAIN**

Gearbox	2F/N/R with push-button reverse	
Drive clutch type	pDrive with slider shoes (900 ACE) pDrive (900 ACE Turbo)	
Driven clutch type	QRS	
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder	

## **SUSPENSION**

Front suspension	LFS with bended lower A-Arms
Front shock	HPG 36
Rear suspension	EasyRide with adjustment
Center shock	HPG 36
Rear shock	HPG 36

## **FEATURES**

Frame	Radien-X
Skis	Blade DS+
Seating	Modular, 1+1
Handlebar	U-type steel with hooks, low grab handle
Riser block height	145 mm
Starter	Electric
Reverse	Electromechanical
Heated throttle lever	Standard

Heated grips	Standard	
Gauge	7.2-in. wide digital display	
Windshield	Extra high with side deflectors	
Hitch	Standard	
Visor Plug front / rear	Front	
USB power outlet	Front	
Air radiator with fan	Yes	
LinQ attachment	Multi-LinQ plate	
	Traiti Lina piate	



<sup>\*</sup> Vehicle overall length without snowflap.