

MY24 TRAXTER X MR HD10



 Hyper Silver & Legion Red

ENGINE

| | |
|----------------------|--|
| Type | 61 kW (82 hp) / 69 lb-ft, Rotax® 976 cc, V-twin, liquid cooled with strategically positioned engine air intake |
| Fuel Delivery System | Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI) |
| Transmission | PRO-TORQ CVT Transmission with Quick Response System (QRS), Electronic Drive Belt Protection, lower gearing ratio and high airflow ventilation with strategically positioned CVT air intake and exhaust Extra-L / H / N / R / P |
| Drive Train | Selectable Turf Mode / 2WD / 4WD TRAIL / 4WD MUD with exclusive Smart-Lok technology |
| Driving Assistance | Electronic Hill Descent Control ECO™ / ECO™ Off / Work modes Brake holding mechanism |
| Power Steering | Dynamic Power Steering (DPS™) |

SUSPENSIONS

| | |
|------------------|---|
| Front Suspension | Arched double A-arm with swaybar / 12 in. (30.5 cm) travel |
| Front Shocks | Twin tube gas charged shocks |
| Rear Suspension | Arched TTA with external sway bar / 12 in. (30.5 cm) travel |
| Rear Shocks | Twin tube gas charged shocks |

TIRES / WHEELS

| | |
|--------------------|---|
| Front & Rear Tires | XPS Swamp Force 30 x 9 / 11 x 14 in. (76.2 x 22.9 / 27.9 x 35.6 cm) |
| Wheels | 14 in. (35.6 cm) cast-aluminum |

BRAKES

| | |
|-------|---|
| Front | Dual 220 mm disc brakes with hydraulic twin-piston calipers |
| Rear | Dual 220 mm disc brakes with hydraulic single-piston calipers |

HIGHLIGHTS

- Smart-Lok front differential
- Strategically positioned engine air intake and CVT inlet / outlet
- Brake holding mechanism
- VERSA-PRO bolster bench seat, reinforced seat skin featuring X package trims and adjustable driver seat
- 7.6 in. (19.3 cm) digital display with keypad
- 64 in. (162.5 cm) wide with Arched A-arm
- LED Signature
- 30 in. (76.2 cm) XPS Swamp Force tires
- 4,500-lb (2,041 kg) winch
- Heavy-duty front steel bumper
- Aluminum rock slider
- HMWPE full skid plate
- Horn & side mirrors

DIMENSIONS / CAPACITIES

| | |
|------------------------|---|
| Cage | Profiled cage. ROPS approved |
| Estimated Dry Weight * | 1,746 lb (792 kg) |
| L x W x H | 129.4 x 64 x 82 in. (328.6 x 162.6 x 208.3 cm) |
| Wheelbase | 83 in. (211.5 cm) |
| Ground Clearance | 15 in. (38.1 cm) |
| Cargo Box Dimensions | 38 x 54.5 x 12 in. (96.5 x 138.4 x 30.5 cm) |
| Cargo Box Capacity | 1,000 lb (454 kg) |
| Power tilt bed | N/A |
| Tailgate Load Capacity | 250 lb (113.4 kg) |
| Storage Capacity | Total: 16.2 gal (61.3 L) |
| Towing Capacity | 2,500 lb (1,136 kg) |
| Payload Capacity | 1,500 lb (680 kg) |
| Fuel Capacity | 10.6 gal (40 L) |
| Person Capacity | 3 |

FEATURES

| | |
|-----------------|---|
| Gauge | 7.6 in. (19.3 cm) wide digital display with keypad |
| Battery | 12-V (30 amp/h) |
| Magneto | 650-W |
| Instrumentation | DC outlet (10-A) USB Port (10-A) x 2 |
| Lighting | Front lighting output 140 W LED signature LED tail lights |
| Winch | Relocated 4,500-lb (2,041 kg) winch with synthetic rope and roller fairlead |
| Seat | VERSA-PRO bolster bench seats with passenger seats flipping up, adjustable driver seat, underside hooks, reinforced seat skin featuring X package trims |
| Steering Wheel | Adjustable tilt steering |
| Protection | Heavy-duty front steel bumper HMWPE full skid plate Aluminum rock sliders Mudguards |
| Hitch Type | 2-in hitch receiver |

WARRANTY

| | |
|------------------|-----------------------------|
| Factory warranty | 2-year BRP limited warranty |
|------------------|-----------------------------|



REQUEST A QUOTE



©2024 Bombardier Recreational Products Inc. (BRP). All rights reserved. TM, ® and the BRP logo are trademarks of BRP or its affiliates. *Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrive GmbH. ‡All other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all SSV drivers take a training course. For safety and training information, see your dealer. SSVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. SSVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any SSV not specifically designated for such use. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Some models depicted may include optional equipment.