


Model M122K - 12"



Mounting Feet

- Lowest profile high performance reversibles on the market
- Sealed motor tested in accordance with DIN EN 60529, dust and water proof to IP68
- Quiet, reversible S-blade design
- All glass-filled nylon construction
- Includes (4) 90° mounting feet
- Includes locking mating pigtail connector and rubber spacers for proper spacing off of heat exchanger
- Recommended wire harnesses* (sold separately)
 - Part No. MFA100 (adjustable thermostat)
 - Part No. MFA102 (185° temperature switch)
 - Part No. MFA103 (195° temperature switch)
- Optional brackets* (sold separately)
 - Part No. MFA104 (metal bracket strips)
 - Part No. MFA105 (aluminum brackets)



Fan Harness

Pigtail

TYPICAL PERFORMANCE DATA		
M122K 12" LP REVERSIBLE CHAMPION 12V 225W		
Static In H ₂ O	Total Flow CFM	13.5 VDC AMPS
0.00	1548	13.3
0.10	1464	13.6
0.20	1380	13.9
0.30	1245	14.0
0.40	1139	13.9
0.50	995	14.1
0.60	851	14.0
0.70	613	13.7
0.80	346	13.3
0.90	232	13.9
1.10	STALL @ 1.10"	15.6

