


PCIe x8 Gen 3 Quad-port Cable Adapter

Part Number: OSS-PCIe-HIB38-x8-QUAD

FEATURES

- Operates at up to 64Gb/s at PCIe Gen 3 speeds
- I/O expansion requires no additional software
- Card supports 4 modes: host mode, target mode, dual host



PCIe x8 Gen 3 quad-port, switch-based cable adapter with DMA controller and optional NT ports. The cable adapter operates in I/O expansion or with a DIP switch setting change.

SPECIFICATIONS

Form Factor	Dual width PCIe add-in card
Dimensions	5.85 x 4.00" (14.85 x 10.16 cm)
Connectors	Quad PCIe x8 cable connectors PCIe x16 edge connector
Operating Temperature	0° C to +50° C
Storage Temperature	-40° C to +85° C
Operating Humidity	10% to 90% relative humidity non-condensing
Storage Humidity	5% to 95% relative humidity non-condensing
PCB	PCI Express add-in card standard Thickness .063 +/-0.008 inch (1.6 +/- 0.2mm)
PCIe Switch	<ul style="list-style-type: none"> PLX PEX8733 8.0 GT/s 32-Lane PCI Express Gen 3 Switch DMA controller
Spread Spectrum	Supports spread spectrum isolation
Agency Compliance	FCC Class A CE RoHS

Block Diagram

