

HOT DIP GALVANIZED

Capacity	81.7 cu ft/ 10.2 liters	101.3 cu ft/ 12.9 liters	117.8 cu ft/ 15 liters	120.1 cu ft/ 15.3 liters	133.5 cu ft/ 17 liters	85.0 cu ft/ 13 liters
Service Pressure	3,442 psi/ 237 bar	3,442 psi/ 237 bar	3,442 psi/ 237 bar	3,442 psi/ 237 bar	3,442 psi/ 237 bar	2640 psi/182 bar (2400+ 10%)
Buoyancy (Full)	-8.05 lbs/ -3.65 kg	-8.41 lbs/ -3.81 kg	-9.12 lbs/ -4.13 kg	-8.82 lbs/ -4.13 kg	-9.08 lbs/ 0.66 kg	-3.80 lbs/ -1.72 kg
Buoyancy (500 psi)	-1.74 lbs/ -0.79 kg	-0.59 lbs/ -0.15 kg	0.35 lbs/ 0.16 kg	0.65 lbs/ 0.29 kg	1.45 lbs/ 0.66 kg	2.32 lbs/ 1.05 kg
Empty Weight	28.3 lbs/ 13.0 kg	34.0 lbs/ 15.6 kg	37.6 lbs/ 17.7 kg	39.2 lbs/ 17.8 kg	42.4 lbs/ 19.4 kg	31.2 lbs/ 14.2 kg
Outside Dia.	7.25 in/ 184 mm	7.25 in/ 184 mm	8.0 in/ 203 mm	7.25 in/ 184 mm	8.0 in/ 203 mm	7.0 in/ 178 mm
Cylinder Ht.	20.8 in/ 53 cm	25.3 in/ 64.5 cm	24.2 in/ 61.5 cm	29.1 in/ 74.5 cm	26.85 in/ 68 cm	25.98 in/ 66.0 cm