

<b>Capacity</b>	50 cu ft/7.8 liters	85 cu ft/13.0 liters	95 cu ft/15 liters	108 cu ft/17 liters	120 cu ft/19 liters
<b>Service Pressure</b>	2640 psi/182 bar (2400+ 10%)	2640 psi/182 bar (2400+ 10%)	2640 psi/182 bar (2400+ 10%)	2640 psi/182 bar (2400+ 10%)	2640 psi/182bar (2400+ 10%)
<b>Buoyancy (Full)</b>	-2.4 lbs/-1.1 kg	-3.8 lbs/-1.72 kg	-5.4 lbs/-2.44 kg	-5.0 lbs/-2.28 kg	-4.9 lbs/-1.4 kg
<b>Buoyancy (500 psi)</b>	1.2 lbs/0.56 kg	2.3 lbs/1.05 kg	1.7 lbs/0.77 kg	3.0 lbs/1.35 kg	4.1 lbs/1.86 kg
<b>Empty Weight</b>	18.9 lbs/8.6 kg	31.2 lbs/14.2 kg	37.2 lbs/16.9 kg	41 lbs/18.6 kg	44.9 lbs/20.4 kg
<b>Outside Dia.</b>	5.51 in/14 cm	7.01 in/17.8 cm	8.02 in/20.4 cm	8.02 in/20.4 cm	6.84 in/17.4 cm
<b>Cylinder Ht.</b>	25.2 in/64 cm	25.98 in/66 cm	23.8 in/60.5 cm	26.8 in/68 cm	29.3 in/74.4 cm